



OpenShift Container Platform 4.17

Console APIs

Reference guide for console APIs

OpenShift Container Platform 4.17 Console APIs

Reference guide for console APIs

Legal Notice

Copyright © 2024 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document describes the OpenShift Container Platform console API objects and their detailed specifications.

Table of Contents

CHAPTER 1. CONSOLE APIS	4
1.1. CONSOLECLIDOWNLOAD [CONSOLE.OPENSIFT.IO/V1]	4
1.2. CONSOLEEXTERNALLOGLINK [CONSOLE.OPENSIFT.IO/V1]	4
1.3. CONSOLELINK [CONSOLE.OPENSIFT.IO/V1]	4
1.4. CONSOLENOTIFICATION [CONSOLE.OPENSIFT.IO/V1]	4
1.5. CONSOLEPLUGIN [CONSOLE.OPENSIFT.IO/V1]	4
1.6. CONSOLEQUICKSTART [CONSOLE.OPENSIFT.IO/V1]	4
1.7. CONSOLESAMPLE [CONSOLE.OPENSIFT.IO/V1]	5
1.8. CONSOLEYAMLSAMPLE [CONSOLE.OPENSIFT.IO/V1]	5
CHAPTER 2. CONSOLECLIDOWNLOAD [CONSOLE.OPENSIFT.IO/V1]	6
2.1. SPECIFICATION	6
2.1.1. .spec	7
2.1.2. .spec.links	7
2.1.3. .spec.links[]	7
2.2. API ENDPOINTS	8
2.2.1. /apis/console.openshift.io/v1/consoleclidownloads	8
2.2.2. /apis/console.openshift.io/v1/consoleclidownloads/{name}	10
2.2.3. /apis/console.openshift.io/v1/consoleclidownloads/{name}/status	13
CHAPTER 3. CONSOLEEXTERNALLOGLINK [CONSOLE.OPENSIFT.IO/V1]	17
3.1. SPECIFICATION	17
3.1.1. .spec	18
3.2. API ENDPOINTS	19
3.2.1. /apis/console.openshift.io/v1/consoleexternalloglinks	20
3.2.2. /apis/console.openshift.io/v1/consoleexternalloglinks/{name}	22
3.2.3. /apis/console.openshift.io/v1/consoleexternalloglinks/{name}/status	25
CHAPTER 4. CONSOLELINK [CONSOLE.OPENSIFT.IO/V1]	28
4.1. SPECIFICATION	28
4.1.1. .spec	28
4.1.2. .spec.applicationMenu	29
4.1.3. .spec.namespaceDashboard	30
4.1.4. .spec.namespaceDashboard.namespaceSelector	30
4.1.5. .spec.namespaceDashboard.namespaceSelector.matchExpressions	31
4.1.6. .spec.namespaceDashboard.namespaceSelector.matchExpressions[]	31
4.2. API ENDPOINTS	32
4.2.1. /apis/console.openshift.io/v1/consolelinks	32
4.2.2. /apis/console.openshift.io/v1/consolelinks/{name}	34
4.2.3. /apis/console.openshift.io/v1/consolelinks/{name}/status	37
CHAPTER 5. CONSOLENOTIFICATION [CONSOLE.OPENSIFT.IO/V1]	41
5.1. SPECIFICATION	41
5.1.1. .spec	42
5.1.2. .spec.link	42
5.2. API ENDPOINTS	43
5.2.1. /apis/console.openshift.io/v1/consolenotifications	43
5.2.2. /apis/console.openshift.io/v1/consolenotifications/{name}	45
5.2.3. /apis/console.openshift.io/v1/consolenotifications/{name}/status	48
CHAPTER 6. CONSOLEPLUGIN [CONSOLE.OPENSIFT.IO/V1]	52
6.1. SPECIFICATION	52

6.1.1. .spec	53
6.1.2. .spec.backend	53
6.1.3. .spec.backend.service	54
6.1.4. .spec.i18n	55
6.1.5. .spec.proxy	55
6.1.6. .spec.proxy[]	55
6.1.7. .spec.proxy[].endpoint	56
6.1.8. .spec.proxy[].endpoint.service	57
6.2. API ENDPOINTS	57
6.2.1. /apis/console.openshift.io/v1/consoleplugins	58
6.2.2. /apis/console.openshift.io/v1/consoleplugins/{name}	60
CHAPTER 7. CONSOLEQUICKSTART [CONSOLE.OPENSIFT.IO/V1]	64
7.1. SPECIFICATION	64
7.1.1. .spec	65
7.1.2. .spec.accessReviewResources	66
7.1.3. .spec.accessReviewResources[]	66
7.1.4. .spec.tasks	67
7.1.5. .spec.tasks[]	67
7.1.6. .spec.tasks[].review	68
7.1.7. .spec.tasks[].summary	69
7.2. API ENDPOINTS	69
7.2.1. /apis/console.openshift.io/v1/consolequickstarts	70
7.2.2. /apis/console.openshift.io/v1/consolequickstarts/{name}	71
CHAPTER 8. CONSOLESAMPLE [CONSOLE.OPENSIFT.IO/V1]	75
8.1. SPECIFICATION	75
8.1.1. .spec	76
8.1.2. .spec.source	78
8.1.3. .spec.source.containerImport	78
8.1.4. .spec.source.containerImport.service	79
8.1.5. .spec.source.gitImport	79
8.1.6. .spec.source.gitImport.repository	80
8.1.7. .spec.source.gitImport.service	81
8.2. API ENDPOINTS	81
8.2.1. /apis/console.openshift.io/v1/consolesamples	82
8.2.2. /apis/console.openshift.io/v1/consolesamples/{name}	83
CHAPTER 9. CONSOLEYAMLSAMPLE [CONSOLE.OPENSIFT.IO/V1]	87
9.1. SPECIFICATION	87
9.1.1. .spec	88
9.1.2. .spec.targetResource	89
9.2. API ENDPOINTS	89
9.2.1. /apis/console.openshift.io/v1/consoleyaml samples	90
9.2.2. /apis/console.openshift.io/v1/consoleyaml samples/{name}	91

CHAPTER 1. CONSOLE APIS

1.1. CONSOLECLIDOWNLOAD [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleCLIDownload is an extension for configuring openshift web console command line interface (CLI) downloads. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

1.2. CONSOLEEXTERNALLOGLINK [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleExternalLogLink is an extension for customizing OpenShift web console log links. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

1.3. CONSOLELINK [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleLink is an extension for customizing OpenShift web console links. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

1.4. CONSOLENOTIFICATION [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleNotification is the extension for configuring openshift web console notifications. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

1.5. CONSOLEPLUGIN [CONSOLE.OPENSIFT.IO/V1]

Description

ConsolePlugin is an extension for customizing OpenShift web console by dynamically loading code from another service running on the cluster. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).

Type

object

1.6. CONSOLEQUICKSTART [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleQuickStart is an extension for guiding user through various workflows in the OpenShift web console. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

1.7. CONSOLESAMPLE [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleSample is an extension to customizing OpenShift web console by adding samples. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).

Type

object

1.8. CONSOLEYAMLSAMPLE [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleYAMLSample is an extension for customizing OpenShift web console YAML samples. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

CHAPTER 2. CONSOLECLIDOWNLOAD [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleCLIDownload is an extension for configuring openshift web console command line interface (CLI) downloads. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

Required

- **spec**

2.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata
spec	object	ConsoleCLIDownloadSpec is the desired cli download configuration.

2.1.1. .spec

Description

ConsoleCLIDownloadSpec is the desired cli download configuration.

Type

object

Required

- **description**
- **displayName**
- **links**

Property	Type	Description
description	string	description is the description of the CLI download (can include markdown).
displayName	string	displayName is the display name of the CLI download.
links	array	links is a list of objects that provide CLI download link details.
links[]	object	

2.1.2. .spec.links

Description

links is a list of objects that provide CLI download link details.

Type

array

2.1.3. .spec.links[]

Description

Type

object

Required

- **href**

Property	Type	Description
href	string	href is the absolute secure URL for the link (must use https)
text	string	text is the display text for the link

2.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consoleclidownloads**
 - **DELETE**: delete collection of ConsoleCLIDownload
 - **GET**: list objects of kind ConsoleCLIDownload
 - **POST**: create a ConsoleCLIDownload
- **/apis/console.openshift.io/v1/consoleclidownloads/{name}**
 - **DELETE**: delete a ConsoleCLIDownload
 - **GET**: read the specified ConsoleCLIDownload
 - **PATCH**: partially update the specified ConsoleCLIDownload
 - **PUT**: replace the specified ConsoleCLIDownload
- **/apis/console.openshift.io/v1/consoleclidownloads/{name}/status**
 - **GET**: read status of the specified ConsoleCLIDownload
 - **PATCH**: partially update status of the specified ConsoleCLIDownload
 - **PUT**: replace status of the specified ConsoleCLIDownload

2.2.1. /apis/console.openshift.io/v1/consoleclidownloads

HTTP method

DELETE

Description

delete collection of ConsoleCLIDownload

Table 2.1. HTTP responses

HTTP code	Response body
200 - OK	Status schema

HTTP code	Reponse body
401 - Unauthorized	Empty

HTTP method**GET****Description**

list objects of kind ConsoleCLIDownload

Table 2.2. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleCLIDownloadList schema
401 - Unauthorized	Empty

HTTP method**POST****Description**

create a ConsoleCLIDownload

Table 2.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 2.4. Body parameters

Parameter	Type	Description
body	ConsoleCLIDownload schema	

Table 2.5. HTTP responses

HTTP code	Response body
200 - OK	ConsoleCLIDownload schema
201 - Created	ConsoleCLIDownload schema
202 - Accepted	ConsoleCLIDownload schema
401 - Unauthorized	Empty

2.2.2. /apis/console.openshift.io/v1/consoleclidownloads/{name}

Table 2.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleCLIDownload

HTTP method**DELETE****Description**

delete a ConsoleCLIDownload

Table 2.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 2.8. HTTP responses

HTTP code	Response body
200 - OK	Status schema
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method**GET****Description**

read the specified ConsoleCLIDownload

Table 2.9. HTTP responses

HTTP code	Response body
200 - OK	ConsoleCLIDownload schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update the specified ConsoleCLIDownload

Table 2.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 2.11. HTTP responses

HTTP code	Response body
200 - OK	ConsoleCLIDownload schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace the specified ConsoleCLIDownload

Table 2.12. Query parameters

Parameter	Type	Description
-----------	------	-------------

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 2.13. Body parameters

Parameter	Type	Description
body	ConsoleCLIDownload schema	

Table 2.14. HTTP responses

HTTP code	Response body
200 - OK	ConsoleCLIDownload schema
201 - Created	ConsoleCLIDownload schema
401 - Unauthorized	Empty

2.2.3. /apis/console.openshift.io/v1/consoleclidownloads/{name}/status

Table 2.15. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleCLIDownload

HTTP method**GET****Description**

read status of the specified ConsoleCLIDownload

Table 2.16. HTTP responses

HTTP code	Response body
200 - OK	ConsoleCLIDownload schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update status of the specified ConsoleCLIDownload

Table 2.17. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 2.18. HTTP responses

HTTP code	Response body
200 - OK	ConsoleCLIDownload schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace status of the specified ConsoleCLIDownload

Table 2.19. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 2.20. Body parameters

Parameter	Type	Description
body	ConsoleCLIDownload schema	

Table 2.21. HTTP responses

HTTP code	Response body
200 - OK	ConsoleCLIDownload schema
201 - Created	ConsoleCLIDownload schema
401 - Unauthorized	Empty

CHAPTER 3. CONSOLEEXTERNALLOGLINK [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleExternalLogLink is an extension for customizing OpenShift web console log links.
Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

Required

- **spec**

3.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata

Property	Type	Description
spec	object	ConsoleExternalLogLinkSpec is the desired log link configuration. The log link will appear on the logs tab of the pod details page.

3.1.1. .spec

Description

ConsoleExternalLogLinkSpec is the desired log link configuration. The log link will appear on the logs tab of the pod details page.

Type

object

Required

- **hrefTemplate**
- **text**

Property	Type	Description
----------	------	-------------

Property	Type	Description
hrefTemplate	string	<p>hrefTemplate is an absolute secure URL (must use https) for the log link including variables to be replaced. Variables are specified in the URL with the format <code>\${variableName}</code>, for instance, <code>\${containerName}</code> and will be replaced with the corresponding values from the resource. Resource is a pod. Supported variables are: - <code>\${resourceName}</code> - name of the resource which contains the logs - <code>\${resourceUID}</code> - UID of the resource which contains the logs - e.g. 11111111-2222-3333-4444-555555555555 - <code>\${containerName}</code> - name of the resource's container that contains the logs - <code>\${resourceNamespace}</code> - namespace of the resource that contains the logs - <code>\${resourceNamespaceUID}</code> - namespace UID of the resource that contains the logs - <code>\${podLabels}</code> - JSON representation of labels matching the pod with the logs - e.g. <code>{"key1":"value1","key2":"value2"}</code> e.g., https://example.com/logs?resourceName=\${resourceName}&containerName=\${containerName}&resourceNamespace=\${resourceNamespace}&podLabels=\${podLabels}</p>
namespaceFilter	string	<p>namespaceFilter is a regular expression used to restrict a log link to a matching set of namespaces (e.g., <code>^openshift-</code>). The string is converted into a regular expression using the JavaScript RegExp constructor. If not specified, links will be displayed for all the namespaces.</p>
text	string	text is the display text for the link

3.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consoleexternalloglinks**
 - **DELETE**: delete collection of ConsoleExternalLogLink
 - **GET**: list objects of kind ConsoleExternalLogLink
 - **POST**: create a ConsoleExternalLogLink
- **/apis/console.openshift.io/v1/consoleexternalloglinks/{name}**
 - **DELETE**: delete a ConsoleExternalLogLink
 - **GET**: read the specified ConsoleExternalLogLink
 - **PATCH**: partially update the specified ConsoleExternalLogLink
 - **PUT**: replace the specified ConsoleExternalLogLink
- **/apis/console.openshift.io/v1/consoleexternalloglinks/{name}/status**
 - **GET**: read status of the specified ConsoleExternalLogLink
 - **PATCH**: partially update status of the specified ConsoleExternalLogLink
 - **PUT**: replace status of the specified ConsoleExternalLogLink

3.2.1. /apis/console.openshift.io/v1/consoleexternalloglinks

HTTP method

DELETE

Description

delete collection of ConsoleExternalLogLink

Table 3.1. HTTP responses

HTTP code	Response body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

list objects of kind ConsoleExternalLogLink

Table 3.2. HTTP responses

HTTP code	Response body
200 - OK	ConsoleExternalLogLinkList schema
401 - Unauthorized	Empty

HTTP method**POST****Description**

create a ConsoleExternalLogLink

Table 3.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 3.4. Body parameters

Parameter	Type	Description
body	ConsoleExternalLogLink schema	

Table 3.5. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleExternalLogLink schema
201 - Created	ConsoleExternalLogLink schema
202 - Accepted	ConsoleExternalLogLink schema
401 - Unauthorized	Empty

3.2.2. /apis/console.openshift.io/v1/consoleexternalloglinks/{name}

Table 3.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleExternalLogLink

HTTP method

DELETE

Description

delete a ConsoleExternalLogLink

Table 3.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 3.8. HTTP responses

HTTP code	Reponse body
200 - OK	Status schema
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

read the specified ConsoleExternalLogLink

Table 3.9. HTTP responses

HTTP code	Response body
200 - OK	ConsoleExternalLogLink schema
401 - Unauthorized	Empty

HTTP method

PATCH

Description

partially update the specified ConsoleExternalLogLink

Table 3.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 3.11. HTTP responses

HTTP code	Response body
200 - OK	ConsoleExternalLogLink schema

HTTP code	Response body
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace the specified ConsoleExternalLogLink

Table 3.12. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 3.13. Body parameters

Parameter	Type	Description
body	ConsoleExternalLog Link schema	

Table 3.14. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleExternalLogLink schema
201 - Created	ConsoleExternalLogLink schema
401 - Unauthorized	Empty

3.2.3. /apis/console.openshift.io/v1/consoleexternalloglinks/{name}/status

Table 3.15. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleExternalLogLink

HTTP method

GET

Description

read status of the specified ConsoleExternalLogLink

Table 3.16. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleExternalLogLink schema
401 - Unauthorized	Empty

HTTP method

PATCH

Description

partially update status of the specified ConsoleExternalLogLink

Table 3.17. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 3.18. HTTP responses

HTTP code	Response body
200 - OK	ConsoleExternalLogLink schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace status of the specified ConsoleExternalLogLink

Table 3.19. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 3.20. Body parameters

Parameter	Type	Description
body	ConsoleExternalLogLink schema	

Table 3.21. HTTP responses

HTTP code	Response body
200 - OK	ConsoleExternalLogLink schema
201 - Created	ConsoleExternalLogLink schema
401 - Unauthorized	Empty

CHAPTER 4. CONSOLELINK [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleLink is an extension for customizing OpenShift web console links. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

Required

- **spec**

4.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata
spec	object	ConsoleLinkSpec is the desired console link configuration.

4.1.1. .spec

Description

ConsoleLinkSpec is the desired console link configuration.

Type

object

Required

- **href**
- **location**
- **text**

Property	Type	Description
applicationMenu	object	applicationMenu holds information about section and icon used for the link in the application menu, and it is applicable only when location is set to ApplicationMenu.
href	string	href is the absolute secure URL for the link (must use https)
location	string	location determines which location in the console the link will be appended to (ApplicationMenu, HelpMenu, UserMenu, NamespaceDashboard).
namespaceDashboard	object	namespaceDashboard holds information about namespaces in which the dashboard link should appear, and it is applicable only when location is set to NamespaceDashboard. If not specified, the link will appear in all namespaces.
text	string	text is the display text for the link

4.1.2. .spec.applicationMenu**Description**

applicationMenu holds information about section and icon used for the link in the application menu, and it is applicable only when location is set to ApplicationMenu.

Type

object

Required

- **section**

Property	Type	Description
imageUrl	string	imageUrl is the URL for the icon used in front of the link in the application menu. The URL must be an HTTPS URL or a Data URI. The image should be square and will be shown at 24x24 pixels.
section	string	section is the section of the application menu in which the link should appear. This can be any text that will appear as a subheading in the application menu dropdown. A new section will be created if the text does not match text of an existing section.

4.1.3. .spec.namespaceDashboard**Description**

namespaceDashboard holds information about namespaces in which the dashboard link should appear, and it is applicable only when location is set to NamespaceDashboard. If not specified, the link will appear in all namespaces.

Type

object

Property	Type	Description
namespaceSelector	object	namespaceSelector is used to select the Namespaces that should contain dashboard link by label. If the namespace labels match, dashboard link will be shown for the namespaces.
namespaces	array (string)	namespaces is an array of namespace names in which the dashboard link should appear.

4.1.4. .spec.namespaceDashboard.namespaceSelector**Description**

namespaceSelector is used to select the Namespaces that should contain dashboard link by label. If the namespace labels match, dashboard link will be shown for the namespaces.

Type
object

Property	Type	Description
matchExpressions	array	matchExpressions is a list of label selector requirements. The requirements are ANDed.
matchExpressions[]	object	A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.
matchLabels	object (string)	matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

4.1.5. .spec.namespaceDashboard.namespaceSelector.matchExpressions

Description

matchExpressions is a list of label selector requirements. The requirements are ANDed.

Type

array

4.1.6. .spec.namespaceDashboard.namespaceSelector.matchExpressions[]

Description

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

Type

object

Required

- **key**
- **operator**

Property	Type	Description
key	string	key is the label key that the selector applies to.

Property	Type	Description
operator	string	operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.
values	array (string)	values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

4.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consolelinks**
 - **DELETE:** delete collection of ConsoleLink
 - **GET:** list objects of kind ConsoleLink
 - **POST:** create a ConsoleLink
- **/apis/console.openshift.io/v1/consolelinks/{name}**
 - **DELETE:** delete a ConsoleLink
 - **GET:** read the specified ConsoleLink
 - **PATCH:** partially update the specified ConsoleLink
 - **PUT:** replace the specified ConsoleLink
- **/apis/console.openshift.io/v1/consolelinks/{name}/status**
 - **GET:** read status of the specified ConsoleLink
 - **PATCH:** partially update status of the specified ConsoleLink
 - **PUT:** replace status of the specified ConsoleLink

4.2.1. /apis/console.openshift.io/v1/consolelinks

HTTP method

DELETE

Description

delete collection of ConsoleLink

Table 4.1. HTTP responses

HTTP code	Reponse body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

list objects of kind ConsoleLink

Table 4.2. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleLinkList schema
401 - Unauthorized	Empty

HTTP method

POST

Description

create a ConsoleLink

Table 4.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 4.4. Body parameters

Parameter	Type	Description
body	ConsoleLink schema	

Table 4.5. HTTP responses

HTTP code	Response body
200 - OK	ConsoleLink schema
201 - Created	ConsoleLink schema
202 - Accepted	ConsoleLink schema
401 - Unauthorized	Empty

4.2.2. /apis/console.openshift.io/v1/consolelinks/{name}

Table 4.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleLink

HTTP method**DELETE****Description**

delete a ConsoleLink

Table 4.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 4.8. HTTP responses

HTTP code	Response body
200 - OK	Status schema
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method**GET****Description**

read the specified ConsoleLink

Table 4.9. HTTP responses

HTTP code	Response body
200 - OK	ConsoleLink schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update the specified ConsoleLink

Table 4.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 4.11. HTTP responses

HTTP code	Response body
200 - OK	ConsoleLink schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace the specified ConsoleLink

Table 4.12. Query parameters

Parameter	Type	Description
-----------	------	-------------

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 4.13. Body parameters

Parameter	Type	Description
body	ConsoleLink schema	

Table 4.14. HTTP responses

HTTP code	Response body
200 - OK	ConsoleLink schema
201 - Created	ConsoleLink schema
401 - Unauthorized	Empty

4.2.3. /apis/console.openshift.io/v1/consolelinks/{name}/status

Table 4.15. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleLink

HTTP method**GET****Description**

read status of the specified ConsoleLink

Table 4.16. HTTP responses

HTTP code	Response body
200 - OK	ConsoleLink schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update status of the specified ConsoleLink

Table 4.17. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 4.18. HTTP responses

HTTP code	Response body
200 - OK	ConsoleLink schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace status of the specified ConsoleLink

Table 4.19. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: <ul style="list-style-type: none"> - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 4.20. Body parameters

Parameter	Type	Description
body	ConsoleLink schema	

Table 4.21. HTTP responses

HTTP code	Response body
200 - OK	ConsoleLink schema
201 - Created	ConsoleLink schema
401 - Unauthorized	Empty

CHAPTER 5. CONSOLENOTIFICATION [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleNotification is the extension for configuring openshift web console notifications.
Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

Required

- **spec**

5.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata
spec	object	ConsoleNotificationSpec is the desired console notification configuration.

5.1.1. .spec

Description

ConsoleNotificationSpec is the desired console notification configuration.

Type

object

Required

- **text**

Property	Type	Description
backgroundColor	string	backgroundColor is the color of the background for the notification as CSS data type color.
color	string	color is the color of the text for the notification as CSS data type color.
link	object	link is an object that holds notification link details.
location	string	location is the location of the notification in the console. Valid values are: "BannerTop", "BannerBottom", "BannerTopBottom".
text	string	text is the visible text of the notification.

5.1.2. .spec.link

Description

link is an object that holds notification link details.

Type

object

Required

- **href**
- **text**

Property	Type	Description
href	string	href is the absolute secure URL for the link (must use https)
text	string	text is the display text for the link

5.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consolenotifications**
 - **DELETE**: delete collection of ConsoleNotification
 - **GET**: list objects of kind ConsoleNotification
 - **POST**: create a ConsoleNotification
- **/apis/console.openshift.io/v1/consolenotifications/{name}**
 - **DELETE**: delete a ConsoleNotification
 - **GET**: read the specified ConsoleNotification
 - **PATCH**: partially update the specified ConsoleNotification
 - **PUT**: replace the specified ConsoleNotification
- **/apis/console.openshift.io/v1/consolenotifications/{name}/status**
 - **GET**: read status of the specified ConsoleNotification
 - **PATCH**: partially update status of the specified ConsoleNotification
 - **PUT**: replace status of the specified ConsoleNotification

5.2.1. /apis/console.openshift.io/v1/consolenotifications

HTTP method

DELETE

Description

delete collection of ConsoleNotification

Table 5.1. HTTP responses

HTTP code	Response body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method**GET****Description**

list objects of kind ConsoleNotification

Table 5.2. HTTP responses

HTTP code	Response body
200 - OK	ConsoleNotificationList schema
401 - Unauthorized	Empty

HTTP method**POST****Description**

create a ConsoleNotification

Table 5.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 5.4. Body parameters

Parameter	Type	Description
body	ConsoleNotification schema	

Table 5.5. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleNotification schema
201 - Created	ConsoleNotification schema
202 - Accepted	ConsoleNotification schema
401 - Unauthorized	Empty

5.2.2. /apis/console.openshift.io/v1/consolenotifications/{name}

Table 5.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleNotification

HTTP method

DELETE

Description

delete a ConsoleNotification

Table 5.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 5.8. HTTP responses

HTTP code	Reponse body
200 - OK	Status schema

HTTP code	Reponse body
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method**GET****Description**

read the specified ConsoleNotification

Table 5.9. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleNotification schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update the specified ConsoleNotification

Table 5.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 5.11. HTTP responses

HTTP code	Response body
200 - OK	ConsoleNotification schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace the specified ConsoleNotification

Table 5.12. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 5.13. Body parameters

Parameter	Type	Description
body	ConsoleNotification schema	

Table 5.14. HTTP responses

HTTP code	Response body
200 - OK	ConsoleNotification schema
201 - Created	ConsoleNotification schema
401 - Unauthorized	Empty

5.2.3. /apis/console.openshift.io/v1/consolenotifications/{name}/status

Table 5.15. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleNotification

HTTP method

GET**Description**

read status of the specified ConsoleNotification

Table 5.16. HTTP responses

HTTP code	Response body
200 - OK	ConsoleNotification schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update status of the specified ConsoleNotification

Table 5.17. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 5.18. HTTP responses

HTTP code	Response body
200 - OK	ConsoleNotification schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace status of the specified ConsoleNotification

Table 5.19. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 5.20. Body parameters

Parameter	Type	Description
body	ConsoleNotification schema	

Table 5.21. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleNotification schema
201 - Created	ConsoleNotification schema
401 - Unauthorized	Empty

CHAPTER 6. CONSOLEPLUGIN [CONSOLE.OPENSIFT.IO/V1]

Description

ConsolePlugin is an extension for customizing OpenShift web console by dynamically loading code from another service running on the cluster. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).

Type

object

Required

- **metadata**
- **spec**

6.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata
spec	object	ConsolePluginSpec is the desired plugin configuration.

6.1.1. .spec

Description

ConsolePluginSpec is the desired plugin configuration.

Type

object

Required

- **backend**
- **displayName**

Property	Type	Description
backend	object	backend holds the configuration of backend which is serving console's plugin .
displayName	string	displayName is the display name of the plugin. The display name should be between 1 and 128 characters.
i18n	object	i18n is the configuration of plugin's localization resources.
proxy	array	proxy is a list of proxies that describe various service type to which the plugin needs to connect to.
proxy[]	object	ConsolePluginProxy holds information on various service types to which console's backend will proxy the plugin's requests.

6.1.2. .spec.backend

Description

backend holds the configuration of backend which is serving console's plugin .

Type

object

Required

- **type**

Property	Type	Description
service	object	service is a Kubernetes Service that exposes the plugin using a deployment with an HTTP server. The Service must use HTTPS and Service serving certificate. The console backend will proxy the plugins assets from the Service using the service CA bundle.
type	string	type is the backend type which servers the console's plugin. Currently only "Service" is supported. ---

6.1.3. .spec.backend.service

Description

service is a Kubernetes Service that exposes the plugin using a deployment with an HTTP server. The Service must use HTTPS and Service serving certificate. The console backend will proxy the plugins assets from the Service using the service CA bundle.

Type

object

Required

- **name**
- **namespace**
- **port**

Property	Type	Description
basePath	string	basePath is the path to the plugin's assets. The primary asset is the manifest file called plugin-manifest.json , which is a JSON document that contains metadata about the plugin and the extensions.
name	string	name of Service that is serving the plugin assets.
namespace	string	namespace of Service that is serving the plugin assets.

Property	Type	Description
port	integer	port on which the Service that is serving the plugin is listening to.

6.1.4. .spec.i18n

Description

i18n is the configuration of plugin's localization resources.

Type

object

Required

- **loadType**

Property	Type	Description
loadType	string	loadType indicates how the plugin's localization resource should be loaded. Valid values are Preload, Lazy and the empty string. When set to Preload, all localization resources are fetched when the plugin is loaded. When set to Lazy, localization resources are lazily loaded as and when they are required by the console. When omitted or set to the empty string, the behaviour is equivalent to Lazy type.

6.1.5. .spec.proxy

Description

proxy is a list of proxies that describe various service type to which the plugin needs to connect to.

Type

array

6.1.6. .spec.proxy[]

Description

ConsolePluginProxy holds information on various service types to which console's backend will proxy the plugin's requests.

Type

object

Required

- **alias**
- **endpoint**

Property	Type	Description
alias	string	alias is a proxy name that identifies the plugin's proxy. An alias name should be unique per plugin. The console backend exposes following proxy endpoint: /api/proxy/plugin/<plugin-name>/<proxy-alias>/<request-path>?<optional-query-parameters> Request example path: /api/proxy/plugin/acm/search/pods?namespace=openshift-apiserver
authorization	string	authorization provides information about authorization type, which the proxied request should contain
caCertificate	string	caCertificate provides the cert authority certificate contents, in case the proxied Service is using custom service CA. By default, the service CA bundle provided by the service-ca operator is used.
endpoint	object	endpoint provides information about endpoint to which the request is proxied to.

6.1.7. .spec.proxy[].endpoint

Description

endpoint provides information about endpoint to which the request is proxied to.

Type

object

Required

- **type**

Property	Type	Description
service	object	service is an in-cluster Service that the plugin will connect to. The Service must use HTTPS. The console backend exposes an endpoint in order to proxy communication between the plugin and the Service. Note: service field is required for now, since currently only "Service" type is supported.
type	string	type is the type of the console plugin's proxy. Currently only "Service" is supported. ---

6.1.8. .spec.proxy[].endpoint.service

Description

service is an in-cluster Service that the plugin will connect to. The Service must use HTTPS. The console backend exposes an endpoint in order to proxy communication between the plugin and the Service. Note: service field is required for now, since currently only "Service" type is supported.

Type

object

Required

- **name**
- **namespace**
- **port**

Property	Type	Description
name	string	name of Service that the plugin needs to connect to.
namespace	string	namespace of Service that the plugin needs to connect to
port	integer	port on which the Service that the plugin needs to connect to is listening on.

6.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consoleplugins**
 - **DELETE**: delete collection of ConsolePlugin
 - **GET**: list objects of kind ConsolePlugin
 - **POST**: create a ConsolePlugin
- **/apis/console.openshift.io/v1/consoleplugins/{name}**
 - **DELETE**: delete a ConsolePlugin
 - **GET**: read the specified ConsolePlugin
 - **PATCH**: partially update the specified ConsolePlugin
 - **PUT**: replace the specified ConsolePlugin

6.2.1. /apis/console.openshift.io/v1/consoleplugins

HTTP method

DELETE

Description

delete collection of ConsolePlugin

Table 6.1. HTTP responses

HTTP code	Response body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

list objects of kind ConsolePlugin

Table 6.2. HTTP responses

HTTP code	Response body
200 - OK	ConsolePluginList schema
401 - Unauthorized	Empty

HTTP method

POST

Description

create a ConsolePlugin

Table 6.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 6.4. Body parameters

Parameter	Type	Description
body	ConsolePlugin schema	

Table 6.5. HTTP responses

HTTP code	Response body
200 - OK	ConsolePlugin schema
201 - Created	ConsolePlugin schema
202 - Accepted	ConsolePlugin schema

HTTP code	Reponse body
401 - Unauthorized	Empty

6.2.2. /apis/console.openshift.io/v1/consoleplugins/{name}

Table 6.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsolePlugin

HTTP method

DELETE

Description

delete a ConsolePlugin

Table 6.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 6.8. HTTP responses

HTTP code	Reponse body
200 - OK	Status schema
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

read the specified ConsolePlugin

Table 6.9. HTTP responses

HTTP code	Response body
200 - OK	ConsolePlugin schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update the specified ConsolePlugin

Table 6.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 6.11. HTTP responses

HTTP code	Response body
200 - OK	ConsolePlugin schema
401 - Unauthorized	Empty

HTTP method

PUT

Description

replace the specified ConsolePlugin

Table 6.12. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 6.13. Body parameters

Parameter	Type	Description
body	ConsolePlugin schema	

Table 6.14. HTTP responses

HTTP code	Response body
200 - OK	ConsolePlugin schema
201 - Created	ConsolePlugin schema

HTTP code	Reponse body
401 - Unauthorized	Empty

CHAPTER 7. CONSOLEQUICKSTART [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleQuickStart is an extension for guiding user through various workflows in the OpenShift web console. Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

Required

- **spec**

7.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata
spec	object	ConsoleQuickStartSpec is the desired quick start configuration.

7.1.1. .spec

Description

ConsoleQuickStartSpec is the desired quick start configuration.

Type

object

Required

- **description**
- **displayName**
- **durationMinutes**
- **introduction**
- **tasks**

Property	Type	Description
accessReviewResources	array	accessReviewResources contains a list of resources that the user's access will be reviewed against in order for the user to complete the Quick Start. The Quick Start will be hidden if any of the access reviews fail.
accessReviewResources[]	object	ResourceAttributes includes the authorization attributes available for resource requests to the Authorizer interface
conclusion	string	conclusion sums up the Quick Start and suggests the possible next steps. (includes markdown)
description	string	description is the description of the Quick Start. (includes markdown)
displayName	string	displayName is the display name of the Quick Start.
durationMinutes	integer	durationMinutes describes approximately how many minutes it will take to complete the Quick Start.

Property	Type	Description
icon	string	icon is a base64 encoded image that will be displayed beside the Quick Start display name. The icon should be an vector image for easy scaling. The size of the icon should be 40x40.
introduction	string	introduction describes the purpose of the Quick Start. (includes markdown)
nextQuickStart	array (string)	nextQuickStart is a list of the following Quick Starts, suggested for the user to try.
prerequisites	array (string)	prerequisites contains all prerequisites that need to be met before taking a Quick Start. (includes markdown)
tags	array (string)	tags is a list of strings that describe the Quick Start.
tasks	array	tasks is the list of steps the user has to perform to complete the Quick Start.
tasks[]	object	ConsoleQuickStartTask is a single step in a Quick Start.

7.1.2. .spec.accessReviewResources

Description

accessReviewResources contains a list of resources that the user's access will be reviewed against in order for the user to complete the Quick Start. The Quick Start will be hidden if any of the access reviews fail.

Type

array

7.1.3. .spec.accessReviewResources[]

Description

ResourceAttributes includes the authorization attributes available for resource requests to the Authorizer interface

Type

object

Property	Type	Description
group	string	Group is the API Group of the Resource. "*" means all.
name	string	Name is the name of the resource being requested for a "get" or deleted for a "delete". "" (empty) means all.
namespace	string	Namespace is the namespace of the action being requested. Currently, there is no distinction between no namespace and all namespaces "" (empty) is defaulted for LocalSubjectAccessReviews "" (empty) is empty for cluster-scoped resources "" (empty) means "all" for namespace scoped resources from a SubjectAccessReview or SelfSubjectAccessReview
resource	string	Resource is one of the existing resource types. "*" means all.
subresource	string	Subresource is one of the existing resource types. "" means none.
verb	string	Verb is a kubernetes resource API verb, like: get, list, watch, create, update, delete, proxy. "*" means all.
version	string	Version is the API Version of the Resource. "*" means all.

7.1.4. .spec.tasks**Description**

tasks is the list of steps the user has to perform to complete the Quick Start.

Type

array

7.1.5. .spec.tasks[]**Description**

ConsoleQuickStartTask is a single step in a Quick Start.

Type

object

Required

- **description**
- **title**

Property	Type	Description
description	string	description describes the steps needed to complete the task. (includes markdown)
review	object	review contains instructions to validate the task is complete. The user will select 'Yes' or 'No'. using a radio button, which indicates whether the step was completed successfully.
summary	object	summary contains information about the passed step.
title	string	title describes the task and is displayed as a step heading.

7.1.6. .spec.tasks[].review

Description

review contains instructions to validate the task is complete. The user will select 'Yes' or 'No'. using a radio button, which indicates whether the step was completed successfully.

Type

object

Required

- **failedTaskHelp**
- **instructions**

Property	Type	Description
failedTaskHelp	string	failedTaskHelp contains suggestions for a failed task review and is shown at the end of task. (includes markdown)

Property	Type	Description
instructions	string	instructions contains steps that user needs to take in order to validate his work after going through a task. (includes markdown)

7.1.7. .spec.tasks[].summary

Description

summary contains information about the passed step.

Type

object

Required

- **failed**
- **success**

Property	Type	Description
failed	string	failed briefly describes the unsuccessfully passed task. (includes markdown)
success	string	success describes the successfully passed task.

7.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consolequickstarts**
 - **DELETE**: delete collection of ConsoleQuickStart
 - **GET**: list objects of kind ConsoleQuickStart
 - **POST**: create a ConsoleQuickStart
- **/apis/console.openshift.io/v1/consolequickstarts/{name}**
 - **DELETE**: delete a ConsoleQuickStart
 - **GET**: read the specified ConsoleQuickStart
 - **PATCH**: partially update the specified ConsoleQuickStart
 - **PUT**: replace the specified ConsoleQuickStart

7.2.1. /apis/console.openshift.io/v1/consolequickstarts

HTTP method

DELETE

Description

delete collection of ConsoleQuickStart

Table 7.1. HTTP responses

HTTP code	Reponse body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

list objects of kind ConsoleQuickStart

Table 7.2. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleQuickStartList schema
401 - Unauthorized	Empty

HTTP method

POST

Description

create a ConsoleQuickStart

Table 7.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 7.4. Body parameters

Parameter	Type	Description
body	ConsoleQuickStart schema	

Table 7.5. HTTP responses

HTTP code	Response body
200 - OK	ConsoleQuickStart schema
201 - Created	ConsoleQuickStart schema
202 - Accepted	ConsoleQuickStart schema
401 - Unauthorized	Empty

7.2.2. /apis/console.openshift.io/v1/consolequickstarts/{name}

Table 7.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleQuickStart

HTTP method**DELETE****Description**

delete a ConsoleQuickStart

Table 7.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 7.8. HTTP responses

HTTP code	Response body
200 - OK	Status schema
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method**GET****Description**

read the specified ConsoleQuickStart

Table 7.9. HTTP responses

HTTP code	Response body
200 - OK	ConsoleQuickStart schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update the specified ConsoleQuickStart

Table 7.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 7.11. HTTP responses

HTTP code	Response body
200 - OK	ConsoleQuickStart schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace the specified ConsoleQuickStart

Table 7.12. Query parameters

Parameter	Type	Description
-----------	------	-------------

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 7.13. Body parameters

Parameter	Type	Description
body	ConsoleQuickStart schema	

Table 7.14. HTTP responses

HTTP code	Response body
200 - OK	ConsoleQuickStart schema
201 - Created	ConsoleQuickStart schema
401 - Unauthorized	Empty

CHAPTER 8. CONSOLESAMPLE [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleSample is an extension to customizing OpenShift web console by adding samples.
Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).

Type

object

Required

- **metadata**
- **spec**

8.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata

Property	Type	Description
spec	object	spec contains configuration for a console sample.

8.1.1. .spec

Description

spec contains configuration for a console sample.

Type

object

Required

- **abstract**
- **description**
- **source**
- **title**

Property	Type	Description
abstract	string	abstract is a short introduction to the sample. It is required and must be no more than 100 characters in length. The abstract is shown on the sample card tile below the title and provider and is limited to three lines of content.
description	string	description is a long form explanation of the sample. It is required and can have a maximum length of 4096 characters. It is a README.md-like content for additional information, links, pre-conditions, and other instructions. It will be rendered as Markdown so that it can contain line breaks, links, and other simple formatting.

Property	Type	Description
icon	string	<p>icon is an optional base64 encoded image and shown beside the sample title. The format must follow the data: URL format and can have a maximum size of 10 KB. data:[<mediatype>][;base64], <base64 encoded image> For example: data:image;base64, plus the base64 encoded image. Vector images can also be used. SVG icons must start with: data:image/svg+xml;base64, plus the base64 encoded SVG image. All sample catalog icons will be shown on a white background (also when the dark theme is used). The web console ensures that different aspect ratios work correctly. Currently, the surface of the icon is at most 40x100px. For more information on the data URL format, please visit https://developer.mozilla.org/en-US/docs/Web/HTTP/Basics_of_HTTP/Data_URLs.</p>
provider	string	<p>provider is an optional label to honor who provides the sample. It is optional and must be no more than 50 characters in length. A provider can be a company like "Red Hat" or an organization like "CNCF" or "Knative". Currently, the provider is only shown on the sample card tile below the title with the prefix "Provided by "</p>
source	object	<p>source defines where to deploy the sample service from. The sample may be sourced from an external git repository or container image.</p>
tags	array (string)	<p>tags are optional string values that can be used to find samples in the samples catalog. Examples of common tags may be "Java", "Quarkus", etc. They will be displayed on the samples details page.</p>

Property	Type	Description
title	string	title is the display name of the sample. It is required and must be no more than 50 characters in length.
type	string	type is an optional label to group multiple samples. It is optional and must be no more than 20 characters in length. Recommendation is a singular term like "Builder Image", "Devfile" or "Serverless Function". Currently, the type is shown a badge on the sample card tile in the top right corner.

8.1.2. .spec.source

Description

source defines where to deploy the sample service from. The sample may be sourced from an external git repository or container image.

Type

object

Required

- **type**

Property	Type	Description
containerImport	object	containerImport allows the user import a container image.
gitImport	object	gitImport allows the user to import code from a git repository.
type	string	type of the sample, currently supported: "GitImport";"ContainerImport"

8.1.3. .spec.source.containerImport

Description

containerImport allows the user import a container image.

Type

object

Required

- **image**

Property	Type	Description
image	string	reference to a container image that provides a HTTP service. The service must be exposed on the default port (8080) unless otherwise configured with the port field. Supported formats: - <repository-name>/<image-name> - docker.io/<repository-name>/<image-name> - quay.io/<repository-name>/<image-name> - quay.io/<repository-name>/<image-name>@sha256:<image hash> - quay.io/<repository-name>/<image-name>:<tag>
service	object	service contains configuration for the Service resource created for this sample.

8.1.4. .spec.source.containerImport.service**Description**

service contains configuration for the Service resource created for this sample.

Type

object

Property	Type	Description
targetPort	integer	targetPort is the port that the service listens on for HTTP requests. This port will be used for Service and Route created for this sample. Port must be in the range 1 to 65535. Default port is 8080.

8.1.5. .spec.source.gitImport**Description**

gitImport allows the user to import code from a git repository.

Type

object

Required

- **repository**

Property	Type	Description
repository	object	repository contains the reference to the actual Git repository.
service	object	service contains configuration for the Service resource created for this sample.

8.1.6. .spec.source.gitImport.repository**Description**

repository contains the reference to the actual Git repository.

Type

object

Required

- **url**

Property	Type	Description
contextDir	string	contextDir is used to specify a directory within the repository to build the component. Must start with / and have a maximum length of 256 characters. When omitted, the default value is to build from the root of the repository.
revision	string	revision is the git revision at which to clone the git repository. Can be used to clone a specific branch, tag or commit SHA. Must be at most 256 characters in length. When omitted the repository's default branch is used.

Property	Type	Description
url	string	url of the Git repository that contains a HTTP service. The HTTP service must be exposed on the default port (8080) unless otherwise configured with the port field. Only public repositories on GitHub, GitLab and Bitbucket are currently supported: - <a href="https://github.com/<org>/<repository>">https://github.com/<org>/<repository> - <a href="https://gitlab.com/<org>/<repository>">https://gitlab.com/<org>/<repository> - <a href="https://bitbucket.org/<org>/<repository>">https://bitbucket.org/<org>/<repository> The url must have a maximum length of 256 characters.

8.1.7. .spec.source.gitImport.service

Description

service contains configuration for the Service resource created for this sample.

Type

object

Property	Type	Description
targetPort	integer	targetPort is the port that the service listens on for HTTP requests. This port will be used for Service created for this sample. Port must be in the range 1 to 65535. Default port is 8080.

8.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consolesamples**
 - **DELETE:** delete collection of ConsoleSample
 - **GET:** list objects of kind ConsoleSample
 - **POST:** create a ConsoleSample
- **/apis/console.openshift.io/v1/consolesamples/{name}**
 - **DELETE:** delete a ConsoleSample

- **GET**: read the specified ConsoleSample
- **PATCH**: partially update the specified ConsoleSample
- **PUT**: replace the specified ConsoleSample

8.2.1. /apis/console.openshift.io/v1/consolesamples

HTTP method

DELETE

Description

delete collection of ConsoleSample

Table 8.1. HTTP responses

HTTP code	Reponse body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

list objects of kind ConsoleSample

Table 8.2. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleSampleList schema
401 - Unauthorized	Empty

HTTP method

POST

Description

create a ConsoleSample

Table 8.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 8.4. Body parameters

Parameter	Type	Description
body	ConsoleSample schema	

Table 8.5. HTTP responses

HTTP code	Response body
200 - OK	ConsoleSample schema
201 - Created	ConsoleSample schema
202 - Accepted	ConsoleSample schema
401 - Unauthorized	Empty

8.2.2. /apis/console.openshift.io/v1/consolesamples/{name}

Table 8.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleSample

HTTP method**DELETE****Description**

delete a ConsoleSample

Table 8.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 8.8. HTTP responses

HTTP code	Response body
200 - OK	Status schema
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method**GET****Description**

read the specified ConsoleSample

Table 8.9. HTTP responses

HTTP code	Response body
200 - OK	ConsoleSample schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update the specified ConsoleSample

Table 8.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 8.11. HTTP responses

HTTP code	Response body
200 - OK	ConsoleSample schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace the specified ConsoleSample

Table 8.12. Query parameters

Parameter	Type	Description
-----------	------	-------------

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 8.13. Body parameters

Parameter	Type	Description
body	ConsoleSample schema	

Table 8.14. HTTP responses

HTTP code	Response body
200 - OK	ConsoleSample schema
201 - Created	ConsoleSample schema
401 - Unauthorized	Empty

CHAPTER 9. CONSOLEYAMLSAMPLE [CONSOLE.OPENSIFT.IO/V1]

Description

ConsoleYAMLSample is an extension for customizing OpenShift web console YAML samples.
Compatibility level 2: Stable within a major release for a minimum of 9 months or 3 minor releases (whichever is longer).

Type

object

Required

- **metadata**
- **spec**

9.1. SPECIFICATION

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds
metadata	ObjectMeta	Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata

Property	Type	Description
spec	object	ConsoleYAMLSampleSpec is the desired YAML sample configuration. Samples will appear with their descriptions in a samples sidebar when creating a resources in the web console.

9.1.1. .spec

Description

ConsoleYAMLSampleSpec is the desired YAML sample configuration. Samples will appear with their descriptions in a samples sidebar when creating a resources in the web console.

Type

object

Required

- **description**
- **targetResource**
- **title**
- **yaml**

Property	Type	Description
description	string	description of the YAML sample.
snippet	boolean	snippet indicates that the YAML sample is not the full YAML resource definition, but a fragment that can be inserted into the existing YAML document at the user's cursor.
targetResource	object	targetResource contains apiVersion and kind of the resource YAML sample is representing.
title	string	title of the YAML sample.
yaml	string	yaml is the YAML sample to display.

9.1.2. .spec.targetResource

Description

targetResource contains apiVersion and kind of the resource YAML sample is representing.

Type

object

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds

9.2. API ENDPOINTS

The following API endpoints are available:

- **/apis/console.openshift.io/v1/consoleyamlsamples**
 - **DELETE:** delete collection of ConsoleYAMLSample
 - **GET:** list objects of kind ConsoleYAMLSample
 - **POST:** create a ConsoleYAMLSample
- **/apis/console.openshift.io/v1/consoleyamlsamples/{name}**
 - **DELETE:** delete a ConsoleYAMLSample
 - **GET:** read the specified ConsoleYAMLSample
 - **PATCH:** partially update the specified ConsoleYAMLSample
 - **PUT:** replace the specified ConsoleYAMLSample

9.2.1. /apis/console.openshift.io/v1/consoleyamlsamples

HTTP method

DELETE

Description

delete collection of ConsoleYAMLSample

Table 9.1. HTTP responses

HTTP code	Reponse body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

list objects of kind ConsoleYAMLSample

Table 9.2. HTTP responses

HTTP code	Reponse body
200 - OK	ConsoleYAMLSampleList schema
401 - Unauthorized	Empty

HTTP method

POST

Description

create a ConsoleYAMLSample

Table 9.3. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: <ul style="list-style-type: none"> - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 9.4. Body parameters

Parameter	Type	Description
body	ConsoleYAMLSample schema	

Table 9.5. HTTP responses

HTTP code	Response body
200 - OK	ConsoleYAMLSample schema
201 - Created	ConsoleYAMLSample schema
202 - Accepted	ConsoleYAMLSample schema
401 - Unauthorized	Empty

9.2.2. /apis/console.openshift.io/v1/consoleyaml.samples/{name}

Table 9.6. Global path parameters

Parameter	Type	Description
name	string	name of the ConsoleYAMLSample

HTTP method**DELETE****Description**

delete a ConsoleYAMLSample

Table 9.7. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Table 9.8. HTTP responses

HTTP code	Response body
200 - OK	Status schema
202 - Accepted	Status schema
401 - Unauthorized	Empty

HTTP method**GET****Description**

read the specified ConsoleYAMLSample

Table 9.9. HTTP responses

HTTP code	Response body
200 - OK	ConsoleYAMLSample schema
401 - Unauthorized	Empty

HTTP method**PATCH****Description**

partially update the specified ConsoleYAMLSample

Table 9.10. Query parameters

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 9.11. HTTP responses

HTTP code	Response body
200 - OK	ConsoleYAMLSample schema
401 - Unauthorized	Empty

HTTP method**PUT****Description**

replace the specified ConsoleYAMLSample

Table 9.12. Query parameters

Parameter	Type	Description
-----------	------	-------------

Parameter	Type	Description
dryRun	string	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
fieldValidation	string	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Table 9.13. Body parameters

Parameter	Type	Description
body	ConsoleYAMLSample schema	

Table 9.14. HTTP responses

HTTP code	Response body
200 - OK	ConsoleYAMLSample schema
201 - Created	ConsoleYAMLSample schema
401 - Unauthorized	Empty