



Red Hat Advanced Cluster Management for Kubernetes 2.0

APIs

APIs

APIs

Legal Notice

Copyright © 2021 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

API guide for Red Hat Advanced Cluster Management for Kubernetes

Table of Contents

CHAPTER 1. APIS	7
1.1. CLUSTERS API	7
1.1.1. Overview	7
1.1.1.1. Version information	7
1.1.1.2. Contact information	7
1.1.1.3. License information	7
1.1.1.4. URI scheme	7
1.1.1.5. Tags	7
1.1.1.6. External Docs	7
1.1.2. Paths	8
1.1.2.1. Query all clusters	8
1.1.2.1.1. Description	8
1.1.2.1.2. Parameters	8
1.1.2.1.3. Responses	8
1.1.2.1.4. Consumes	8
1.1.2.1.5. Tags	8
1.1.2.2. Create a cluster	8
1.1.2.2.1. Description	9
1.1.2.2.2. Parameters	9
1.1.2.2.3. Responses	9
1.1.2.2.4. Consumes	9
1.1.2.2.5. Tags	9
1.1.2.2.6. Example HTTP request	9
1.1.2.2.6.1. Request body	9
1.1.2.3. Query a single cluster	10
1.1.2.3.1. Description	10
1.1.2.3.2. Parameters	10
1.1.2.3.3. Responses	10
1.1.2.3.4. Tags	10
1.1.2.4. Delete a cluster	11
1.1.2.4.1. Description	11
1.1.2.4.2. Parameters	11
1.1.2.4.3. Responses	11
1.1.2.4.4. Tags	11
1.1.3. Definitions	11
1.1.3.1. Cluster	11
1.2. CHANNELS API	12
1.2.1. Overview	12
1.2.1.1. Version information	12
1.2.1.2. Contact information	12
1.2.1.3. License information	13
1.2.1.4. URI scheme	13
1.2.1.5. Tags	13
1.2.1.6. External Docs	13
1.2.2. Paths	13
1.2.2.1. Create a channel	13
1.2.2.1.1. Description	13
1.2.2.1.2. Parameters	13
1.2.2.1.3. Responses	13
1.2.2.1.4. Consumes	14
1.2.2.1.5. Tags	14

1.2.2.1.6. Example HTTP request	14
1.2.2.1.6.1. Request body	14
1.2.2.2. Query all channels for the target namespace	14
1.2.2.2.1. Description	14
1.2.2.2.2. Parameters	14
1.2.2.2.3. Responses	15
1.2.2.2.4. Consumes	15
1.2.2.2.5. Tags	15
1.2.2.3. Query a single channels of a namespace	15
1.2.2.3.1. Description	15
1.2.2.3.2. Parameters	15
1.2.2.3.3. Responses	16
1.2.2.3.4. Tags	16
1.2.2.4. Delete a Channel	16
1.2.2.4.1. Parameters	16
1.2.2.4.2. Responses	16
1.2.2.4.3. Tags	17
1.2.3. Definitions	17
1.2.3.1. Channel	17
1.3. SUBSCRIPTIONS API	21
1.3.1. Overview	21
1.3.1.1. Version information	21
1.3.1.2. Contact information	21
1.3.1.3. License information	21
1.3.1.4. URI scheme	21
1.3.1.5. Tags	21
1.3.1.6. External Docs	21
1.3.2. Paths	21
1.3.2.1. Create a subscription	21
1.3.2.1.1. Description	21
1.3.2.1.2. Parameters	21
1.3.2.1.3. Responses	22
1.3.2.1.4. Consumes	22
1.3.2.1.5. Tags	22
1.3.2.1.6. Example HTTP request	22
1.3.2.1.6.1. Request body	22
1.3.2.2. Query all subscriptions	23
1.3.2.2.1. Description	23
1.3.2.2.2. Parameters	23
1.3.2.2.3. Responses	24
1.3.2.2.4. Consumes	24
1.3.2.2.5. Tags	24
1.3.2.3. Query a single subscription	24
1.3.2.3.1. Description	24
1.3.2.3.2. Parameters	24
1.3.2.3.3. Responses	25
1.3.2.3.4. Tags	25
1.3.2.4. Delete a subscription	25
1.3.2.4.1. Parameters	25
1.3.2.4.2. Responses	25
1.3.2.4.3. Tags	26
1.3.3. Definitions	26
1.3.3.1. Subscription	26

1.4. PLACEMENTRULES API	31
1.4.1. Overview	31
1.4.1.1. Version information	31
1.4.1.2. Contact information	32
1.4.1.3. License information	32
1.4.1.4. URI scheme	32
1.4.1.5. Tags	32
1.4.1.6. External Docs	32
1.4.2. Paths	32
1.4.2.1. Create a placementrule	32
1.4.2.1.1. Description	32
1.4.2.1.2. Parameters	32
1.4.2.1.3. Responses	32
1.4.2.1.4. Consumes	33
1.4.2.1.5. Tags	33
1.4.2.1.6. Example HTTP request	33
1.4.2.1.6.1. Request body	33
1.4.2.2. Query all placementrules	33
1.4.2.2.1. Description	33
1.4.2.2.2. Parameters	33
1.4.2.2.3. Responses	34
1.4.2.2.4. Consumes	34
1.4.2.2.5. Tags	34
1.4.2.3. Query a single placementrule	34
1.4.2.3.1. Description	34
1.4.2.3.2. Parameters	34
1.4.2.3.3. Responses	35
1.4.2.3.4. Tags	35
1.4.2.4. Delete a placementrule	35
1.4.2.4.1. Parameters	35
1.4.2.4.2. Responses	36
1.4.2.4.3. Tags	36
1.4.3. Definitions	36
1.4.3.1. Placementrule	36
1.5. APPLICATIONS API	39
1.5.1. Overview	39
1.5.1.1. Version information	39
1.5.1.2. Contact information	39
1.5.1.3. License information	39
1.5.1.4. URI scheme	39
1.5.1.5. Tags	39
1.5.1.6. External Docs	39
1.5.2. Paths	39
1.5.2.1. Create a application	39
1.5.2.1.1. Description	40
1.5.2.1.2. Parameters	40
1.5.2.1.3. Responses	40
1.5.2.1.4. Consumes	40
1.5.2.1.5. Tags	40
1.5.2.1.6. Example HTTP request	40
1.5.2.1.6.1. Request body	40
1.5.2.2. Query all applications	41
1.5.2.2.1. Description	41

1.5.2.2.2. Parameters	41
1.5.2.2.3. Responses	41
1.5.2.2.4. Consumes	42
1.5.2.2.5. Tags	42
1.5.2.3. Query a single application	42
1.5.2.3.1. Description	42
1.5.2.3.2. Parameters	42
1.5.2.3.3. Responses	42
1.5.2.3.4. Tags	43
1.5.2.4. Delete a application	43
1.5.2.4.1. Parameters	43
1.5.2.4.2. Responses	43
1.5.2.4.3. Tags	43
1.5.3. Definitions	44
1.5.3.1. Application	44
1.6. HELM API	49
1.6.1. Overview	49
1.6.1.1. Version information	50
1.6.1.2. Contact information	50
1.6.1.3. License information	50
1.6.1.4. URI scheme	50
1.6.1.5. Tags	50
1.6.1.6. External Docs	50
1.6.2. Paths	50
1.6.2.1. Create a helmrelease	50
1.6.2.1.1. Description	50
1.6.2.1.2. Parameters	50
1.6.2.1.3. Responses	51
1.6.2.1.4. Consumes	51
1.6.2.1.5. Tags	51
1.6.2.1.6. Example HTTP request	51
1.6.2.1.6.1. Request body	51
1.6.2.2. Query all helmreleases	52
1.6.2.2.1. Description	52
1.6.2.2.2. Parameters	52
1.6.2.2.3. Responses	52
1.6.2.2.4. Consumes	52
1.6.2.2.5. Tags	52
1.6.2.3. Query a single helmrelease	53
1.6.2.3.1. Description	53
1.6.2.3.2. Parameters	53
1.6.2.3.3. Responses	53
1.6.2.3.4. Tags	53
1.6.2.4. Delete a helmrelease	53
1.6.2.4.1. Parameters	53
1.6.2.4.2. Responses	54
1.6.2.4.3. Tags	54
1.6.3. Definitions	54
1.6.3.1. HelmRelease	54
1.7. POLICY API	58
1.7.1. Overview	58
1.7.1.1. Version information	58
1.7.1.2. Contact information	58

1.7.1.3. License information	58
1.7.1.4. URI scheme	58
1.7.1.5. Tags	58
1.7.1.6. External Docs	59
1.7.2. Paths	59
1.7.2.1. Create a policy	59
1.7.2.1.1. Description	59
1.7.2.1.2. Parameters	59
1.7.2.1.3. Responses	59
1.7.2.1.4. Consumes	59
1.7.2.1.5. Tags	60
1.7.2.1.6. Example HTTP request	60
1.7.2.1.6.1. Request body	60
1.7.2.2. Query all policies	61
1.7.2.2.1. Description	61
1.7.2.2.2. Parameters	62
1.7.2.2.3. Responses	62
1.7.2.2.4. Consumes	62
1.7.2.2.5. Tags	62
1.7.2.3. Query a single policy	62
1.7.2.3.1. Description	62
1.7.2.3.2. Parameters	62
1.7.2.3.3. Responses	63
1.7.2.3.4. Tags	63
1.7.2.4. Delete a policy	63
1.7.2.4.1. Parameters	63
1.7.2.4.2. Responses	64
1.7.2.4.3. Tags	64
1.7.3. Definitions	64
1.7.3.1. Policy	64

CHAPTER 1. APIS

You can access APIs for to create and manage application resources, channels, subscriptions, and to query information.

For more information, review the API documentation for each of the following resources:

- [Clusters API](#)
- [Channels API](#)
- [Subscriptions API](#)
- [PlacementRules API](#)
- [Applications API](#)
- [Helm API](#)
- [Policy API](#)

1.1. CLUSTERS API

1.1.1. Overview

This documentation is for the cluster resource for Red Hat Advanced Cluster Management for Kubernetes. Cluster resource has four possible requests: create, query, delete and update.

1.1.1.1. Version information

Version : 2.0.0

1.1.1.2. Contact information

Contact Email : apiteam@swagger.io

1.1.1.3. License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

Terms of service : <http://swagger.io/terms/>

1.1.1.4. URI scheme

BasePath : /kubernetes/apis

Schemes : HTTPS

1.1.1.5. Tags

- [cluster.open-cluster-management.io](#) : Create and manage clusters

1.1.1.6. External Docs

Description : Find out more about Swagger.

URL : <http://swagger.io>

1.1.2. Paths

1.1.2.1. Query all clusters

GET /cluster.open-cluster-management.io/v1/managedclusters

1.1.2.1.1. Description

Query your clusters for more details.

1.1.2.1.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string

1.1.2.1.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.1.2.1.4. Consumes

- **cluster/yaml**

1.1.2.1.5. Tags

- cluster.open-cluster-management.io

1.1.2.2. Create a cluster

POST /cluster.open-cluster-management.io/v1/managedclusters

1.1.2.2.1. Description

Create a cluster

1.1.2.2.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Body	body <i>required</i>	Parameters describing the cluster to be created.	Cluster

1.1.2.2.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.1.2.2.4. Consumes

- **cluster/yaml**

1.1.2.2.5. Tags

- `cluster.open-cluster-management.io`

1.1.2.2.6. Example HTTP request

1.1.2.2.6.1. Request body

```
{
  "apiVersion": "cluster.open-cluster-management.io/v1",
  "kind": "ManagedCluster",
  "metadata": {
    "labels": {
      "vendor": "OpenShift"
    }
  },
  "name": "cluster1",
```

```

    },
    "spec": {
      "hubAcceptsClient": true,
      "managedClusterClientConfigs": [
        {
          "caBundle": "test",
          "url": "https://test.com"
        }
      ]
    },
    "status": {}
  }
}

```

1.1.2.3. Query a single cluster

GET /cluster.open-cluster-management.io/v1/managedclusters/{cluster_name}

1.1.2.3.1. Description

Query a single cluster for more details.

1.1.2.3.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	cluster_name <i>required</i>	Name of the cluster that you want to query.	string

1.1.2.3.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.1.2.3.4. Tags

- cluster.open-cluster-management.io

1.1.2.4. Delete a cluster

DELETE /cluster.open-cluster-management.io/v1/managedclusters/{cluster_name}

1.1.2.4.1. Description

Delete a single cluster

1.1.2.4.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	cluster_name <i>required</i>	Name of the cluster that you want to delete.	string

1.1.2.4.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.1.2.4.4. Tags

- cluster.open-cluster-management.io

1.1.3. Definitions

1.1.3.1. Cluster

Name	Schema
apiVersion <i>required</i>	string

Name	Schema
kind <i>required</i>	string
metadata <i>required</i>	object
spec <i>required</i>	spec

spec

Name	Schema
hubAcceptsClient <i>required</i>	bool
managedClusterClientConfigs <i>optional</i>	< managedClusterClientConfigs > array
leaseDurationSeconds <i>optional</i>	integer (int32)

managedClusterClientConfigs

Name	Description	Schema
URL <i>required</i>		string
CABundle <i>optional</i>	Pattern: <code>"^(?:[A-Za-z0-9+]{4})*(?:[A-Za-z0-9+]{2}=? [A-Za-z0-9+]{3}=)?\$"</code>	string (byte)

1.2. CHANNELS API

1.2.1. Overview

This documentation is for the Channel resource for Red Hat Advanced Cluster Management for Kubernetes. The Channel resource has four possible requests: create, query, delete and update.

1.2.1.1. Version information

Version : 2.0.0

1.2.1.2. Contact information

Contact Email : apiteam@swagger.io

1.2.1.3. License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

Terms of service : <http://swagger.io/terms/>

1.2.1.4. URI scheme

BasePath : /kubernetes/apis

Schemes : HTTPS

1.2.1.5. Tags

- channels.apps.open-cluster-management.io : Create and manage deployables

1.2.1.6. External Docs

Description : Find out more about Swagger.

URL : <http://swagger.io>

1.2.2. Paths

1.2.2.1. Create a channel

POST /apps.open-cluster-management.io/v1/namespaces/{namespace}/channels

1.2.2.1.1. Description

Create a channel.

1.2.2.1.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string
Body	body <i>required</i>	Parameters describing the deployable to be created.	Channel

1.2.2.1.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.2.2.1.4. Consumes

- **application/yaml**

1.2.2.1.5. Tags

- channels.apps.open-cluster-management.io

1.2.2.1.6. Example HTTP request

1.2.2.1.6.1. Request body

```
{
  "apiVersion" : "apps.open-cluster-management.io/v1",
  "kind" : "Channel",
  "name" : "sample-channel",
  "namespace" : "default",
  "spec" : {
    "type" : "Git",
    "pathname" : "https://github.com/IBM/charts.git",
    "configMapRef" : {
      "name" : "bookinfo-resource-filter-configmap",
      "kind" : "configmap"
    }
  }
}
```

1.2.2.2. Query all channels for the target namespace

```
GET /apps.open-cluster-management.io/v1/namespaces/{namespace}/channels
```

1.2.2.2.1. Description

Query your channels for more details.

1.2.2.2.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.2.2.2.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.2.2.2.4. Consumes

- **application/yaml**

1.2.2.2.5. Tags

- channels.apps.open-cluster-management.io

1.2.2.3. Query a single channels of a namespace

```
GET /apps.open-cluster-management.io/v1/namespaces/{namespace}/channels/{channel_name}
```

1.2.2.3.1. Description

Query a single channels for more details.

1.2.2.3.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string

Type	Name	Description	Schema
Path	channel_name <i>required</i>	Name of the deployable that you wan to query.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.2.2.3.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.2.2.3.4. Tags

- channels.apps.open-cluster-management.io

1.2.2.4. Delete a Channel

```
DELETE /apps.open-cluster-management.io/v1/namespaces/{namespace}/channels/{channel_name}
```

1.2.2.4.1. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	channel_name <i>required</i>	Name of the Channel that you want to delete.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.2.2.4.2. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.2.2.4.3. Tags

- `channels.apps.open-cluster-management.io`

1.2.3. Definitions

1.2.3.1. Channel

Name	Schema
apiVersion <i>required</i>	string
kind <i>required</i>	string
metadata <i>required</i>	object
spec <i>required</i>	spec

spec

Name	Description	Schema
configMapRef <i>optional</i>	ObjectReference contains enough information to let you inspect or modify the referred object.	configMapRef
gates <i>optional</i>	ChannelGate defines criteria for promote to channel	gates
pathname <i>required</i>		string

Name	Description	Schema
secretRef <i>optional</i>	ObjectReference contains enough information to let you inspect or modify the referred object.	secretRef
sourceNamespaces <i>optional</i>		< enum (Namespace, HelmRepo, ObjectBucket, Git, namespace, helmrepo, objectbucket, github) > array

configMapRef

Name	Description	Schema
apiVersion <i>optional</i>	API version of the referent.	string
fieldPath <i>optional</i>	If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as desiredState.manifest.containers[2]. For example, if the object reference is to a container within a pod, this would take on a value like "spec.containers{name}" (where "name" refers to the name of the container that triggered the event) or if no container name is specified "spec.containers[2]" (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object. TODO: this design is not final and this field is subject to change in the future.	string
kind <i>optional</i>	Kind of the referent. More info: https://git.k8s.io/community/contributors/devel/api-conventions.md#types-kinds	string
name <i>optional</i>	Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names	string
namespace <i>optional</i>	Namespace of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/namespaces/	string
resourceVersion <i>optional</i>	Specific resourceVersion to which this reference is made, if any. More info: https://git.k8s.io/community/contributors/devel/api-conventions.md#concurrency-control-and-consistency	string

Name	Description	Schema
uid <i>optional</i>	UID of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#uids	string

gates

Name	Description	Schema
annotations <i>optional</i>	typical annotations of k8s	annotations
labelSelector <i>optional</i>	A label selector is a label query over a set of resources. The result of matchLabels and matchExpressions are ANDed. An empty label selector matches all objects. A null label selector matches no objects.	labelSelector
name <i>optional</i>		string

annotations

Name	Schema
key <i>optional</i>	string
value <i>optional</i>	string

labelSelector

Name	Description	Schema
matchExpressions <i>optional</i>	matchExpressions is a list of label selector requirements. The requirements are ANDed.	< matchExpressions > array
matchLabels <i>optional</i>	matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.	< string, string > map

matchExpressions

Name	Description	Schema
key <i>required</i>	key is the label key that the selector applies to.	string
operator <i>required</i>	operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.	string
values <i>optional</i>	values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.	< string > array

secretRef

Name	Description	Schema
apiVersion <i>optional</i>	API version of the referent.	string
fieldPath <i>optional</i>	If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as desiredState.manifest.containers[2]. For example, if the object reference is to a container within a pod, this would take on a value like: "spec.containers{name}" (where "name" refers to the name of the container that triggered the event) or if no container name is specified "spec.containers[2]" (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object. TODO: this design is not final and this field is subject to change in the future.	string
kind <i>optional</i>	Kind of the referent. More info: https://git.k8s.io/community/contributors/devel/api-conventions.md#types-kinds	string
name <i>optional</i>	Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names	string
namespace <i>optional</i>	Namespace of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/namespaces/	string
resourceVersion <i>optional</i>	Specific resourceVersion to which this reference is made, if any. More info: https://git.k8s.io/community/contributors/devel/api-conventions.md#concurrency-control-and-consistency	string
uid <i>optional</i>	UID of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#uids	string

1.3. SUBSCRIPTIONS API

1.3.1. Overview

This documentation is for the Subscription resource for Red Hat Advanced Cluster Management for Kubernetes. The Subscription resource has four possible requests: create, query, delete and update.

1.3.1.1. Version information

Version : 2.0.0

1.3.1.2. Contact information

Contact Email : apiteam@swagger.io

1.3.1.3. License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

Terms of service : <http://swagger.io/terms/>

1.3.1.4. URI scheme

BasePath : /kubernetes/apis

Schemes : HTTPS

1.3.1.5. Tags

- `subscriptions.apps.open-cluster-management.io` : Create and manage subscriptions

1.3.1.6. External Docs

Description : Find out more about Swagger.

URL : <http://swagger.io>

1.3.2. Paths

1.3.2.1. Create a subscription

POST /apps.open-cluster-management.io/v1/namespaces/{namespace}/subscriptions

1.3.2.1.1. Description

Create a subscription.

1.3.2.1.2. Parameters

Type	Name	Description	Schema
------	------	-------------	--------

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string
Body	body <i>required</i>	Parameters describing the subscription to be created.	Subscription

1.3.2.1.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.3.2.1.4. Consumes

- **subscription/yaml**

1.3.2.1.5. Tags

- subscriptions.apps.open-cluster-management.io

1.3.2.1.6. Example HTTP request

1.3.2.1.6.1. Request body

```
{
  "apiVersion": "apps.open-cluster-management.io/v1",
  "kind": "Subscription",
  "metadata": {
    "name": "sample_subscription",
    "namespace": "default",
    "labels": {
      "app": "sample_subscription-app"
    }
  },
  "annotations": {
```

```

    "apps.open-cluster-management.io/git-path" : "apps/sample/",
    "apps.open-cluster-management.io/git-branch" : "sample_branch"
  }
},
"spec" : {
  "channel" : "channel_namespace/sample_channel",
  "packageOverrides" : [ {
    "packageName" : "my-sample-application",
    "packageAlias" : "the-sample-app",
    "packageOverrides" : [ {
      "path" : "spec",
      "value" : {
        "persistence" : {
          "enabled" : false,
          "useDynamicProvisioning" : false
        },
        "license" : "accept",
        "tls" : {
          "hostname" : "my-mcm-cluster.icp"
        },
        "sso" : {
          "registrationImage" : {
            "pullSecret" : "hub-repo-docker-secret"
          }
        }
      }
    }
  ]
},
"placement" : {
  "placementRef" : {
    "kind" : "PlacementRule",
    "name" : "demo-clusters"
  }
}
}
}
}

```

1.3.2.2. Query all subscriptions

```
GET /apps.open-cluster-management.io/v1/namespaces/{namespace}/subscriptions
```

1.3.2.2.1. Description

Query your subscriptions for more details.

1.3.2.2.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string

Type	Name	Description	Schema
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.3.2.2.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.3.2.2.4. Consumes

- **subscription/yaml**

1.3.2.2.5. Tags

- subscriptions.apps.open-cluster-management.io

1.3.2.3. Query a single subscription

```
GET /apps.open-cluster-management.io/v1/namespaces/{namespace}/subscriptions/{subscription_name}
```

1.3.2.3.1. Description

Query a single subscription for more details.

1.3.2.3.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

Type	Name	Description	Schema
Path	subscription_name <i>required</i>	Name of the subscription that you wan to query.	string

1.3.2.3.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.3.2.3.4. Tags

- subscriptions.apps.open-cluster-management.io

1.3.2.4. Delete a subscription

DELETE /apps.open-cluster-management.io/v1/namespaces/{namespace}/subscriptions/{subscription_name}

1.3.2.4.1. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string
Path	subscription_name <i>required</i>	Name of the subscription that you want to delete.	string

1.3.2.4.2. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.3.2.4.3. Tags

- `subscriptions.apps.open-cluster-management.io`

1.3.3. Definitions

1.3.3.1. Subscription

Name	Schema
apiVersion <i>required</i>	string
kind <i>required</i>	string
metadata <i>required</i>	metadata
spec <i>required</i>	spec
status <i>optional</i>	status

metadata

Name	Schema
annotations <i>optional</i>	object
labels <i>optional</i>	object

Name	Schema
name <i>optional</i>	string
namespace <i>optional</i>	string

spec

Name	Schema
channel <i>required</i>	string
name <i>optional</i>	string
overrides <i>optional</i>	< overrides > array
packageFilter <i>optional</i>	packageFilter
packageOverrides <i>optional</i>	< packageOverrides > array
placement <i>optional</i>	placement
timewindow <i>optional</i>	timewindow

overrides

Name	Schema
clusterName <i>required</i>	string
clusterOverrides <i>required</i>	< object > array

packageFilter

Name	Description	Schema
annotations <i>optional</i>		< string, string > map
filterRef <i>optional</i>		filterRef
labelSelector <i>optional</i>		labelSelector
version <i>optional</i>	Pattern : "()(\\.[0-9])(\\.) (\\.[0-9])?(\\.[xX])"	string

filterRef

Name	Schema
name <i>optional</i>	string

labelSelector

Name	Schema
matchExpressions <i>optional</i>	< matchExpressions > array
matchLabels <i>optional</i>	< string, string > map

matchExpressions

Name	Schema
key <i>required</i>	string
operator <i>required</i>	string
values <i>optional</i>	< string > array

packageOverrides

Name	Schema
packageAlias <i>optional</i>	string
packageName <i>required</i>	string
packageOverrides <i>optional</i>	< object > array

placement

Name	Schema
clusterSelector <i>optional</i>	clusterSelector
clusters <i>optional</i>	< clusters > array
local <i>optional</i>	boolean
placementRef <i>optional</i>	placementRef

clusterSelector

Name	Schema
matchExpressions <i>optional</i>	< matchExpressions > array
matchLabels <i>optional</i>	< string, string > map

matchExpressions

Name	Schema
key <i>required</i>	string
operator <i>required</i>	string

Name	Schema
values <i>optional</i>	< string > array

clusters

Name	Schema
name <i>required</i>	string

placementRef

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string
namespace <i>optional</i>	string
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

timewindow

Name	Schema
daysofweek <i>optional</i>	< string > array
hours <i>optional</i>	< hours > array

Name	Schema
location <i>optional</i>	string
windowType <i>optional</i>	enum (active, blocked, Active, Blocked)

hours

Name	Schema
end <i>optional</i>	string
start <i>optional</i>	string

status

Name	Schema
lastUpdateTime <i>optional</i>	string (date-time)
message <i>optional</i>	string
phase <i>optional</i>	string
reason <i>optional</i>	string
statuses <i>optional</i>	object

1.4. PLACEMENTRULES API

1.4.1. Overview

This documentation is for the Placementrule resource for Red Hat Advanced Cluster Management for Kubernetes. The Placementrule resource has four possible requests: create, query, delete and update.

1.4.1.1. Version information

Version : 2.0.0

1.4.1.2. Contact information

Contact Email : apiteam@swagger.io

1.4.1.3. License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

Terms of service : <http://swagger.io/terms/>

1.4.1.4. URI scheme

BasePath : /kubernetes/apis

Schemes : HTTPS

1.4.1.5. Tags

- `placementrules.apps.open-cluster-management.io` : Create and manage placementrules

1.4.1.6. External Docs

Description : Find out more about Swagger.

URL : <http://swagger.io>

1.4.2. Paths

1.4.2.1. Create a placementrule

POST /apps.open-cluster-management.io/v1/namespaces/{namespace}/placementrules

1.4.2.1.1. Description

Create a placementrule.

1.4.2.1.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN} ; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string
Body	body <i>required</i>	Parameters describing the placementrule to be created.	Placementrule

1.4.2.1.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.4.2.1.4. Consumes

- **application/yaml**

1.4.2.1.5. Tags

- placementrules.apps.open-cluster-management.io

1.4.2.1.6. Example HTTP request

1.4.2.1.6.1. Request body

```
{
  "apiVersion": "apps.open-cluster-management.io/v1",
  "kind": "PlacementRule",
  "metadata": {
    "name": "towhichcluster",
    "namespace": "ns-sub-1"
  },
  "spec": {
    "clusterConditions": [ {
      "type": "ManagedClusterConditionAvailable",
      "status": "True"
    } ],
    "clusterSelector": { }
  }
}
```

1.4.2.2. Query all placementrules

```
GET /apps.open-cluster-management.io/v1/namespaces/{namespace}/placementrules
```

1.4.2.2.1. Description

Query your placementrules for more details.

1.4.2.2.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.4.2.2.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.4.2.2.4. Consumes

- **application/yaml**

1.4.2.2.5. Tags

- placementrules.apps.open-cluster-management.io

1.4.2.3. Query a single placementrule

```
GET /apps.open-cluster-management.io/v1/namespaces/{namespace}/placementrules/{placementrule_name}
```

1.4.2.3.1. Description

Query a single placementrule for more details.

1.4.2.3.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string

Type	Name	Description	Schema
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string
Path	placementrule_name <i>required</i>	Name of the placementrule that you want to query.	string

1.4.2.3.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.4.2.3.4. Tags

- placementrules.apps.open-cluster-management.io

1.4.2.4. Delete a placementrule

```
DELETE /apps.open-cluster-management.io/v1/namespaces/{namespace}/placementrules/{placementrule_name}
```

1.4.2.4.1. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

Type	Name	Description	Schema
Path	placementrule_name <i>required</i>	Name of the placementrule that you want to delete.	string

1.4.2.4.2. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.4.2.4.3. Tags

- `placementrules.apps.open-cluster-management.io`

1.4.3. Definitions

1.4.3.1. Placementrule

Name	Schema
apiVersion <i>required</i>	string
kind <i>required</i>	string
metadata <i>required</i>	object
spec <i>required</i>	spec

spec

Name	Schema
clusterConditions <i>optional</i>	< clusterConditions > array
clusterReplicas <i>optional</i>	integer
clusterSelector <i>optional</i>	clusterSelector
clusters <i>optional</i>	< clusters > array
policies <i>optional</i>	< policies > array
resourceHint <i>optional</i>	resourceHint
schedulerName <i>optional</i>	string

clusterConditions

Name	Schema
status <i>optional</i>	string
type <i>optional</i>	string

clusterSelector

Name	Schema
matchExpressions <i>optional</i>	< matchExpressions > array
matchLabels <i>optional</i>	< string, string > map

matchExpressions

Name	Schema
key <i>optional</i>	string
operator <i>optional</i>	string
values <i>optional</i>	< string > array

clusters

Name	Schema
name <i>optional</i>	string

policies

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string
namespace <i>optional</i>	string
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

resourceHint

Name	Schema
order <i>optional</i>	string
type <i>optional</i>	string

1.5. APPLICATIONS API

1.5.1. Overview

This documentation is for the Application resource for Red Hat Advanced Cluster Management for Kubernetes. Application resource has four possible requests: create, query, delete and update.

1.5.1.1. Version information

Version : 2.0.0

1.5.1.2. Contact information

Contact Email : apiteam@swagger.io

1.5.1.3. License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

Terms of service : <http://swagger.io/terms/>

1.5.1.4. URI scheme

BasePath : /kubernetes/apis

Schemes : HTTPS

1.5.1.5. Tags

- `applications.app.k8s.io` : Create and manage applications

1.5.1.6. External Docs

Description : Find out more about Swagger.

URL : <http://swagger.io>

1.5.2. Paths

1.5.2.1. Create a application

POST /app.k8s.io/v1beta1/namespaces/{namespace}/applications

1.5.2.1.1. Description

Create a application.

1.5.2.1.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN} ; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string
Body	body <i>required</i>	Parameters describing the application to be created.	Application

1.5.2.1.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.5.2.1.4. Consumes

- **application/yaml**

1.5.2.1.5. Tags

- applications.app.k8s.io

1.5.2.1.6. Example HTTP request

1.5.2.1.6.1. Request body

```
{
  "apiVersion" : "app.k8s.io/v1beta1",
  "kind" : "Application",
  "metadata" : {
    "labels" : {
```

```

    "app" : "nginx-app-details"
  },
  "name" : "nginx-app-3",
  "namespace" : "ns-sub-1"
},
"spec" : {
  "componentKinds" : [ {
    "group" : "apps.open-cluster-management.io",
    "kind" : "Subscription"
  } ]
},
"selector" : {
  "matchLabels" : {
    "app" : "nginx-app-details"
  }
},
"status" : { }
}

```

1.5.2.2. Query all applications

```
GET /app.k8s.io/v1beta1/namespaces/{namespace}/applications
```

1.5.2.2.1. Description

Query your applications for more details.

1.5.2.2.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.5.2.2.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content

HTTP Code	Description	Schema
503	Service unavailable	No Content

1.5.2.2.4. Consumes

- **application/yaml**

1.5.2.2.5. Tags

- applications.app.k8s.io

1.5.2.3. Query a single application

```
GET /app.k8s.io/v1beta1/namespaces/{namespace}/applications/{application_name}
```

1.5.2.3.1. Description

Query a single application for more details.

1.5.2.3.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN} ; ACCESS_TOKEN is the user access token.	string
Path	application_name <i>required</i>	Name of the application that you wan to query.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.5.2.3.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content

HTTP Code	Description	Schema
503	Service unavailable	No Content

1.5.2.3.4. Tags

- applications.app.k8s.io

1.5.2.4. Delete a application

```
DELETE /app.k8s.io/v1beta1/namespaces/{namespace}/applications/{application_name}
```

1.5.2.4.1. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	application_name <i>required</i>	Name of the application that you want to delete.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.5.2.4.2. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.5.2.4.3. Tags

- applications.app.k8s.io

1.5.3. Definitions

1.5.3.1. Application

Name	Schema
apiVersion <i>required</i>	string
kind <i>required</i>	string
metadata <i>required</i>	object
spec <i>required</i>	spec

spec

Name	Schema
assemblyPhase <i>optional</i>	string
componentKinds <i>optional</i>	< object > array
descriptor <i>optional</i>	descriptor
info <i>optional</i>	< info > array
selector <i>optional</i>	object

descriptor

Name	Schema
description <i>optional</i>	string
icons <i>optional</i>	< icons > array

Name	Schema
keywords <i>optional</i>	< string > array
links <i>optional</i>	< links > array
maintainers <i>optional</i>	< maintainers > array
notes <i>optional</i>	string
owners <i>optional</i>	< owners > array
type <i>optional</i>	string
version <i>optional</i>	string

icons

Name	Schema
size <i>optional</i>	string
src <i>required</i>	string
type <i>optional</i>	string

links

Name	Schema
description <i>optional</i>	string
url <i>optional</i>	string

maintainers

Name	Schema
email <i>optional</i>	string
name <i>optional</i>	string
url <i>optional</i>	string

owners

Name	Schema
email <i>optional</i>	string
name <i>optional</i>	string
url <i>optional</i>	string

info

Name	Schema
name <i>optional</i>	string
type <i>optional</i>	string
value <i>optional</i>	string
valueFrom <i>optional</i>	valueFrom

valueFrom

Name	Schema
configMapKeyRef <i>optional</i>	configMapKeyRef

Name	Schema
ingressRef <i>optional</i>	ingressRef
secretKeyRef <i>optional</i>	secretKeyRef
serviceRef <i>optional</i>	serviceRef
type <i>optional</i>	string

configMapKeyRef

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
key <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string
namespace <i>optional</i>	string
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

ingressRef

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
host <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string
namespace <i>optional</i>	string
path <i>optional</i>	string
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

secretKeyRef

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
key <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string

Name	Schema
namespace <i>optional</i>	string
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

serviceRef

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string
namespace <i>optional</i>	string
path <i>optional</i>	string
port <i>optional</i>	integer (int32)
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

1.6. HELM API

1.6.1. Overview

This documentation is for the HelmRelease resource for Red Hat Advanced Cluster Management for Kubernetes. The HelmRelease resource has four possible requests: create, query, delete and update.

1.6.1.1. Version information

Version : 2.0.0

1.6.1.2. Contact information

Contact Email : apiteam@swagger.io

1.6.1.3. License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

Terms of service : <http://swagger.io/terms/>

1.6.1.4. URI scheme

BasePath : /kubernetes/apis

Schemes : HTTPS

1.6.1.5. Tags

- helmreleases.apps.open-cluster-management.io : Create and manage helmreleases

1.6.1.6. External Docs

Description : Find out more about Swagger.

URL : <http://swagger.io>

1.6.2. Paths

1.6.2.1. Create a helmrelease

POST /apps.open-cluster-management.io/v1/namespaces/{namespace}/helmreleases

1.6.2.1.1. Description

Create a helmrelease.

1.6.2.1.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

Type	Name	Description	Schema
Body	body <i>required</i>	Parameters describing the helmrelease to be created.	HelmRelease

1.6.2.1.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.6.2.1.4. Consumes

- **application/yaml**

1.6.2.1.5. Tags

- helmreleases.apps.open-cluster-management.io

1.6.2.1.6. Example HTTP request

1.6.2.1.6.1. Request body

```
{
  "apiVersion": "apps.open-cluster-management.io/v1",
  "kind": "HelmRelease",
  "metadata": {
    "name": "nginx-ingress",
    "namespace": "default"
  },
  "repo": {
    "chartName": "nginx-ingress",
    "source": {
      "helmRepo": {
        "urls": [ "https://kubernetes-charts.storage.googleapis.com/nginx-ingress-1.26.0.tgz" ]
      },
      "type": "helmrepo"
    }
  },
  "version": "1.26.0"
}
```

```

    },
    "spec" : {
      "defaultBackend" : {
        "replicaCount" : 3
      }
    }
  }
}

```

1.6.2.2. Query all helmreleases

GET /apps.open-cluster-management.io/v1/namespaces/{namespace}/helmreleases

1.6.2.2.1. Description

Query your helmreleases for more details.

1.6.2.2.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.6.2.2.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.6.2.2.4. Consumes

- **application/yaml**

1.6.2.2.5. Tags

- helmreleases.apps.open-cluster-management.io

1.6.2.3. Query a single helmrelease

```
GET /apps.open-cluster-
management.io/v1/namespaces/{namespace}/helmreleases/{helmrelease_name}
```

1.6.2.3.1. Description

Query a single helmrelease for more details.

1.6.2.3.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	helmrelease_name <i>required</i>	Name of the helmrelease that you want to query.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.6.2.3.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.6.2.3.4. Tags

- helmreleases.apps.open-cluster-management.io

1.6.2.4. Delete a helmrelease

```
DELETE /apps.open-cluster-
management.io/v1/namespaces/{namespace}/helmreleases/{helmrelease_name}
```

1.6.2.4.1. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	helmrelease_name <i>required</i>	Name of the helmrelease that you want to delete.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.6.2.4.2. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.6.2.4.3. Tags

- `helmreleases.apps.open-cluster-management.io`

1.6.3. Definitions

1.6.3.1. HelmRelease

Name	Schema
apiVersion <i>required</i>	string
kind <i>required</i>	string
metadata <i>required</i>	object

Name	Schema
repo <i>required</i>	repo
spec <i>required</i>	object
status <i>required</i>	status

repo

Name	Schema
chartName <i>optional</i>	string
configMapRef <i>optional</i>	configMapRef
secretRef <i>optional</i>	secretRef
source <i>optional</i>	source
version <i>optional</i>	string

configMapRef

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string

Name	Schema
namespace <i>optional</i>	string
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

secretRef

Name	Schema
apiVersion <i>optional</i>	string
fieldPath <i>optional</i>	string
kind <i>optional</i>	string
name <i>optional</i>	string
namespace <i>optional</i>	string
resourceVersion <i>optional</i>	string
uid <i>optional</i>	string

source

Name	Schema
github <i>optional</i>	github
helmRepo <i>optional</i>	helmRepo

Name	Schema
type <i>optional</i>	string

github

Name	Schema
branch <i>optional</i>	string
chartPath <i>optional</i>	string
urls <i>optional</i>	< string > array

helmRepo

Name	Schema
urls <i>optional</i>	< string > array

status

Name	Schema
conditions <i>required</i>	< conditions > array
deployedRelease <i>optional</i>	deployedRelease

conditions

Name	Schema
lastTransitionTime <i>optional</i>	string (date-time)
message <i>optional</i>	string

Name	Schema
reason <i>optional</i>	string
status <i>required</i>	string
type <i>required</i>	string

deployedRelease

Name	Schema
manifest <i>optional</i>	string
name <i>optional</i>	string

1.7. POLICY API

1.7.1. Overview

This documentation is for the Policy resource for Red Hat Advanced Cluster Management for Kubernetes. The Policy resource has four possible requests: create, query, delete and update.

1.7.1.1. Version information

Version : 2.0.0

1.7.1.2. Contact information

Contact Email : apiteam@swagger.io

1.7.1.3. License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

Terms of service : <http://swagger.io/terms/>

1.7.1.4. URI scheme

BasePath : /kubernetes/apis

Schemes : HTTPS

1.7.1.5. Tags

- `policy.open-cluster-management.io/v1` : Create and manage policies

1.7.1.6. External Docs

Description : Find out more about Swagger.

URL : <http://swagger.io>

1.7.2. Paths

1.7.2.1. Create a policy

POST `/policy.open-cluster-management.io/v1/v1alpha1/namespaces/{namespace}/policies/{policy_name}`

1.7.2.1.1. Description

Create a policy.

1.7.2.1.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string
Body	body <i>required</i>	Parameters describing the policy to be created.	Application

1.7.2.1.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.7.2.1.4. Consumes

- **application/json**

1.7.2.1.5. Tags

- `policy.open-cluster-management.io`

1.7.2.1.6. Example HTTP request

1.7.2.1.6.1. Request body

```
{
  "apiVersion": "policy.open-cluster-management.io/v1/v1alpha1",
  "kind": "Policy",
  "metadata": {
    "name": "test-policy-swagger",
    "description": "Example body for Policy API Swagger docs"
  },
  "spec": {
    "remediationAction": "enforce",
    "namespaces": {
      "include": [
        "default"
      ],
      "exclude": [
        "kube*"
      ]
    },
    "policy-templates": {
      "kind": "ConfigurationPolicy",
      "apiVersion": "policy.open-cluster-management.io/v1alpha1",
      "complianceType": "musthave",
      "metadata": {
        "namespace": null,
        "name": "test-role"
      },
      "selector": {
        "matchLabels": {
          "cloud": "IBM"
        }
      },
      "spec": {
        "object-templates": {
          "complianceType": "mustHave",
          "objectDefinition": {
            "apiVersion": "rbac.authorization.k8s.io/v1",
            "kind": "Role",
            "metadata": {
              "name": "role-policy",
            },
            "rules": [
              {
                "apiGroups": [
                  "extensions",
                  "apps"
                ],

```



```
    "resources": [
      "deployments"
    ],
    "verbs": [
      "get",
      "list",
      "watch",
      "delete"
    ]
  },
  {
    "apiGroups": [
      "core"
    ],
    "resources": [
      "pods"
    ],
    "verbs": [
      "create",
      "update",
      "patch"
    ]
  },
  {
    "apiGroups": [
      "core"
    ],
    "resources": [
      "secrets"
    ],
    "verbs": [
      "get",
      "watch",
      "list",
      "create",
      "delete",
      "update",
      "patch"
    ]
  },
],
},
],
},
},
},
},
},
```

1.7.2.2. Query all policies

```
GET /policy.open-cluster-management.io/v1/v1alpha1/namespaces/{namespace}/policies/{policy_name}
```

1.7.2.2.1. Description

Query your policies for more details.

1.7.2.2.2. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	namespace <i>required</i>	Namespace that you want to apply the policy to, for example, default.	string

1.7.2.2.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.7.2.2.4. Consumes

- **application/json**

1.7.2.2.5. Tags

- policy.open-cluster-management.io

1.7.2.3. Query a single policy

```
GET /policy.open-cluster-management.io/v1/v1alpha1/namespaces/{namespace}/policies/{policy_name}
```

1.7.2.3.1. Description

Query a single policy for more details.

1.7.2.3.2. Parameters

Type	Name	Description	Schema
------	------	-------------	--------

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	policy_name <i>required</i>	Name of the policy that you want to query.	string
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.7.2.3.3. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.7.2.3.4. Tags

- policy.open-cluster-management.io

1.7.2.4. Delete a policy

```
DELETE /policy.open-cluster-
management.io/v1/v1alpha1/namespaces/{namespace}/policies/{policy_name}
```

1.7.2.4.1. Parameters

Type	Name	Description	Schema
Header	COOKIE <i>required</i>	Authorization: Bearer {ACCESS_TOKEN}; ACCESS_TOKEN is the user access token.	string
Path	policy_name <i>required</i>	Name of the policy that you want to delete.	string

Type	Name	Description	Schema
Path	namespace <i>required</i>	Namespace that you want to use, for example, default.	string

1.7.2.4.2. Responses

HTTP Code	Description	Schema
200	Success	No Content
403	Access forbidden	No Content
404	Resource not found	No Content
500	Internal service error	No Content
503	Service unavailable	No Content

1.7.2.4.3. Tags

- policy.open-cluster-management.io

1.7.3. Definitions

1.7.3.1. Policy

Name	Description	Schema
apiVersion <i>required</i>	The versioned schema of Policy.	string
kind <i>required</i>	String value that represents the REST resource.	string
metadata <i>required</i>	Describes rules that define the policy.	object

spec

Name	Description	Schema
remediationAction <i>optional</i>	Value that represents how violations are handled as defined in the resource.	string

Name	Description	Schema
namespace <i>required</i>	Value that represents which namespaces the policy is applied.	string

policy-templates

Name	Description	Schema
apiVersion <i>required</i>	The versioned schema of Policy.	string
kind <i>optional</i>	String value that represents the REST resource.	string
complianceType <i>required</i>	The compliance standard.	string
metadata <i>required</i>	Describes rules that define the policy.	object
clusterConditions <i>optional</i>	Section to define labels.	string
rules <i>optional</i>		string

selector

Name	Description	Schema
matchLabels <i>optional</i>	The label that is required for the policy to be applied to a namespace.	object
cloud <i>optional</i>	The label that is required for the policy to be applied to a cloud provider.	string

rules

Name	Description	Schema
apiGroups <i>required</i>	List of APIs that the rule applies to.	string

Name	Description	Schema
resources <i>required</i>	A list of resource types.	object
verbs <i>required</i>	A list of verbs.	string