



Red Hat Decision Manager 7.13

Release notes for Red Hat Decision Manager 7.13

Red Hat Decision Manager 7.13 Release notes for Red Hat Decision Manager 7.13

Legal Notice

Copyright © 2024 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document contains release notes for Red Hat Decision Manager 7.13.

Table of Contents

PREFACE	5
MAKING OPEN SOURCE MORE INCLUSIVE	6
CHAPTER 1. PRODUCT OVERVIEW	7
CHAPTER 2. NEW FEATURES	8
2.1. UNIFIED PRODUCT DELIVERABLE AND DEPRECATION OF RED HAT DECISION MANAGER DISTRIBUTION FILES	8
2.2. ABILITY TO ONLY ENABLE DECISION MANAGEMENT COMPONENTS AND FUNCTIONALITY	8
2.3. ABILITY TO CHANGE THE ROUTE TERMINATION AND ENABLE EDGE TERMINATION	8
2.4. ABILITY TO USE A CUSTOM REGISTRY AND SPECIFIC IMAGES	8
2.5. ABILITY TO USE A SECRET FOR ADMIN USER DURING KIEAPP CONFIGURATION	8
2.6. ABILITY TO CHANGE THE ROUTE TERMINATION AND ENABLE EDGE TERMINATION	8
2.7. DMN DESIGNER	9
2.7.1. Drools DMN Engine support for DMN Specification v1.4	9
2.8. RED HAT OPENSIFT CONTAINER PLATFORM	9
2.8.1. Configurable startup strategy when using the Operator installer	9
2.8.2. Custom hostname routes	9
2.8.3. Improved SSL configurability	9
2.8.4. Default configuration for Cross Domain Resource Sharing (CORS)	9
2.8.5. Red Hat Data Grid user name and password configuration on Red Hat OpenShift Container Platform	9
2.9. RED HAT BUILD OF OPTAPLANNER	9
2.9.1. Red Hat build of OptaPlanner solver with Micrometer	9
2.10. RED HAT OPENSIFT CONTAINER PLATFORM	9
2.10.1. Custom host name routes	9
2.10.2. Improved SSL configurability	9
2.10.3. Default configuration for cross domain resource sharing (CORS)	10
CHAPTER 3. SUPPORT AND COMPATIBILITY	11
CHAPTER 4. DEPRECATED COMPONENTS	12
4.1. BUSINESS OPTIMIZER	12
4.2. OPTAPLANNER 7	12
4.3. OPTAPLANNER TOOLING COMPONENTS IN BUSINESS CENTRAL	12
4.4. UNIFIED PRODUCT DELIVERABLE AND DEPRECATION OF RED HAT DECISION MANAGER DISTRIBUTION FILES	12
4.5. RED HAT OPENSIFT CONTAINER PLATFORM 3	12
4.6. RED HAT ENTERPRISE LINUX 7	12
4.7. SUPPORT FOR JDK 8	13
4.8. LEGACY KIE-PMML DEPENDENCY	13
4.9. SUPPORT FOR OSGI FRAMEWORK INTEGRATION	13
4.10. SUPPORT FOR THE RULEUNIT API	13
4.11. LEGACY TEST SCENARIOS TOOL	13
4.12. SUPPORT FOR HACEP	13
CHAPTER 5. TECHNOLOGY PREVIEW	14
5.1. DEPLOYING A HIGH-AVAILABILITY AUTHORIZING ENVIRONMENT ON RED HAT OPENSIFT CONTAINER PLATFORM 4.X	14
5.2. OPENSIFT OPERATOR INSTALLER WIZARD	14
5.3. AUTHORIZING PERSPECTIVE CUSTOMIZATION	14
5.4. RED HAT BUILD OF OPTAPLANNER NEW CONSTRAINT COLLECTORS	14
5.5. RED HAT BUILD OF KOGITO AND KAFKA INTEGRATION	15

CHAPTER 6. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13	16
6.1. SPRING BOOT	16
6.2. RED HAT BUILD OF KOGITO	16
CHAPTER 7. FIXED ISSUES IN RED HAT DECISION MANAGER 7.13	18
7.1. BUSINESS CENTRAL	18
7.2. BUILD AND ASSEMBLY	18
7.3. KIE SERVER	18
7.4. RED HAT BUILD OF KOGITO	18
7.5. DMN DESIGNER	18
7.6. MIGRATION	19
7.7. CERTIFICATION	19
7.8. RED HAT OPENSIFT CONTAINER PLATFORM	19
7.9. DECISION ENGINE	19
CHAPTER 8. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13.1	20
8.1. BUSINESS CENTRAL	20
8.2. FORM MODELER	20
8.3. RED HAT OPENSIFT CONTAINER PLATFORM	20
CHAPTER 9. FIXED ISSUES IN RED HAT DECISION MANAGER 7.13.1	22
9.1. BUSINESS CENTRAL	22
9.2. KIE SERVER	22
9.3. RED HAT BUILD OF KOGITO	22
9.4. DMN DESIGNER	22
9.5. CONFIGURATION	22
9.6. RED HAT OPENSIFT CONTAINER PLATFORM	22
9.7. DECISION ENGINE	23
CHAPTER 10. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13.2	24
10.1. RED HAT OPENSIFT CONTAINER PLATFORM	24
CHAPTER 11. FIXED ISSUES IN RED HAT DECISION MANAGER 7.13.2	25
11.1. BUSINESS CENTRAL	25
11.2. KIE SERVER	25
11.3. RED HAT OPENSIFT CONTAINER PLATFORM	25
11.4. DECISION ENGINE	25
CHAPTER 12. FIXED ISSUES IN RED HAT DECISION MANAGER 7.13.3	26
12.1. BUSINESS CENTRAL	26
12.2. RED HAT BUILD OF KOGITO	26
12.3. DMN DESIGNER	26
12.4. RED HAT OPENSIFT CONTAINER PLATFORM	26
12.5. DECISION ENGINE	26
CHAPTER 13. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13.4	27
13.1. BUSINESS CENTRAL	27
CHAPTER 14. FIXED ISSUES IN RED HAT DECISION MANAGER 7.13.4	28
14.1. BUSINESS CENTRAL	28
14.2. KIE SERVER	28
14.3. RED HAT OPENSIFT CONTAINER PLATFORM	28
14.4. DECISION ENGINE	29
CHAPTER 15. FIXED ISSUES IN RED HAT DECISION MANAGER 7.13.5	30
15.1. BUSINESS CENTRAL	30

15.2. KIE SERVER	30
15.3. DECISION ENGINE	30
APPENDIX A. VERSIONING INFORMATION	31
APPENDIX B. CONTACT INFORMATION	32

PREFACE

These release notes list new features, features in technology preview, known issues, and issues fixed in Red Hat Decision Manager 7.13.

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

CHAPTER 1. PRODUCT OVERVIEW

Red Hat Decision Manager is an open-source decision management platform that combines business rules management, complex event processing, Decision Model & Notation (DMN) execution, and Red Hat build of OptaPlanner for solving planning problems. It automates business decisions and makes that logic available to the entire business.

Business assets such as rules, decision tables, and DMN models are stored in a central repository. This ensures consistency, transparency, and the ability to audit across the business. Business users can modify business logic without requiring assistance from IT personnel.

Red Hat Decision Manager 7.13 provides increased stability, several fixed issues, and new features.

Red Hat Decision Manager is fully supported on Red Hat OpenShift Container Platform and can be installed on various platforms.

For information about the support policy for Red Hat Decision Manager, see the [Release maintenance plan for Red Hat Decision Manager 7.x and Red Hat Process Automation Manager 7.x](#).

CHAPTER 2. NEW FEATURES

This section highlights new features in Red Hat Decision Manager 7.13.

2.1. UNIFIED PRODUCT DELIVERABLE AND DEPRECATION OF RED HAT DECISION MANAGER DISTRIBUTION FILES

In the Red Hat Process Automation Manager 7.13 release, the distribution files for Red Hat Decision Manager will be replaced with Red Hat Process Automation Manager files. Note that there will not be any change to the Red Hat Decision Manager subscription and the support entitlements and fees will remain the same. Red Hat Decision Manager is a subset of Red Hat Process Automation Manager, and Red Hat Decision Manager subscribers will continue to receive full support for the decision management and optimization capabilities. The business process management (BPM) capabilities are exclusive to Red Hat Process Automation Manager and will be available for use by Red Hat Decision Manager subscribers but with development support services only. Red Hat Decision Manager subscribers can upgrade to a full Red Hat Process Automation Manager subscription at any time to receive full support for BPM features.

Red Hat Decision Manager container images are now deprecated with unified deliverables. Red Hat Decision Manager subscribers can upgrade or install the latest Red Hat Process Automation Manager images from version 7.13 onward instead.

2.2. ABILITY TO ONLY ENABLE DECISION MANAGEMENT COMPONENTS AND FUNCTIONALITY

You can now configure the deployment to only enable decision management related components and functionality so that jBPM and case management features are disabled.

2.3. ABILITY TO CHANGE THE ROUTE TERMINATION AND ENABLE EDGE TERMINATION

During configuration of the environment, you can now change the route termination, enable edge termination, and set optional credentials.

2.4. ABILITY TO USE A CUSTOM REGISTRY AND SPECIFIC IMAGES

You can now configure the custom registry to use specific images during the configuration of the environment.

2.5. ABILITY TO USE A SECRET FOR ADMIN USER DURING KIEAPP CONFIGURATION

You can now use a secret containing the credentials for the Admin user during KieApp configuration.

2.6. ABILITY TO CHANGE THE ROUTE TERMINATION AND ENABLE EDGE TERMINATION

During configuration of the environment, you can now change the route termination, enable edge termination and set optional credentials.

2.7. DMN DESIGNER

2.7.1. Drools DMN Engine support for DMN Specification v1.4

Red Hat Decision Manager now provides runtime support for DMN Specification v1.4 in the Drools DMN engine.

2.8. RED HAT OPENSIFT CONTAINER PLATFORM

2.8.1. Configurable startup strategy when using the Operator installer

When you deploy Red Hat Decision Manager on Red Hat OpenShift Container Platform using the operator installer, by default the deployment uses the **OpenShiftStartupStrategy** setting. You can now switch to the Controller startup strategy in the configuration user interface if necessary.

2.8.2. Custom hostname routes

You can now set custom hostnames for external routes by using the **routeHostname** property.

2.8.3. Improved SSL configurability

You can now enable or disable SSL in the operator and expose the SSL route.

2.8.4. Default configuration for Cross Domain Resource Sharing (CORS)

You can now specify whether to use a default or user customized CORS configuration.

2.8.5. Red Hat Data Grid user name and password configuration on Red Hat OpenShift Container Platform

When deploying a high-availability Red Hat Decision Manager environment on Red Hat OpenShift Container Platform, you can now configure the user name and password for the Red Hat Data Grid component.

2.9. RED HAT BUILD OF OPTAPLANNER

2.9.1. Red Hat build of OptaPlanner solver with Micrometer

Additional metrics are available for monitoring the OptaPlanner solver with Micrometer.

2.10. RED HAT OPENSIFT CONTAINER PLATFORM

2.10.1. Custom host name routes

You can now set custom host names for external routes by using the **routeHostname** property.

2.10.2. Improved SSL configurability


You can now enable or disable SSL in the operator and expose the SSL route.

2.10.3. Default configuration for cross domain resource sharing (CORS)

You can now specify whether to use a default or user-customized CORS configuration.

CHAPTER 3. SUPPORT AND COMPATIBILITY

This section highlights supported version updates in Red Hat Decision Manager 7.13.



NOTE

Oracle WebLogic Server (WLS) was not tested or verified for Red Hat Decision Manager 7.13.4 SP2.

For a complete list of supported configurations, see [Red Hat Decision Manager 7 Supported Configurations](#).

Table 3.1. Supported configurations in Red Hat Decision Manager 7.13

Component	Supported Version	Notes
Red Hat build of Quarkus	2.7.x	NA
Red Hat JBoss EAP	7.4.x	Red Hat Decision Manager now supports Red Hat JBoss EAP version 7.4.2 or later
Spring Boot	2.5.12	NA
AMQ Streams	2.2	Supported for high-availability event-driven decisions
Red Hat JBoss Web Server	5.6	NA
Red Hat OpenShift Container Platform	4.12	NA

CHAPTER 4. DEPRECATED COMPONENTS

The components listed in this section have been deprecated.

4.1. BUSINESS OPTIMIZER

Business Optimizer (OptaPlanner) 8.13.x, included as part of Red Hat Decision Manager, is in maintenance support. For the latest supported versions of OptaPlanner (8.29 and later) upgrade to Red Hat build of OptaPlanner, the newest addition to Red Hat Application Foundations. For more info, see [Red Hat build of OptaPlanner is now available in Red Hat Application Foundations](#) .

4.2. OPTAPLANNER 7

Both OptaPlanner 7 and OptaPlanner 8 are included with Red Hat Decision Manager 7.13, but OptaPlanner 7 is deprecated and might be removed in a future release. For information about migrating your OptaPlanner 7 projects to OptaPlanner 8, see [Upgrading your Red Hat build of OptaPlanner projects to OptaPlanner 8](#).

4.3. OPTAPLANNER TOOLING COMPONENTS IN BUSINESS CENTRAL

The following OptaPlanner tooling in Business Central is part of OptaPlanner 7. They are deprecated and might be removed in a future release.

- Data modeler annotations
- Guided rule editor actions for OptaPlanner score modification
- Solver assets

4.4. UNIFIED PRODUCT DELIVERABLE AND DEPRECATION OF RED HAT DECISION MANAGER DISTRIBUTION FILES

In the Red Hat Process Automation Manager 7.13 release, the distribution files for Red Hat Decision Manager will be replaced with Red Hat Process Automation Manager files. Note that there will not be any change to the Red Hat Decision Manager subscription and the support entitlements and fees will remain the same. Red Hat Decision Manager is a subset of Red Hat Process Automation Manager, and Red Hat Decision Manager subscribers will continue to receive full support for the decision management and optimization capabilities. The business process management (BPM) capabilities are exclusive to Red Hat Process Automation Manager and will be available for use by Red Hat Decision Manager subscribers but with development support services only. Red Hat Decision Manager subscribers can upgrade to a full Red Hat Process Automation Manager subscription at any time to receive full support for BPM features.

Red Hat Decision Manager container images are now deprecated with unified deliverables. Red Hat Decision Manager subscribers can upgrade or install the latest Red Hat Process Automation Manager images from version 7.13 onward instead.

4.5. RED HAT OPENSIFT CONTAINER PLATFORM 3

Support for Red Hat OpenShift Container Platform 3 is removed in this release

4.6. RED HAT ENTERPRISE LINUX 7

Support for Red Hat Enterprise Linux 7 is deprecated in Red Hat Decision Manager and features and will be removed in a future release.

4.7. SUPPORT FOR JDK 8

Support for JDK 8 is deprecated in Red Hat Decision Manager and might be removed in a future release.

For a complete list of supported JDK configurations, see [Red Hat Decision Manager 7 Supported Configurations](#).

4.8. LEGACY KIE-PMML DEPENDENCY

The legacy **kie-pmml** dependency was deprecated with Red Hat Decision Manager 7.10.0 and will be replaced in a future Red Hat Decision Manager release. For more information, see [Designing a decision service using PMML models](#).

4.9. SUPPORT FOR OSGI FRAMEWORK INTEGRATION

Support for integration with the OSGi framework is deprecated in Red Hat Decision Manager. It does not receive any new enhancements or features and will be removed in a future release. The decision and process engine integration with the OSGi framework is currently incompatible with Fuse version 7.8. If you intend to use the OSGi framework, continue to use Red Hat Decision Manager version 7.9 with Fuse version 7.7 until Fuse version 7.9 is available and certified.

4.10. SUPPORT FOR THE RULEUNIT API

The Red Hat Decision Manager RuleUnit API is deprecated due to incompatibility with the Kogito RuleUnit API.

4.11. LEGACY TEST SCENARIOS TOOL

The legacy Test Scenarios tool was deprecated in Red Hat Decision Manager version 7.3.0. It will be removed in a future Red Hat Decision Manager release. Use the new Test Scenarios designer instead.

4.12. SUPPORT FOR HACEP

High available (HA) event-driven decisioning, including Complex Event Processing (CEP), is deprecated due to end of support for AMQ Streams 1.x.

CHAPTER 5. TECHNOLOGY PREVIEW

This section lists features that are in Technology Preview in Red Hat Decision Manager 7.13. Business Central includes an experimental features administration page that is disabled by default. To enable this page, set the value of the **appformer.experimental.features** property to **true**.



IMPORTANT

These features are for Technology Preview only. Technology Preview features are not supported with Red Hat production service level agreements (SLAs), might not be functionally complete, and Red Hat does not recommend using them for production. These features provide early access to upcoming product features, enabling customers to test functionality and provide feedback during the development process.

For more information on Red Hat Technology Preview features, see [Technology Preview Features Scope](#).

5.1. DEPLOYING A HIGH-AVAILABILITY AUTHORIZING ENVIRONMENT ON RED HAT OPENSIFT CONTAINER PLATFORM 4.X

You can deploy a high-availability Red Hat Decision Manager authoring environment on Red Hat OpenShift Container Platform 4.x using the operator.

5.2. OPENSIFT OPERATOR INSTALLER WIZARD

An installer wizard is provided in the Red Hat OpenShift Container Platform operator for Red Hat Decision Manager. You can use the wizard to deploy a Red Hat Decision Manager environment on Red Hat OpenShift Container Platform with the operator.

5.3. AUTHORIZING PERSPECTIVE CUSTOMIZATION

You can perform the following tasks to customize the Business Central authoring perspective:

- Open a Business Central project directly using an URL path parameter, without going through a list of spaces and projects.
- Hide or show the project toolbar, **Metrics** tab, and **Change Request** tab according to your requirements.
- Enhance the pagination.
- Customize the number of assets present on the project screen.

5.4. RED HAT BUILD OF OPTAPLANNER NEW CONSTRAINT COLLECTORS

In order to provide a full implementation of some pre-existing OptaPlanner examples using the Constraint Streams API, the standard library of constraint collectors has been extended to include the following constraint collectors:

- One constraint collector takes point values such as dates, orders them on a number line, and makes groups of consecutive values with breaks between the groups available downstream.

- Another constraint collector takes interval values such as shifts, creates clusters of consecutive and possibly overlapping values with breaks between clusters, and makes the clusters available downstream.

These new collectors are in technology preview. Their interfaces, names, and functionality are subject to change. They have been placed in an experimental package outside of the public API to encourage public feedback before they become an officially supported part of the OptaPlanner public API.

5.5. RED HAT BUILD OF KOGITO AND KAFKA INTEGRATION

Red Hat build of Kogito decision microservices integration with managed Kafka by using the **org.kie.kogito:kogito-addons-{quarkus|springboot}-events-decisions** event-driven add-on is now available as technology preview. On Red Hat build of Quarkus, you can add the **io.quarkus:quarkus-kubernetes-service-binding** dependency to the application to handle the service binding created by the managed Kafka. On Spring boot, you must add the **mappings** field to the created service binding which must contain the required environment variables needed by the application. Another solution is to use the custom configuration maps available in the Red Hat build of Kogito operator.

CHAPTER 6. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13

This section lists known issues with Red Hat Decision Manager 7.13.

6.1. SPRING BOOT

Wrong managed version of Spring Boot dependencies [[RHPAM-4413](#)]

Issue: The Spring Boot version (2.6.6) in the Maven repository is not certified by Red Hat yet. Therefore, you will receive a mismatch for the Narayana starter in productized binaries.

Workaround: In your **pom.xml** file, define the following properties to override the current versions:

```
<version.org.springframework.boot>2.5.12</version.org.springframework.boot>
<version.me.snowdrop.narayana>2.6.3.redhat-00001</version.me.snowdrop.narayana>
```

6.2. RED HAT BUILD OF KOGITO

Red Hat build of Kogito is aligned with a non-supported Spring Boot version [[RHPAM-4419](#)]

Issue: Red Hat build of Kogito Spring Boot versions are managed in the **kogito-spring-boot-bom** file, which imports dependency management from the **org.springframework.boot:spring-boot-dependencies** BOM. The currently aligned version is 2.6.6, which does not map to any Red Hat supported versions. The latest supported version is 2.5.12. You must override dependency management with a BOM aligning to the Red Hat supported version which is 2.5.12.

Workaround:

1. To maintain the order of the imported BOM files, first include the Spring Boot BOM and then include the Red Hat build of Kogito specific BOM file:

```
<dependencyManagement>
  <dependencies>
    <dependency>
      <groupId>dev.snowdrop</groupId>
      <artifactId>snowdrop-dependencies</artifactId>
      <version>2.5.12.Final-redhat-00001</version>
      <type>pom</type>
      <scope>import</scope>
    </dependency>
    <dependency>
      <groupId>org.kie.kogito</groupId>
      <artifactId>kogito-spring-boot-bom</artifactId>
      <version>1.13.2.redhat-00002</version>
      <type>pom</type>
      <scope>import</scope>
    </dependency>
  </dependencies>
</dependencyManagement>
```

2. Align the version of **spring-boot-maven-plugin** to the same version in your project build configuration file:

```

<plugins>
  <plugin>
    <groupId>org.kie.kogito</groupId>
    <artifactId>kogito-maven-plugin</artifactId>
    <version>1.13.2.redhat-00002</version>
    <extensions>>true</extensions>
  </plugin>
  <plugin>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-maven-plugin</artifactId>
    <version>2.5.12</version>
    <executions>
      <execution>
        <goals>
          <goal>repackage</goal>
        </goals>
      </execution>
    </executions>
  </plugin>
</plugins>

```

Red Hat build of Kogito on Spring Boot leads to misalignment of Kafka-clients version [RHPAM-4418]

Issue: The Kafka-clients dependency version for Red Hat build of Kogito Spring Boot is by default managed by the **org.springframework.boot:spring-boot-dependencies** BOM. Depending on which Spring Boot version is used, users might end up with an unsupported or vulnerable version of Kafka-clients. You must override the default dependency in your **kogito-spring-boot-bom** to make sure you have the expected Kafka-clients version.

Workaround: In your projects, define **dependencyManagement** explicitly for **org.apache.kafka:kafka-clients** dependency to use the version released by AMQ Streams.

CHAPTER 7. FIXED ISSUES IN RED HAT DECISION MANAGER

7.13

Red Hat Decision Manager 7.13 provides increased stability and fixed issues listed in this section.

7.1. BUSINESS CENTRAL

- When you migrate to 7.12.0 version from a previous version, Business Central fails to start with the **no marshaller for type: org.guvnor.structure.contributors.Contributor** error [[RHPAM-4152](#)]
- Importing a project via SSH is not working over a proxy [[RHPAM-3954](#)]
- The guided rule expression editor text box splits the expression in multiple text boxes separated by dot(.) [[RHPAM-3679](#)]
- In guided decision table, allow the search feature for the data from an external datasource [[RHPAM-3415](#)]

7.2. BUILD AND ASSEMBLY

- When you are reading a specifically crafted TAR archive, an Apache Ant build allocates a large amount of memory that leads to an out-of-memory error even for small inputs [[RHPAM-3802](#)]

7.3. KIE SERVER

- if **JSONMarshaller** cannot find a class **com.nonexisting.Person** from a classloader, it deserializes the object as a **LinkedHashMap** with a **com.nonexisting.Person** key and it may result in no matching rule [[RHPAM-4134](#)]

7.4. RED HAT BUILD OF KOGITO

- It is not possible to run the tests for Red Hat build of Kogito examples which contain scenario simulation dependency. The Surefire plugin fails with an exception [[RHPAM-4068](#)]

7.5. DMN DESIGNER

- When you try to invoke a Business Knowledge Model (BKM) function from included DMN model, the validation fails [[RHDM-1395](#)]
- When you are validating a DMN file invoking a java function, you receive an error message [[RHPAM-3500](#)]
- Elbow lines for object connections do not work [[RHDM-1856](#)]
- When you are publishing a decision model using the **Documentation** tab in the DMN Modeller, a PDF file is generated. In the **Data Types** section, data type names are not readable when they are longer. The part of the data type names are replaced with three dots. [[RHDM-1690](#)]
- A standalone DMN editor is missing **isDirty** indication and fails to reflect changes in the data types or included models [[RHDM-1560](#)]

7.6. MIGRATION

- The distribution files for Red Hat Decision Manager will be replaced with Red Hat Process Automation Manager files [[RHPAM-3917](#)]

7.7. CERTIFICATION

- Dropping the support of HA CEP reference implementation due to end of life of AMQ Streams 1.x [[RHPAM-4416](#)]

7.8. RED HAT OPENSIFT CONTAINER PLATFORM

- When LDAP is integrated by an operator on Red Hat OpenShift Container Platform 4, the LDAP authentication fails because **direct-verification=true** is not set in LDAP realm [[RHPAM-4148](#)]
- Add a capability to configure route termination from CRD files [[RHPAM-4125](#)]
- when a **postconfigure.sh** script is introduced as an extension, it is not executed as custom KieServer S2I script unless another **delayedpostconfigure.sh** script is present [[RHPAM-3665](#)]
- The **ImageStreams** objects are not updated with the new image releases, it needs **importPolicy** [[RHPAM-4167](#)]

7.9. DECISION ENGINE

- The KJAR build fails with an executable model when you are comparing a **BigDecimal** type and **String** type property [[RHDM-1880](#)]
- The **varargs** argument invocations are not jitted correctly, the varargs argument is wrapped into an array even when not necessary [[RHPAM-4186](#)]
- Inconsistent property reactivity with JoinNode and FromNode [[RHDM-1881](#)]
- An executable model generates **BigDecimal** expressions without using a **MathContext** [[RHDM-1878](#)]
- The **SegmentPropagator** does not deal with a tuple staged as update and you receive an error [[RHDM-1875](#)]

CHAPTER 8. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13.1

This section lists known issues with Red Hat Decision Manager 7.13.1.

8.1. BUSINESS CENTRAL

Unable to deploy Business Central using JDK version 11.0.16 [[RHPAM-4497](#)]

Issue: It is not possible to deploy Business Central if your installation uses JDK version 11.0.16.

Actual result: Business Central does not deploy when launched.

Expected result: Business Central deploys successfully.

Workaround: Use a previous JDK version such as 11.0.5 or earlier.

8.2. FORM MODELER

Date type process variable is empty when the process is started using Business Central form with the `showTime` set to `false` [[RHPAM-4514](#)]

Issue: When you use the default form rendering in Business Central and the process variable field has **`showTime=false`**, the started process instance shows that the variable is empty. The affected types are **`java.time.LocalDateTime`**, **`java.time.LocalDate`**, **`java.time.LocalTime`**, and **`java.util.Date`**.

Steps to reproduce:

1. Define the process variable with a specific type.
2. Generate a form.
3. Open a form and set **`showTime=false`** for a specified field.
4. Deploy the project.
5. Open the process form.
6. Specify the value in the process form.
7. Check the process instance variables. The value for the specified variable is empty.

Workaround: None.

Form in KIE Server with a `java.util.Date` field does not allow the time to be inserted [[RHPAM-4513](#)]

Issue: When a process has a variable of type **`java.util.Date`**, the generated form, if the **`showTime`** attribute is **`true`**, does not allow inserting the time part. Then after submitting the **`Date`** variable shows all zeros in the time part of the datatype.

Workaround: None.

8.3. RED HAT OPENSIFT CONTAINER PLATFORM

PostgreSQL 13 Pod won't start because of an incompatible data directory [[RHPAM-4464](#)]

Issue: When you start a PostgreSQL pod after you upgrade the operator, the pod fails to start and you receive the following message:

Incompatible data directory. This container image provides PostgreSQL '13', but data directory is of version '10'. This image supports automatic data directory upgrade from '12', please carefully consult image documentation about how to use the '\$POSTGRESQL_UPGRADE' startup option.

Workaround:

1. Check the version of PostgreSQL:

```
$ postgres -V
```

2. If the PostgreSQL version returned is 12.x or earlier, upgrade PostgreSQL:

Red Hat Decision Manager version	PostgreSQL version	Upgrade instructions
7.13.1	7.10	Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 12.x.
7.13.2	7.10	<ol style="list-style-type: none"> 1. Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 12.x. 2. Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 13.x.
7.13.2	7.12	Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 13.x.

3. Verify that PostgreSQL has been upgraded to your required version:

```
$ postgres -V
```

CHAPTER 9. FIXED ISSUES IN RED HAT DECISION MANAGER

7.13.1

Red Hat Decision Manager 7.13.1 provides increased stability and fixed issues listed in this section.

9.1. BUSINESS CENTRAL

- The test scenario returns an error when it is executed in the **mvn test** command [[RHDM-1539](#)]

9.2. KIE SERVER

- A **ClassCastException** occurs if you submit a form in a **kie-server** that contains the date process variable [[RHPAM-4326](#)]
- The EJB service **saveContentFromUser** method does not work with the custom **usercontentcallback** and you receive an error message [[RHPAM-4234](#)]
- The custom query response does not return the **SLAduedate** with the **UserTasksWithCustomVariables** mapper [[RHPAM-4232](#)]
- The EventEmitter returns wrong task statuses [[RHPAM-4091](#)]
- The properties on custom settings are not available on the KIE Server deployments [[RHPAM-3976](#)]
- Class retention by **JSONMashaller ObjectMapper._typeFactory._typeCache** [[RHDM-1933](#)]
- The class retention by **JSONMashaller ObjectMapper._typeFactory._typeCache** and you receive **OutOfMemoryError: Metaspace** error [[RHDM-1933](#)]

9.3. RED HAT BUILD OF KOGITO

- Kogito aligned with non supported Spring Boot version [[RHPAM-4419](#)]

9.4. DMN DESIGNER

- In the DMN designer, a text annotation is not saved correctly if it created by copying and pasting [[RHDM-1890](#)]
- Unable to include the DMN model [[RHDM-1850](#)]

9.5. CONFIGURATION

- Wrong managed version of Spring Boot dependencies [[RHPAM-4413](#)]

9.6. RED HAT OPENSIFT CONTAINER PLATFORM

- Upgrade Red Hat JBoss EAP version to 7.4.6 on RHPAM image [[RHPAM-4481](#)]
- Sensitive information such as user names and passwords are exposed in environment variables and pod logs [[RHPAM-4438](#)]

- The Kie Server OpenShift startup strategy watcher is closed and the **DeploymentConfig** is not updated [[RHPAM-3333](#)]

9.7. DECISION ENGINE

- When you are using generics in accumulate inline code, you receive an error with the **ClassNotFoundException** exception [[RHPAM-4444](#)]
- The metrics of rule execution must include the rules fired from a BPMN process [[RHPAM-4248](#)]
- The **kie-server-client** fails to unmarshall a response suddenly with the **NumberFormatException** [[RHDM-1942](#)]
- The build fails with a "**_this cannot be resolved**" message during the compilation of a generated executable model [[RHDM-1940](#)]
- In an executable model, you receive a **NullPointerException** in **LambdaConsequence** error with global variable [[RHDM-1920](#)]
- Fails to parse a constraint connected with OR with a bind variable on right side in an executable model [[RHDM-1910](#)]
- In an executable model, when a **BigDecimal** literal is set to a variable with a MVEL dialect, you receive the **ClassCastException** exception [[RHDM-1908](#)]
- In an executable model, a prop with method invocation is not recognized in a modify block [[RHDM-1907](#)]
- In an executable model, an arithmetic operation with a **String** coercion in constraint fails to execute [[RHDM-1905](#)]
- In an executable model, an arithmetic operation with a **BigDecimal** in constraint fails [[RHDM-1904](#)]

CHAPTER 10. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13.2

This section lists known issues with Red Hat Decision Manager 7.13.2.

10.1. RED HAT OPENSIFT CONTAINER PLATFORM

PostgreSQL 13 Pod won't start because of an incompatible data directory [[RHPAM-4464](#)]

Issue: When you start a PostgreSQL pod after you upgrade the operator, the pod fails to start and you receive the following message:

Incompatible data directory. This container image provides PostgreSQL '13', but data directory is of version '10'. This image supports automatic data directory upgrade from '12', please carefully consult image documentation about how to use the '\$POSTGRESQL_UPGRADE' startup option.

Workaround:

1. Check the version of PostgreSQL:

```
$ postgres -V
```

2. If the PostgreSQL version returned is 12.x or earlier, upgrade PostgreSQL:

Red Hat Decision Manager version	PostgreSQL version	Upgrade instructions
7.13.1	7.10	Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 12.x.
7.13.2	7.10	<ol style="list-style-type: none"> 1. Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 12.x. 2. Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 13.x.
7.13.2	7.12	Follow the instructions in Upgrading database (by switching to newer PostgreSQL image version) to upgrade to PostgreSQL 13.x.

3. Verify that PostgreSQL has been upgraded to your required version:

```
$ postgres -V
```

CHAPTER 11. FIXED ISSUES IN RED HAT DECISION MANAGER

7.13.2

Red Hat Decision Manager 7.13.2 provides increased stability and fixed issues listed in this section.

11.1. BUSINESS CENTRAL

- You cannot save a DMN model if you use the **()not** function [[RHDM-1895](#)]
- You cannot deploy a KJAR to a remote maven repository that requires access via a proxy in Business Central [[RHPAM-4509](#)]
- The **Table 'rhpam.taskEvent' doesn't exist** error appears after upgrading to 7.12.0 or later [[RHPAM-4578](#)]
- The commit history of the **Metrics** tab is not refreshed on branches other than the main branch [[RHPAM-2603](#)]

11.2. KIE SERVER

- Cannot commit a session during a retry of the parent process [[RHPAM-4499](#)]
- Unable to connect to a PostgreSQL DB over SSL from a **kieserver** image [[RHPAM-4400](#)]
- When a process has variable of type **java.util.Date**, if the **showTime** attribute on the generated form is set to **true**, you cannot insert the time part [[RHPAM-4513](#)]
- The ISPN000474 error is generated by **kie-server** when two nodes are configured to support failover [[RHPAM-4223](#)]

11.3. RED HAT OPENSIFT CONTAINER PLATFORM

- Cannot use special characters in passwords in the Business Central operator [[RHPAM-4529](#)]
- The **baseFilter(AUTH_LDAP_BASE_FILTER)** filter is incompatible with versions earlier than 7.12.0 [[RHPAM-4147](#)]
- Upgrade Red Hat JBoss EAP version to 7.4.8 on Red Hat Process Automation Manager image [[RHPAM-4616](#)]

11.4. DECISION ENGINE

- Equality conditions between the BigDecimal property and a numeric value does not work correctly in a non-executable model [[RHDM-1944](#)]
- An unexpected rule fires after upgrading from 7.10.1 to 7.12.1 when capitalized property is updated in modify block [[RHDM-1945](#)]
- The non-executable-model does not react to the bind-only Map property with map access operator [[RHDM-1952](#)]
- Even after modifying, a non-matching rule is fired again when modified facts are provided by a **from** statement [[RHDM-1951](#)]

CHAPTER 12. FIXED ISSUES IN RED HAT DECISION MANAGER

7.13.3

Red Hat Decision Manager 7.13.3 provides increased stability and fixed issues listed in this section.

12.1. BUSINESS CENTRAL

- Dashbuilder does not support the type `MILLISECOND` [[RHPAM-4659](#)]
- An exception occurs while using expressions with the `$` character in BRL condition in GDST [[RHDM-1938](#)]

12.2. RED HAT BUILD OF KOGITO

- BPMN files containing (Java) `ServiceTask` created using VSCode BPMN Editor causes parser errors in maven build [[RHPAM-4604](#)]

12.3. DMN DESIGNER

- `[GSS](7.13.3)` DMN extend rule to catch non-normalized named elements [[RHDM-1957](#)]

12.4. RED HAT OPENSIFT CONTAINER PLATFORM

- Red Hat Decision Manager Kogito Operator 7.x installation is failing with **OOMKilled** and **CrashLoopBackOff** [[RHPAM-4629](#)]

12.5. DECISION ENGINE

- `NullPointerException` in `mvel MathProcessor` with equality check when null property is on right side [[RHPAM-4642](#)]
- **executable-model** fails with `BigDecimal` arithmetic when it's a scope of a method call [[RHDM-1966](#)]
- The **str** operator with bind variable fails after **mvel** jitting [[RHDM-1965](#)]
- The executable model build fails when setting negative `BigDecimal` literal value [[RHDM-1959](#)]

CHAPTER 13. KNOWN ISSUES IN RED HAT DECISION MANAGER 7.13.4

This section lists known issues with Red Hat Decision Manager 7.13.4.

13.1. BUSINESS CENTRAL

Business Central EAP7 deployable zip from 7.13.4 cannot be updated by the update tool [[RHPAM-4838](#)]

Issue:

If you use the update tool to update an Red Hat Decision Manager 7.13.4 **rhpm-business-central-eap7-deployable** installation to release 7.13.4SP1, the update fails with the following error:

```
ERROR - The patch is not valid for the distribution and version!
```

Workaround:

1. Download the **build.metadata** file attached to [RHPAM-4838](#) to the **business-central.war/META-INF** directory in your Business Central installation.
2. Run the update tool again.

CHAPTER 14. FIXED ISSUES IN RED HAT DECISION MANAGER

7.13.4

Red Hat Decision Manager 7.13.4 provides increased stability and fixed issues listed in this section.

14.1. BUSINESS CENTRAL

- Dashbuilder does not support the type `MILLISECOND` [[RHPAM-4659](#)]
- Standalone Business Central does not start on Red Hat Enterprise Linux (RHEL) [[RHPAM-4715](#)]
- Data filter is not working as expected [[RHPAM-4664](#)]

14.2. KIE SERVER

- The **`ClassNotFoundException`** occurs when launching a business application with the command `mvn spring-boot:run` [[RHDM-1984](#)]
- Behavior of the **`ClassCastException`** exception changed after RHPAM 7.13.0 for empty values in the request [[RHPAM-4725](#)]
- The `NoSuchMethodError` occurs when retrieving Kie server information on SpringBoot [[RHPAM-4714](#)]
- The productized `cxfrtbindings-soap` dependency in `kie-camel` is invalid [[RHPAM-4683](#)]
- The `NullPointerException` (NPE) occurs on `TupleSetImpl.setNextTuple` with `SubnetworkTuple` [[RHDM-1968](#)]

14.3. RED HAT OPENSIFT CONTAINER PLATFORM

- Upgrade JBoss Enterprise Application Server to 7.4.12 on RHPAM and BAMOE images [[RHPAM-4762](#)]
- Unable to set `direct-verification=true` individually in LDAP realm by operator [[RHPAM-4754](#)]
- Unable to connect to an external PostgreSQL database over SSL from `kie-server` on OpenShift Container Platform [[RHPAM-4740](#)]
- Do not set URL envs if the `jdbcUrl` property is not set [[RHPAM-4713](#)]
- Legacy datasource scripts do not consider XA properties for the `mariadb` driver [[RHPAM-4712](#)]
- Correctly set the XA Connection URL property [[RHPAM-4711](#)]
- KIE Server `configMap` points to SSL routes when SSL is disabled [[RHPAM-4709](#)]
- Can't login into Business Central without SSL configured [[RHPAM-4705](#)]
- **`NoSuchMethodException`**: Method `setURL` not found [[RHPAM-4704](#)]
- The `pom.xml` file in `rhpm-7-openshift-image/quickstarts/router-ext` contains the wrong version [[RHPAM-4682](#)]

14.4. DECISION ENGINE

- Unnecessary warning message appears when executing a DRL file [[RHPAM-4758](#)]
- The **NullPointerException** error occurs in **MemoryFileSystem** when **kbase.name** is empty in **kmodule.xml** [[RHPAM-4755](#)]
- With a non-executable model and the **mvel** dialect, when the modify-block is placed inside a block such as the **if-block** in RHS, the modify does not work correctly [[RHDM-1985](#)]
- After upgrading to 7.13.2, rules fire incorrectly when BigDecimal equality is involved in a pattern [[RHDM-1974](#)]
- The executable model doesn't resolve bind variables from another pattern of the same type in method call in LHS for property reactivity [[RHDM-1969](#)]
- The executable model doesn't resolve bind variables in a method call in LHS for property reactivity [[RHDM-1967](#)]

CHAPTER 15. FIXED ISSUES IN RED HAT DECISION MANAGER

7.13.5

Red Hat Decision Manager 7.13.5 provides increased stability and fixed issues listed in this section.

15.1. BUSINESS CENTRAL

- Cannot clone project by ssh when business central is integrated with LDAP [[RHPAM-4478](#)]
- System error occurs when you access the Form asset or the Task form which have the listbox component [[RHPAM-4778](#)]
- Duplicate signals received [[RHPAM-4813](#)]

15.2. KIE SERVER

- Backport DROOLS-7014 to Red Hat Decision Manager libraries [[RHDM-2006](#)]
- An immutable KIE container is not deployed with auto scan in SpringBoot kie-server after upgrading to 7.13.1 [[RHPAM-4800](#)]
- Exclusion on kie-server affects custom endpoints [[RHPAM-4876](#)]

15.3. DECISION ENGINE

- Coercion from interger literal to BigDecimal bind variable [[RHDM-1991](#)]
- Behavior of multiple updates in executable model is different from non-executable model [[RHDM-1993](#)]
- Performance degradation when increasing concurrency of rule execution in multi threads [[RHDM-1994](#)]
- Non-matching rule fires randomly and results in infinite-loop [[RHDM-2007](#)]
- The Drools executable-model fails with BigDecimal coercion for method arguments [[RHDM-2014](#)]
- EXISTS and NOT do not work correctly with multiple constraints with BigDecimal [[RHDM-2016](#)]
- Drools executable-model fails with a bind variable to a calculation result of int and BigDecimal [[RHDM-2020](#)]

APPENDIX A. VERSIONING INFORMATION

Documentation last updated on Thursday, March 14th, 2024.

APPENDIX B. CONTACT INFORMATION

Red Hat Decision Manager documentation team: brms-docs@redhat.com