



Red Hat Satellite 6.3

Release Notes

Product notes, new features, and known bugs for Red Hat Satellite 6.3.

Red Hat Satellite 6.3 Release Notes

Product notes, new features, and known bugs for Red Hat Satellite 6.3.

Red Hat Satellite Documentation Team

satellite-doc-list@redhat.com

Legal Notice

Copyright © 2019 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document contains product notes, brief descriptions of new features, and known bugs for Red Hat Satellite 6.3.

Table of Contents

CHAPTER 1. INTRODUCTION	3
1.1. SATELLITE 6 COMPONENT VERSIONS	3
1.2. RED HAT SATELLITE AND PROXY SERVER LIFE CYCLE	3
1.3. RED HAT SATELLITE FAQ	3
CHAPTER 2. CONTENT DELIVERY NETWORK REPOSITORIES	4
2.1. RED HAT SATELLITE	4
2.2. RED HAT SATELLITE CAPSULE	4
2.3. RED HAT SATELLITE MAINTENANCE	4
2.4. RED HAT SATELLITE TOOLS	5
2.5. RED HAT SATELLITE TOOLS - PUPPET 4	7
CHAPTER 3. KEY CHANGES TO THE DOCUMENTATION SET	9
CHAPTER 4. NEW FEATURES AND ENHANCEMENTS	10
CHAPTER 5. RELEASE INFORMATION	13
5.1. ENHANCEMENTS	13
5.2. TECHNOLOGY PREVIEW	13
5.3. RELEASE NOTES	13
5.4. DEPRECATED FUNCTIONALITY	15
5.5. KNOWN ISSUES	15
CHAPTER 6. TECHNICAL NOTES	18
6.1. RED HAT SATELLITE 6.3.0	18
6.1.1. RHSA-2018:0336: Important: Satellite 6.3 Release	18
6.1.2. RHBA-2018:0337: Satellite 6.3 Libraries	20
6.1.3. RHBA-2018:0338: Satellite 6.3 Tools Release	20

CHAPTER 1. INTRODUCTION

Red Hat Satellite is a system management solution that enables you to deploy, configure, and maintain your systems across physical, virtual, and cloud environments. Satellite provides provisioning, remote management and monitoring of multiple Red Hat Enterprise Linux deployments with a single, centralized tool.

Red Hat Satellite Server synchronizes the content from Red Hat Customer Portal and other sources, and provides functionality including fine-grained life cycle management, user and group role-based access control, integrated subscription management, as well as advanced GUI, CLI, or API access.

Red Hat Satellite Capsule Server mirrors content from Red Hat Satellite Server to facilitate content federation across various geographical locations. Host systems can pull content and configuration from the Capsule Server in their location and not from the central Satellite Server. The Capsule Server also provides localized services such as Puppet Master, DHCP, DNS, or TFTP. Capsule Servers assist you in scaling Red Hat Satellite as the number of managed systems increases in your environment.

1.1. SATELLITE 6 COMPONENT VERSIONS

Red Hat Satellite is a combination of a number of upstream projects. For the full details of the major projects included, and the version of those projects included in each major and minor release of Red Hat Satellite, see [Satellite 6 Component Versions](#).

1.2. RED HAT SATELLITE AND PROXY SERVER LIFE CYCLE

For an overview of the life cycle phases for Red Hat Network Satellite and Red Hat Satellite and the status of support for these products, see [Red Hat Satellite and Proxy Server Life Cycle](#).

1.3. RED HAT SATELLITE FAQ

For a list of frequently asked questions about Red Hat Satellite 6, see [Red Hat Satellite 6 FAQ](#).

CHAPTER 2. CONTENT DELIVERY NETWORK REPOSITORIES

This section describes the repositories required to install Red Hat Satellite 6.3.

You can install Red Hat Satellite 6.3 through the Content Delivery Network (CDN). To do so, configure **subscription-manager** to use the correct repository for your operating system version and variant.

Run the following command to enable a CDN repository:

```
# subscription-manager repos --enable=[reponame]
```

Run the following command to disable a CDN repository:

```
# subscription-manager repos --disable=[reponame]
```

The following sections outline the repositories required by Red Hat Satellite 6.3. When one of these repositories is required to install a package, the steps to enable the required repositories are included in the documentation.

2.1. RED HAT SATELLITE

The following table lists the repositories for Red Hat Satellite Server.

Table 2.1. Red Hat Satellite

Channel	Repository Name
Red Hat Satellite 6.3 (for RHEL 7 Server) (RPMs)	rhel-7-server-satellite-6.3-rpms
Red Hat Satellite 6.3 - Puppet 4 (for RHEL 7 Server) (RPMs)	rhel-7-server-satellite-6.3-puppet4-rpms

2.2. RED HAT SATELLITE CAPSULE

The following table lists the repositories for Red Hat Satellite Capsule Server.

Table 2.2. Red Hat Satellite Capsule

Channel	Repository Name
Red Hat Satellite Capsule 6.3 (for RHEL 7 Server) (RPMs)	rhel-7-server-satellite-capsule-6.3-rpms
Red Hat Satellite Capsule 6.3 - Puppet 4 (for RHEL 7 Server) (RPMs)	rhel-7-server-satellite-capsule-6.3-puppet4-rpms

2.3. RED HAT SATELLITE MAINTENANCE

The following table lists the repositories for Red Hat Satellite Maintenance.

Table 2.3. Red Hat Satellite Maintenance

Channel	Repository Name
Red Hat Satellite Maintenance 6 (for RHEL 7 Server) (RPMs)	rhel-7-server-satellite-maintenance-6-rpms

2.4. RED HAT SATELLITE TOOLS

The following table lists the repositories for Red Hat Satellite Tools.

Table 2.4. Red Hat Satellite Tools

Channel	Repository Name
Red Hat Satellite Tools 6.3 (for RHEL 5 Server - AUS) (RPMs)	rhel-5-server-aus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 5 Server - ELS) (RPMs)	rhel-5-server-els-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 5 for System Z - ELS) (RPMs)	rhel-5-for-system-z-els-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 Desktop) (RPMs)	rhel-6-desktop-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 Server) (RPMs)	rhel-6-server-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 Server - EUS) (RPMs)	rhel-6-server-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 Server - AUS) (RPMs)	rhel-6-server-aus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 Workstation) (RPMs)	rhel-6-workstation-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 for System Z) (RPMs)	rhel-6-for-system-z-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 for System Z - EUS) (RPMs)	rhel-6-for-system-z-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 for IBM Power) (RPMs)	rhel-6-for-power-satellite-tools-6.3-rpms

Channel	Repository Name
Red Hat Satellite Tools 6.3 (for RHEL 6 for IBM Power - EUS) (RPMs)	rhel-6-for-power-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 for Scientific Computing) (RPMs)	rhel-6-for-hpc-node-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 6 for Scientific Computing - EUS) (RPMs)	rhel-6-for-hpc-node-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 Desktop) (RPMs)	rhel-7-desktop-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 Server) (RPMs)	rhel-7-server-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 Server - EUS) (RPMs)	rhel-7-server-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 Server - AUS) (RPMs)	rhel-7-server-aus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 Workstation) (RPMs)	rhel-7-workstation-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for System Z) (RPMs)	rhel-7-for-system-z-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for System Z - EUS) (RPMs)	rhel-7-for-system-z-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for IBM Power) (RPMs)	rhel-7-for-power-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for IBM Power - EUS) (RPMs)	rhel-7-for-power-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for Scientific Computing) (RPMs)	rhel-7-for-hpc-node-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for Scientific Computing - EUS) (RPMs)	rhel-7-for-hpc-node-eus-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for IBM Power LE) (RPMs)	rhel-7-for-power-le-satellite-tools-6.3-rpms
Red Hat Satellite Tools 6.3 (for RHEL 7 for IBM Power LE - EUS) (RPMs)	rhel-7-for-power-le-eus-satellite-tools-6.3-rpms

Channel	Repository Name
Red Hat Satellite Tools 6.3 (for RHEL 7 Server for ARM) (RPMs)	rhel-7-for-arm-satellite-tools-6.3-rpms

2.5. RED HAT SATELLITE TOOLS - PUPPET 4

The following table lists the repositories for Red Hat Satellite Tools - Puppet 4.

Table 2.5. Red Hat Satellite Tools - Puppet 4

Channel	Repository Name
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 5 Server - AUS) (RPMs)	rhel-5-server-aus-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 5 Server - ELS) (RPMs)	rhel-5-server-els-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 6 Desktop) (RPMs)	rhel-6-desktop-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 6 Server) (RPMs)	rhel-6-server-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 6 Server - EUS) (RPMs)	rhel-6-server-eus-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 6 Server - AUS) (RPMs)	rhel-6-server-aus-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 6 Workstation) (RPMs)	rhel-6-workstation-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 6 for Scientific Computing) (RPMs)	rhel-6-for-hpc-node-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 6 for Scientific Computing - EUS) (RPMs)	rhel-6-for-hpc-node-eus-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 Desktop) (RPMs)	rhel-7-desktop-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 Server) (RPMs)	rhel-7-server-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 Server - EUS) (RPMs)	rhel-7-server-eus-satellite-tools-6.3-puppet4-rpms

Channel	Repository Name
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 Server - AUS) (RPMs)	rhel-7-server-aus-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 Workstation) (RPMs)	rhel-7-workstation-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 for Scientific Computing) (RPMs)	rhel-7-for-hpc-node-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 for Scientific Computing - EUS) (RPMs)	rhel-7-for-hpc-node-eus-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 for IBM Power LE) (RPMs)	rhel-7-for-power-le-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 for IBM Power LE - EUS) (RPMs)	rhel-7-for-power-le-eus-satellite-tools-6.3-puppet4-rpms
Red Hat Satellite Tools 6.3 - Puppet 4 (for RHEL 7 Server for ARM) (RPMs)	rhel-7-for-arm-satellite-tools-6.3-puppet4-rpms

CHAPTER 3. KEY CHANGES TO THE DOCUMENTATION SET

Several notable changes were made to the Red Hat Satellite documentation set for this release. The following list outlines and explains these changes.

Errata Management Guide

The *Errata Management Guide* is a new title that describes how to set up patching in a Red Hat Satellite environment.

Hammer CLI Guide

A full reference to Hammer commands has now been added. For more information, see [Reference](#) in the *Hammer CLI Guide*.

Host Configuration Guide

The *Host Configuration Guide* included in the Red Hat Satellite 6.2 documentation suite has now been renamed [Managing Hosts](#) to more closely reflect the content it contains. Content on configuring provisioning environments and managing content previously found in this guide has been moved to the [Provisioning Guide](#) and [Content Management Guide](#) respectively.

Installation Guide

Content on upgrading and updating Red Hat Satellite has been moved to a standalone title [Upgrading and Updating Red Hat Satellite](#).

Server Administration Guide

The *Server Administration Guide* included in the Red Hat Satellite 6.2 documentation suite has now been renamed *Administering Red Hat Satellite* to more closely reflect the content it contains. Content on managing content previously found in this guide has been moved to the [Content Management Guide](#).

CHAPTER 4. NEW FEATURES AND ENHANCEMENTS

This chapter introduces new features in Red Hat Satellite 6.3, and links to further information.

Ansible Tower Integration

Satellite 6.3 now supports Ansible Tower Integration. Ansible Tower is a web-based graphical interface for automating management tasks such as cloud provisioning, configuration, and application deployment. Red Hat Satellite, with Ansible Tower, provides a dynamic inventory, and provisioning callbacks. Ansible Tower is able to use Red Hat Satellite as a dynamic inventory source, and both products are able to sync inventory. Systems provisioned by Red Hat Satellite are able to 'callback' to Tower, allowing Ansible playbooks to run post provisioning.

Arbitrary Files in Content Views

Satellite 6.3 provides the ability for custom products to include repositories for custom file types. This provides a generic method to incorporate arbitrary files in a product. Applications range from distributing SSH keys and source code files to larger files such as virtual machine images and ISO files.

Bulk Subscription Upgrade Tooling

Satellite 6.3 subscription management now provides the ability to manage subscriptions against multiple systems. This includes the ability to export subscriptions to a file in CSV format, import from a previously exported CSV file, and bulk-attach subscriptions using the API and CLI.

Cloning Utility

Satellite 6.3 provides the ability to restore Red Hat Satellite to a bare metal environment by cloning an existing Red Hat Satellite 6.1 or 6.2 backup, and then upgrading the clone to Red Hat Satellite 6.3.

Content Synchronization Policies

Red Hat Satellite Capsules now feature their own user selectable download policy for repositories: On Demand, Background, Immediate, and Inherit from Repository.

EC2 Support

Satellite 6.3 now supports running on Amazon Elastic Compute Cloud (Amazon EC2).

Email Setting Configuration

Satellite 6.3 introduces user configurable email settings by the API and the Administer settings of the web user interface. Settings include Sendmail/SMTP settings, authentication settings, and how emails are sent by Satellite.

Future-Dated Subscriptions

Satellite 6.3 introduces the ability to view and attach future dated subscriptions to systems. The Red Hat Customer Portal now has the facility to view and download manifests containing future dated subscriptions.

Host Name Control

Satellite 6.3 features improved hostname creation logic for clients with Discovery, providing the ability to set the fact that is used for the hostname of the system.

Improved Compute Resource Configuration

Satellite 6.3 introduces user configurable resource allocation within hypervisor environments.

LDAP User Organization and Location Assignment

This release adds to Hammer the ability to change the default location or organisation of a user, using the name of the location or organization in addition to the ID.

Login Page Messages

This release adds the ability to specify a custom message on the login screen to the Red Hat Satellite Server web user interface.

Notifications Area

This release adds a notifications area to the Red Hat Satellite Server web user interface. It displays event notifications to inform administrators of important environment changes, such as the following:

- Host discovery
- Host deletion
- Successful provisioning of a system
- Imported host with no owner

OpenSCAP Tailoring Files

This release adds the ability to upload and use tailoring files to customize existing OpenSCAP policies.

Organization Administrator Role

This release adds a new organization administrator role by default. This role can view the configuration of every element of the Satellite structure, logs, and statistics.

Parameterized Subnets

This release adds a method to specify parameters for subnets in a similar way as for domains. From the **Infrastructure** menu, when you create or edit subnets, there is a new **Parameters** tab.

Puppet 4 Support

This release supports hosts with Puppet version 3.8 or later. You can now update hosts to the Puppet 4 agent.

Red Hat Virtualization 4.0 Support

This release adds support for Red Hat Virtualization 4.0 as a compute resource back end.

Rename Utility

This release includes a tool for renaming a Satellite or Capsule Server.

SSH Key Provisioning Support

This release adds support for the deployment of public SSH keys as part of the provisioning process.

Static IP Configuration in Bootdisks

This release adds support for static IP configuration to be included in full host bootdisks.

Template Enhancements

This release adds two enhancements to provisioning templates. It is now possible to export templates. The template editor now features a **Help** tab which contains information about the template syntax.

Tokenized Authentication for Hammer

This release adds the ability to initiate a token-based authenticated session with Satellite and avoid storing credentials in plain text. You are only prompted once for credentials at the beginning of a session when running Hammer commands.

UEFI Support

This release adds support for PXE booting of UEFI systems.

User Description Field

This release adds the ability to specify a custom description for individual users in the Red Hat Satellite Server web user interface.

virt-who Configuration Utility

This release adds a feature which assists the task of creating and deploying virt-who configuration files. For RHEV3, RHV4 and RHEL-Based hypervisors, this release supports the following virt-who configuration types: **rhev** and **libvirt**.

CHAPTER 5. RELEASE INFORMATION

These release notes highlight technology preview items, recommended practices, known issues, and deprecated functionality to be taken into consideration when deploying this release of Red Hat Satellite 6.

Notes for updates released during the support lifecycle of this Red Hat Satellite 6 release will appear in the advisory text associated with each update.

5.1. ENHANCEMENTS

This release of Red Hat Satellite 6 features the following enhancements:

BZ#[1329051](#)

Previously, users had to synchronize the Atomic Kickstart Tree content manually through a custom repository. With this release, users can synchronize the Atomic Kickstart Tree content from within the Red Hat Content Delivery Network.

5.2. TECHNOLOGY PREVIEW

The items listed in this section are provided as Technology Previews. For further information on the scope of Technology Preview status, and the associated support implications, see <https://access.redhat.com/support/offerings/techpreview/>.

Synchronize Templates from Git Repositories

Satellite 6.3 introduces a plug-in that allows templates to be pushed to, and pulled from, an external Git repository or filesystem. For more information, see [Synchronizing Templates with Git](#).

Auto-attach Bootdisk for VMWare

Satellite 6.3 introduces an auto-attach bootdisk for VMWare as a feature. For more information, see [Satellite 6.3 Feature Overview: Auto-attach Bootdisk for VMWare \[Tech Preview\]](#).

Tracer

Satellite 6.3 introduces Tracer, an integration with the Tracer tool that monitors running processes and identifies if they need to be restarted due to package updates or similar activities. For more information, see [Satellite 6.3 Feature Overview: Tracer \[Tech Preview\]](#).

BZ#[1376191](#)

Previously, provisioning on IBM POWER was not available. With this release, provisioning clients on IBM POWER via BOOTP is available as a Technology Preview feature.

5.3. RELEASE NOTES

This section outlines important details about the release, including recommended practices and notable changes to Red Hat Satellite. You must take this information into account to ensure the best possible outcomes for your deployment.

BZ#[1432285](#)

Previously, there was an API JSON field named "enabled_override" for the API at "/api/v2/hosts/1/subscriptions/product_content". With this release, the API JSON field name "enabled_override" has been deprecated in favor of "override" to improve consistency.

BZ#[1433458](#)

To synchronize container images from a registry with self-signed certificates, you must either configure certificates manually or disable the SSL Verify option.

BZ#[1435007](#)

With this release, the roles included in Red Hat Satellite are now read only. If any of these roles were previously customized, an editable version of those roles with the name "Cuztomized XXXX" is created when you upgrade your environment to this version.

BZ#[1469599](#)

Because of security fixes that were introduced with this fix, if you clone templates that contain Ruby's `to_proc` syntax in Satellite 6.2, and then upgrade to Satellite 6.3, you cannot use the template.

As a workaround, write the same code as a full Ruby block, for example, `(1..3).collect(&.to_s)` becomes `(1..3).collect {|num| num.to_s}`.

To find affected code, search the template for `&:`. Replace `...(&:....)` with `...{|i| i....}`.

Use the following two examples as a guide:

Ruby syntax in 6.2 cloned template:

```
<% host_param('ssh_authorized_keys').split(',').map(&.strip).each do |ssh_key| -%>
```

Updated Ruby syntax for Satellite 6.3:

```
<% host_param('ssh_authorized_keys').split(',').map{ |item| item.strip }.each do |ssh_key| -%>
```

Ruby syntax in 6.2 cloned template:

```
nameserver=#{[subnet.dns_primary, subnet.dns_secondary].select(&.present?).join(',')}
```

Updated Ruby syntax for Satellite 6.3:

```
nameserver=#{[subnet.dns_primary, subnet.dns_secondary].select{ |item| item.present? }.join(',')}
```

BZ#[1552093](#)

Previously, the templates used "<%= foreman_url %>" to notify Satellite that the build is done. In 6.3, the templates use "<%= foreman_url('built') %>", which explicitly calls the 'built' template.

BZ#[1512959](#)

If you plan to manually upgrade from Satellite 6.2 to Satellite 6.3, and if you previously installed the python-pulp-agent-lib package, you must enable the satellite-tools repository to successfully perform the upgrade. This package was moved into the tools repository for Satellite 6.3.

-
BZ#[1560607](#)

Several parameters of the `capsule-certs-generate` command were changed, and some were added. Those prefixed `--capsule` were changed to a `--foreman-proxy` prefix. New parameters prefixed `--reset` were added to allow commonly-used parameters to be reset to their default values. A `--certs-reset` parameter was added to reset any custom certificates and use the self-signed CA instead.

5.4. DEPRECATED FUNCTIONALITY

Subscriptions Manager Registration Snippet

In this release, you can no longer use the `subscription_manager_registration` snippet in a template to enable Satellite Tools repositories. You must configure your repositories to be enabled using an activation key.

Hammer Import Tool

In this release, you can no longer use `hammer import` functionality. To import hosts, you can use the bootstrap script `bootstrap.py`. For more information, see [Importing Existing Hosts via the Bootstrap Script](#).

5.5. KNOWN ISSUES

These known issues exist in Red Hat Satellite 6 at this time.

BZ#[1321041](#)

Known Issue

Hosts provisioned by Satellite, but not registered, are showing a green icon, indicating they are covered by a subscription. These should show a red icon, indicating they are not covered by a subscription.

BZ#[1382090](#)

Known Issue

In the Red Hat Subscriptions tab of the user interface, the hyperlinks used in the subscription type "Guests of hypervisor-name" are incorrect and broken. This is due to the hyperlink using the candlepin uuid rather than the host ID.

BZ#[1445625](#)

Known Issue

On Puppet Forge, some Puppet modules are invalid and cannot sync with Satellite. These invalid Puppet modules cause error messages such as **Invalid properties** or **MissingModulePile**.

Despite receiving a report of a sync failure, the valid Puppet modules sync from Puppet Forge into Satellite.

BZ#[1507848](#)

Known Issue

Satellite Installer requires absolute paths. Always provide an absolute path for `--certs-tar`. For example, `/root/new.name-certs.tar`. If you run the installer with a relative path, run the installer again with the absolute path and the `--scenario` parameter to create the `last_scenario.yml`.

BZ#[1518848](#)

Known Issue

The command `katello-change-hostname` creates an error condition when run on Satellite 6.2 during migration and upgrade. This occurs because of a bug in the version of the `katello-change-hostname` command in the 6.2 release. To avoid this problem, complete the upgrade to Satellite 6.3 before running the `katello-change-hostname` command.

BZ#[1523392](#)

Known Issue

Running the `./install_packages` command when attempting to set up a disconnected Satellite Server fails and returns NOKEY error.

Workaround

For more information, see the KCS Solution at <https://access.redhat.com/solutions/3275791>

BZ#[1538597](#)

Known Issue

When using image-based provisioning against VMWare, attempting to add additional storage to the new host returns an error.

BZ#[1541002](#)

Known Issue

If you try to delete a subnet that is used to provision a machine, instead of receiving a user-friendly error message, you receive a confusing error message:

```
| NoMethodError: undefined method `klass' for nil:NilClass  
| Did you mean? class
```

BZ#[1541481](#)

Known Issue

If you have SELinux enabled, using Kerberos (KRB) keys instead of RSA keys can cause remote execution jobs to fail.

BZ#[1541885](#)

For ISO-based disconnected Satellite users

Known Issue

The RPM script is missing `--local`, which makes it search the internet to install the "oauth" gem. For disconnected Satellites, this is a problem.

Workaround

If Puppet 4 is installed, when **yum** installs packages using the default Puppet 4 repositories, before you run **satellite-installer**, enter the following command:

```
/opt/puppetlabs/puppet/bin/gem install --local /usr/share/foreman-installer/gems/oauth-0.5.1.gem
```

Workaround

If you upgrade to Puppet 4, before you enter the **--upgrade-puppet** command, enter the following commands:

```
# yum remove -y puppet-server
# yum install puppetserver puppet-agent puppet-agent-oauth
/opt/puppetlabs/puppet/bin/gem install --local /usr/share/foreman-installer/gems/oauth-0.5.1.gem
```

BZ#[1544401](#)

Known Issue

Running **katello-backup** with a relative path for the destination, for example ``katello-backup .'`, causes an error.

Workaround

Run **katello-backup** with a full path. For example `'katello-backup /backup-destination'`.

CHAPTER 6. TECHNICAL NOTES

This section contains the summary text for bug fixes and enhancements in Red Hat Satellite errata advisories. The information and procedures in this section are relevant to Red Hat Satellite administrators.

6.1. RED HAT SATELLITE 6.3.0

This section outlines the errata advisories released for Red Hat Satellite 6.3.0.

6.1.1. RHSA-2018:0336: Important: Satellite 6.3 Release

Information about this advisory is available at https://access.redhat.com/errata/product/250/ver=6.3/rhel--7/x86_64/RHSA-2018:0336.

vulnerability

BZ#1335449

An integer-overflow flaw was found in V8's Zone class when allocating new memory (Zone::New() and Zone::NewExpand()). An attacker with the ability to manipulate a large zone could crash the application or, potentially, execute arbitrary code with the application privileges.

BZ#1046642

It was found that ruby will_paginate is vulnerable to a XSS via malformed input that cause pagination to occur on an improper boundary. This could allow an attacker with the ability to pass data to the will_paginate gem to display arbitrary HTML including scripting code within the web interface.

BZ#1327471

A flaw was found in the provisioning template handling in foreman. An attacker, with permissions to create templates, can cause internal Rails information to be displayed when it is processed, resulting in potentially sensitive information being disclosed.

BZ#1330264

Pulp makes unsafe use of Bash's \$RANDOM to generate a NSS DB password and seed resulting in insufficient randomness. An attacker could potentially guess the seed used given enough time and compute resources.

BZ#1339889

It was found that Satellite 6 did not properly enforce access controls on certain resources. An attacker, with access to the API and knowledge of the ID name, can potentially access other resources in other organizations.

BZ#1349136

A flaw was found in discovery-debug in foreman. An attacker, with permissions to view the debug results, would be able to view the root password associated with that system, potentially allowing them to access it.

BZ#1365815

It was found that foreman is vulnerable to a stored XSS via a job template with a malformed name. This could allow an attacker with privileges to set the name in a template to display arbitrary HTML including scripting code within the web interface.

BZ#1393291

It was found that foreman is vulnerable to a stored XSS via an organization or location name. This could allow an attacker with privileges to set the organization or location name to display arbitrary HTML including scripting code within the web interface.

BZ#1406729

A flaw was found in katello-debug where certain scripts and log files used insecure temporary files. A local user could exploit this flaw to conduct a symbolic-link attack, allowing them to overwrite the contents of arbitrary files.

BZ#1436262

It was found that the `hammer_cli` command line client disables SSL/TLS certificate verification by default. A man-in-the-middle (MITM) attacker could use this flaw to spoof a valid certificate.

BZ#1439537

A flaw was found in foreman's logging during the adding or registering of images. An attacker with access to the foreman log file would be able to view passwords for provisioned systems in the log file, allowing them to access those systems.

BZ#1480886

It was found that foreman in Satellite 6 did not properly enforce access controls on certain resources. An attacker with access to the API and knowledge of the resource name can access resources in other organizations.

BZ#1328930

It was found that the private CA key was created in a directory that is world-readable for a small amount of time. A local user could possibly use this flaw to gain access to the private key information in the file.

BZ#1348939

A flaw was found in foreman's handling of template previews. An attacker with permissions to preview host templates can access the template preview for any host if they are able to guess the host name, disclosing potentially sensitive information.

BZ#1406384

A flaw was found in foreman-debug's logging. An attacker with access to the foreman log file would be able to view passwords, allowing them to access those systems.

6.1.2. RHBA-2018:0337: Satellite 6.3 Libraries

Information about this advisory is available at <https://access.redhat.com/errata/RHBA-2018:0337.html>.

6.1.3. RHBA-2018:0338: Satellite 6.3 Tools Release

Information about this advisory is available at <https://access.redhat.com/errata/RHBA-2018:0338.html>.

katello-agent**BZ#1395700**

Under certain conditions, build 19 of the dispatch router can terminate unexpectedly with a segmentation fault. The memory management has been improved to prevent this happening.

BZ#1463809

You can now manage clients without goferd. This limits the host management functionality only to uploading the package profile after installing, removing, updating packages, and triggering the Satellite tasks such as the applicable errata.

BZ#1272758

When repeatedly installing and removing a package on the same Content Host, goferd accumulates memory over time. This has been fixed by locally settling down received messages in qpuid-proton library.

BZ#1331710

Reinstalling katello-ca-consumer on a RHEL 7 Content Host did not restart goferd service. Consequently, katello agent did not reconnect to Satellite. This is now fixed.

BZ#1379341

Restarting the agent on the client forced package applicability calculations which were not necessary. This case has been fixed.

BZ#1403029

Updating katello-agent did not update dependencies. This is now fixed.

BZ#1446726

While pushing Errata using the Web UI and katello-agent, goferd terminated with a segmentation fault on some clients. This is now fixed.

BZ#1530709

Several memory usage bugs in goferd and qpid have been resolved.

BZ#1371585

When removing katello-ca-consumer RPM, the backup of /etc/rhsm/rhsm.conf was not restored. This is now fixed.

BZ#1388545

Several memory leaks have been fixed in the qpid dispatch router.

BZ#1394386

Hypervisor names reported by virt-who are now validated on input.

BZ#1426380

When qdrouterd was not accessible, the goferd process had a memory leak and goferd terminated unexpectedly. This is now fixed.

BZ#1482635

After installing 'katello-hosts-tools' and running the Puppet agent, enabled_repos_upload sent output to stdout after all of the 'yum check-update' had output their data. This caused errors for the Puppet agent on the client.

Qpid

BZ#1463800

During scaling testing of content hosts, qpid consumed huge amounts of memory. This is now fixed.

BZ#1417303

Previously, Satellite had a hard limit of 64k Content Hosts that can run katello agent. The Qpid Dispatch Router has been improved to remove this limit.

BZ#1452183

When pausing a Satellite in a VM, any goferd client on a machine registered to a Capsule failed to connect to the Capsule and logged "qd:no-route-to-dest" error. The error persisted after qdrouterd on the Satellite resumed. The qpid dispatch router has been improved to unmap all addresses in a more reliable way.

BZ#1519140

During scale testing, qdrouterd experienced segmentation faults in libqpid.so. This is now fixed.

BZ#1530689

qdrouterd on Capsule Server was deadlocked and did not react to commands to kill the process. This is now fixed.

BZ#1530692

When several goferd client connections tried to use qdrouterd on Satellite to link to qpidd, qdrouterd experienced a segmentation fault. This is now fixed.

BZ#1450495

During an upgrade, the qpidd user could not access or read the `/etc/pki/katello/nssdb/nss_db_password-file` file. The qpidd broker attempted to restart, which caused a segmentation fault.

BZ#1457977

The 'hammer host-collection erratum install' installation failed with a sub-task error. With the latest update to qpid, this is now fixed.