

builds for Red Hat OpenShift 1.0

Observability (可观察性)

构建控制器可观察性

Last Updated: 2024-02-15

builds for Red Hat OpenShift 1.0 Observability(可观察性)

构建控制器可观察性

法律通告

Copyright © 2023 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

http://creativecommons.org/licenses/by-sa/3.0/

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java [®] is a registered trademark of Oracle and/or its affiliates.

XFS [®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack [®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

摘要

本文档提供有关构建控制器可观察性的信息。

目录

第1章 构建控制器可观察性	 3
1.1. 构建控制器指标	3

第1章 构建控制器可观察性

构建会公开几个指标,以帮助您监控构建资源的性能和功能。构建控制器指标在端口8383上公开。

1.1. 构建控制器指标

您可以检查以下构建控制器指标来监控目的:

表 1.1. 构建控制器指标

Name	类型	描述	标签	Statu s
build_builds_registere d_total	计数	注册构建总数。	 buildstrategy= <build_buildstr ategy_name=""></build_buildstr> namespace= <buildrun_nam espace=""></buildrun_nam> build= <build_name></build_name> 	实验 性
build_buildruns_compl eted_total	计数	完成的构建总数。	 buildstrategy= <build_buildstr ategy_name=""></build_buildstr> namespace= <buildrun_nam espace=""></buildrun_nam> build= <build_name></build_name> buildrun= <buildrun= <buildrun_nam="" e=""></buildrun=> 	实验性
build_buildrun_establi sh_duration_seconds	Histog ram	构建运 行的 时间 (以秒 为单位)。	 buildstrategy= <build_buildstr ategy_name=""></build_buildstr> namespace= <buildrun_nam espace=""></buildrun_nam> build= <build_name></build_name> buildrun= <buildrun= <buildrun-nam="" e=""></buildrun=> 	实验 性

Name	类型	描述	标签	Statu s
build_buildrun_comple tion_duration_seconds	Histog	构建运行完成持续时间(以秒为单位)。	 buildstrategy= <build_buildstr ategy_name=""></build_buildstr> namespace= <buildrun_nam espace=""></buildrun_nam> build= <build_name></build_name> buildrun= <buildrun= <buildrun_nam="" e=""></buildrun=> 	实验 性
build_buildrun_rampu p_duration_seconds	Histog ram	构建运行速度(以秒为单位)。	 buildstrategy= <build_buildstr ategy_name=""></build_buildstr> namespace= <buildrun_nam espace=""></buildrun_nam> build= <build_name></build_name> buildrun= <buildrun= <buildrun-nam="" e=""></buildrun=> 	实验性
build_buildrun_taskrun _rampup_duration_sec onds	Histog ram	任务运行任务的构建运行持续时间(以秒为单位)。	 buildstrategy= <build_buildstr ategy_name=""></build_buildstr> namespace= <buildrun_nam espace=""></buildrun_nam> build= <build_name></build_name> buildrun= <buildrun= <buildrun="<buildrun_nam" e=""></buildrun=> 	实验性

Name	类型	描述	标签	Statu s
build_buildrun_taskrun _pod_rampup_duratio n_seconds	Histog ram	任务运行 pod 的构建运行 持续时间(以秒为单位)。	 buildstrategy= <build_buildstr ategy_name=""></build_buildstr> namespace= <buildrun_nam espace=""></buildrun_nam> build= <build_name></build_name> buildrun= <buildrun= <buildrun_nam="" e=""></buildrun=> 	实验性

1.1.1. 直方图指标

要将自定义存储桶用于构建控制器,您必须为特定的直方图指标设置环境变量。下表显示了所有直方图指标的环境变量:

表 1.2. 直方图指标

指标	环 境 变量	Default (默 认)
build_buildrun_establish_du ration_seconds	PROMETHEUS_BR_EST_DU R_BUCKETS	0,1,2,3,5,7,10,15,20,30
build_buildrun_completion_ duration_seconds	PROMETHEUS_BR_COMP_D UR_BUCKETS	50,100,150,200,250,300,350,4 00,450,500
build_buildrun_rampup_dura tion_seconds	PROMETHEUS_BR_RAMPUP _DUR_BUCKETS	0,1,2,3,4,5,6,7,8,9,10
build_buildrun_taskrun_ram pup_duration_seconds	PROMETHEUS_BR_RAMPUP _DUR_BUCKETS	0,1,2,3,4,5,6,7,8,9,10
build_buildrun_taskrun_pod _rampup_duration_seconds	PROMETHEUS_BR_RAMPUP _DUR_BUCKETS	0,1,2,3,4,5,6,7,8,9,10