



OpenShift Dedicated 4

Serverless

在 OpenShift Dedicated 中配置 OpenShift Serverless

OpenShift Dedicated 4 Serverless

在 OpenShift Dedicated 中配置 OpenShift Serverless

法律通告

Copyright © 2024 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

摘要

本文档提供有关在 OpenShift Dedicated 上设置和使用 OpenShift Serverless 的信息。

目录

第1章 关于 SERVERLESS	3
1.1. OPENSIFT SERVERLESS 概述	3

第1章 关于 SERVERLESS

1.1. OPENSIFT SERVERLESS 概述

OpenShift Serverless 提供 Kubernetes 原生构建块，供开发人员在 OpenShift Dedicated 上创建和部署无服务器、事件驱动的应用程序。OpenShift Serverless 基于开源 [Knative](#) 项目，通过启用企业级无服务器平台为混合和多云环境提供可移植性和一致性。



注意

因为 OpenShift Serverless 的发行节奏与 OpenShift Dedicated 不同，所以 OpenShift Serverless 文档现在作为每个产品的次版本单独提供。

OpenShift Serverless 文档位于 <https://docs.openshift.com/serverless/>。

特定版本的文档使用版本选择器下拉列表，或者直接将版本添加到 URL，例如 <https://docs.openshift.com/serverless/1.28>。

另外，红帽客户门户网站中也提供了 OpenShift Serverless 文档，地址为 https://access.redhat.com/documentation/zh-cn/red_hat_openshift_serverless/。

如需有关 OpenShift Serverless 生命周期和支持的平台的更多信息，请参阅 [平台生命周期政策](#)。

1.1.1. 其他资源

- [什么是无服务器？](#)