



Red Hat Enterprise Linux 7

Image Builder Guide

Creating customized system images with Image Builder

Red Hat Enterprise Linux 7 Image Builder Guide

Creating customized system images with Image Builder

Eliane Pereira

Red Hat Customer Content Services

elpereir@redhat.com

Vladimír Slávik

Red Hat Customer Content Services

法律通告

Copyright © 2019 Red Hat, Inc. and others.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

摘要

Image Builder is a tool for creating deployment-ready customized system images, for example installation disks, virtual machines, cloud vendor-specific images, and others. Image Builder enables you to create these images faster compared to manual procedures, because it abstracts away the specifics of each output type. Learn how to set up Image Builder and create images with it.

目录

第 1 章 IMAGE BUILDER DESCRIPTION	3
1.1. INTRODUCTION TO IMAGE BUILDER	3
1.2. IMAGE BUILDER TERMINOLOGY	3
1.3. IMAGE BUILDER OUTPUT FORMATS	3
1.4. IMAGE BUILDER SYSTEM REQUIREMENTS	4
第 2 章 INSTALLING IMAGE BUILDER	5
2.1. INSTALLING IMAGE BUILDER IN A VIRTUAL MACHINE	5
第 3 章 CREATING SYSTEM IMAGES WITH IMAGE BUILDER COMMAND-LINE INTERFACE	6
3.1. IMAGE BUILDER COMMAND-LINE INTERFACE	6
3.2. CREATING AN IMAGE BUILDER BLUEPRINT WITH COMMAND-LINE INTERFACE	6
3.3. EDITING AN IMAGE BUILDER BLUEPRINT WITH COMMAND-LINE INTERFACE	7
3.4. CREATING A SYSTEM IMAGE WITH IMAGE BUILDER IN THE COMMAND-LINE INTERFACE	8
3.5. BASIC IMAGE BUILDER COMMAND-LINE COMMANDS	9
3.6. IMAGE BUILDER BLUEPRINT FORMAT	10
3.7. SUPPORTED IMAGE CUSTOMIZATIONS	11
第 4 章 CREATING SYSTEM IMAGES WITH IMAGE BUILDER WEB CONSOLE INTERFACE	14
4.1. ACCESSING IMAGE BUILDER GUI IN THE RHEL 7 WEB CONSOLE	14
4.2. CREATING AN IMAGE BUILDER BLUEPRINT IN THE WEB CONSOLE INTERFACE	15
4.3. EDITING AN IMAGE BUILDER BLUEPRINT IN THE WEB CONSOLE INTERFACE	17
4.4. ADDING USERS AND GROUPS TO AN IMAGE BUILDER BLUEPRINT IN THE WEB CONSOLE INTERFACE	18
4.5. CREATING A SYSTEM IMAGE WITH IMAGE BUILDER IN THE WEB CONSOLE INTERFACE	21
第 5 章 DEPLOYING CLOUD IMAGES WITH IMAGE BUILDER	22
5.1. PREPARING AWS AMI IMAGES FOR UPLOAD	22
5.2. UPLOADING AN AMI IMAGE TO AWS	23
5.3. UPLOADING VMDK IMAGES TO VSPHERE	25
5.4. UPLOADING QCOW2 IMAGE TO OPENSTACK	27
附录 A. REVISION HISTORY	30

第 1 章 IMAGE BUILDER DESCRIPTION

1.1. INTRODUCTION TO IMAGE BUILDER

You can use Image Builder to create customized system images of Red Hat Enterprise Linux, including system images prepared for deployment on cloud platforms. Image Builder automatically handles details of setup for each output type and is thus easier to use and faster to work with than manual methods of image creation. You can access Image Builder functionality through a command-line interface in the **composer-cli** tool, or a graphical user interface in the RHEL 7 web console. See [managing the web console](#) for more information.

Image Builder runs as a system service **lorax-composer**. You can interact with this service through two interfaces:

- CLI tool **composer-cli** for running commands in the terminal. This method is recommended.
- GUI plugin for the RHEL 7 web console.

1.2. IMAGE BUILDER TERMINOLOGY

- **Blueprints** Blueprints define customized system images by listing packages and customizations that will be part of the system. Blueprints can be edited and they are versioned. When a system image is created from a blueprint, the image is associated with the blueprint in the Image Builder interface of the RHEL 7 web console.

Blueprints are presented to the user as plain text in the Tom's Obvious, Minimal Language (TOML) format.

- **Compose** Composes are individual builds of a system image, based on a particular version of a particular blueprint. Compose as a term refers to the system image, the logs from its creation, inputs, metadata, and the process itself.
- **Customization** Customizations are specifications for the system, which are not packages. This includes user accounts, groups, kernel, timezone, locale, firewall and ssh key.

1.3. IMAGE BUILDER OUTPUT FORMATS

Image Builder can create images in multiple output formats shown in the following table.

表 1.1. Image Builder output formats

Description	CLI name	file extension
QEMU QCOW2 Image	qcow2	.qcow2
Ext4 File System Image	80	.qcow2
Raw Partitioned Disk Image	partitioned-disk	.img
Live Bootable ISO	live-iso	.iso
TAR Archive	tar	.tar

Description	CLI name	file extension
Amazon Machine Image Disk	ami	.ami
VMware Virtual Machine Disk	vmdk	.vmdk
Openstack	openstack	.qcow2


1.4. IMAGE BUILDER SYSTEM REQUIREMENTS

The **lorax** tool underlying Image Builder performs a number of potentially insecure and unsafe actions while creating the system images. For this reason, use a virtual machine to run Image Builder.

The environment where Image Builder runs must meet requirements listed in the following table.

表 1.2. Image Builder system requirements

Parameter	Minimal Required Value
System type	A dedicated virtual machine
Processor	2 cores
Memory	4 GiB
Disk space	20 GiB
Access privileges	Administrator level (root)
Network	Connectivity to Internet



注意

Creating images on virtual machine directly installed on UEFI systems is not supported.

第 2 章 INSTALLING IMAGE BUILDER

Before using Image Builder, you must install Image Builder in a virtual machine.

2.1. INSTALLING IMAGE BUILDER IN A VIRTUAL MACHINE

To install Image Builder on a dedicated virtual machine, follow these steps:

Prerequisites

- Connect to the virtual machine.
- The virtual machine for Image Builder must be installed, subscribed, and running.

Procedure

1. Install the Image Builder and other necessary packages on the virtual machine:

- `lorax-composer`
- `composer-cli`
- `cockpit-composer`
- `bash-completion`

```
# yum install lorax-composer composer-cli cockpit-composer bash-completion
```

2. Enable Image Builder to start after each reboot:

```
# systemctl enable lorax-composer.socket
```

```
# systemctl enable cockpit.socket
```

The **lorax-composer** and **cockpit** services start automatically on first access.

3. Configure the system firewall to allow access to the web console:

```
# firewall-cmd --add-service=cockpit && firewall-cmd --add-service=cockpit --permanent
```

4. Load the shell configuration script so that the auto-complete feature for the **composer-cli** tool starts working immediately without reboot:

```
$ source /etc/bash_completion.d/composer-cli
```

第 3 章 CREATING SYSTEM IMAGES WITH IMAGE BUILDER COMMAND-LINE INTERFACE

Image Builder is a tool for creating custom system images. To control Image Builder and create your custom system images, use the command-line interface which is currently the preferred method to use Image Builder.

3.1. IMAGE BUILDER COMMAND-LINE INTERFACE

Image Builder command-line interface is currently the preferred method to use Image Builder. It offers more functionality than the [第 4 章 *Creating system images with Image Builder web console interface*](#) . To use this interface, run the **composer-cli** tool with suitable options and sub-commands.

The workflow for the command-line interface can be summarized as follows:

1. Export (save) the blueprint definition to a plain text file
2. Edit this file in a text editor
3. Import (push) the blueprint text file back into Image Builder
4. Run a compose to build an image from the blueprint
5. Export the image file to download it

Apart from the basic sub-commands to achieve this procedure, the **composer-cli** tool offers many sub-commands to examine the state of configured blueprints and composes.

To run the **composer-cli** command as a non-root, the user must be in the **weldr** or **root groups**.

3.2. CREATING AN IMAGE BUILDER BLUEPRINT WITH COMMAND-LINE INTERFACE

This procedure describes how to create a new Image Builder blueprint using the command-line interface.

Procedure

1. Create a plain text file with the following contents:

```
name = "BLUEPRINT-NAME"  
description = "LONGER BLUEPRINT DESCRIPTION TEXT"  
version = "0.0.1"
```

Replace **BLUEPRINT-NAME** and **LONGER BLUEPRINT DESCRIPTION** with a name and description for your blueprint.

Replace **0.0.1** with a version number according to the [Semantic Versioning](#) scheme.

2. For every package that you want to be included in the blueprint, add the following lines to the file:

```
[[packages]]  
name = "package-name"  
version = "package-version"
```

Replace **package-name** with name of the package, such as **httpd**, **gdb-doc**, or **coreutils**.

Replace **package-version** with a version to use. This field supports **dnf** version specifications:

- For a specific version, use the exact version number such as **7.30**
- For latest available version, use the asterisk *****
- For a latest minor version, use format such as **7.***.

3. Blueprints can be customized in a number of ways. For example, Simultaneous Multi-Threading (SMT) can be disabled by performing the steps below. For additional customizations available, please see the [第 3.7 节 "Supported Image Customizations"](#) section.

```
[customizations.kernel]
append = "nosmt=force"
```

4. Save the file as **BLUEPRINT-NAME.toml** and close the text editor.

5. Push (import) the blueprint:

```
# composer-cli blueprints push BLUEPRINT-NAME.toml
```

Replace BLUEPRINT-NAME with the value you used in previous steps.

6. To verify that the blueprint has been pushed and exists, list the existing blueprints:

```
# composer-cli blueprints list
```

7. Check whether the components and versions listed in the blueprint and their dependencies are valid:

```
# composer-cli blueprints depsolve BLUEPRINT-NAME
```

3.3. EDITING AN IMAGE BUILDER BLUEPRINT WITH COMMAND-LINE INTERFACE

This procedure describes how to edit an existing Image Builder blueprint in the command-line interface.

Procedure

1. Save (export) the blueprint to a local text file:

```
# composer-cli blueprints save BLUEPRINT-NAME
```

2. Edit the **BLUEPRINT-NAME.toml** file with a text editor of your choice and make your changes.

3. Before finishing the edits, make sure the file is a valid blueprint:

- Remove this line, if present:

```
packages = []
```

- Increase the version number. Remember that Image Builder blueprint versions must use the [Semantic Versioning](#) scheme. Note also that if you do not change the version, the **patch** component of version is increased automatically.
- Check if the contents are valid TOML specifications. See the [TOML documentation](#) for more information.



注意

TOML documentation is a community product and is not supported by Red Hat. You can report any issues with the tool at <https://github.com/toml-lang/toml/issues>

4. Save the file and close the editor.
5. Push (import) the blueprint back into Image Builder:

```
# composer-cli blueprints push BLUEPRINT-NAME.toml
```

Note that you must supply the file name including the **.toml** extension, while in other commands you use only the name of the blueprint.

6. To verify that the contents uploaded to Image Builder match your edits, list the contents of blueprint:

```
# composer-cli blueprints show BLUEPRINT-NAME
```

7. Check whether the components and versions listed in the blueprint and their dependencies are valid:

```
# composer-cli blueprints depsolve BLUEPRINT-NAME
```

3.4. CREATING A SYSTEM IMAGE WITH IMAGE BUILDER IN THE COMMAND-LINE INTERFACE

This procedure describes how to edit an existing Image Builder blueprint in the command-line interface.

Prerequisites

- You have a blueprint prepared for the image.

Procedure

1. Start the compose:

```
# composer-cli compose start BLUEPRINT-NAME IMAGE-TYPE
```

Replace *BLUEPRINT-NAME* with name of the blueprint, and *IMAGE-TYPE* with the type of image. For possible values, see output of the **composer-cli compose types** command.

The compose process starts in the background and the UUID of the compose is shown.

2. Wait until the compose is finished. Please, notice that this may take several minutes.

To check the status of the compose:

```
# composer-cli compose status
```

A finished compose shows a status value **FINISHED**. Identify the compose in the list by its UUID.

3. Once the compose is finished, download the resulting image file:

```
# composer-cli compose image UUID
```

Replace *UUID* with the UUID value shown in the previous steps.

Alternatively, you can access the image file directly under the path **/var/lib/lorax/composer/results/UUID/**.

You can also download the logs using the **composer-cli compose logs UUID** command, or the metadata using the **composer-cli compose metadata UUID** command.

3.5. BASIC IMAGE BUILDER COMMAND-LINE COMMANDS

The Image Builder command-line interface offers the following sub-commands.

Blueprint manipulation

List all available blueprints

```
# composer-cli blueprints list
```

Show a blueprint contents in the TOML format

```
# composer-cli blueprints show BLUEPRINT-NAME
```

Save (export) blueprint contents in the TOML format into a file *BLUEPRINT-NAME.toml*

```
# composer-cli blueprints save BLUEPRINT-NAME
```

Remove a blueprint

```
# composer-cli blueprints delete BLUEPRINT-NAME
```

Push (import) a blueprint file in the TOML format into Image Builder

```
# composer-cli blueprints push BLUEPRINT-NAME
```

Composing images from blueprints

Start a compose

```
# composer-cli compose start BLUEPRINT COMPOSE-TYPE
```

Replace *BLUEPRINT* with name of the blueprint to build and *COMPOSE-TYPE* with the output image type.

List all composes

```
■
```

```
# composer-cli compose list
```

Cancel a running compose

```
# composer-cli compose cancel COMPOSE-UUID
```

Delete a finished compose

```
# composer-cli compose delete COMPOSE-UUID
```

Show detailed information about a compose

```
# composer-cli compose info COMPOSE-UUID
```

Download image file of a compose

```
# composer-cli compose image COMPOSE-UUID
```

Related information

- The **composer-cli(1)** manual page provides a full list of the available sub-commands and options:

```
$ man composer-cli
```

- The **composer-cli** tool provides help on the sub-commands and options:

```
# composer-cli compose list
```

3.6. IMAGE BUILDER BLUEPRINT FORMAT

Image Builder blueprints are stored as plain text in the Tom's Obvious, Minimal Language (TOML) format.

The elements of a typical blueprint file include:

The blueprint metadata

```
name = "BLUEPRINT-NAME"  
description = "LONGER BLUEPRINT DESCRIPTION"  
version = "VERSION"  
modules = []  
groups = []
```

Replace *BLUEPRINT-NAME* and *LONG FORM DESCRIPTION TEXT* with a name and description for your blueprint.

Replace *VERSION* with a version number according to the [Semantic Versioning](#) scheme.

This part is present only once for the whole blueprint file.

The entry *modules* describe the package names and matching version glob to be installed into the image and the entry *group* describe a group of packages to be installed into the image. If you do not add these items, the blueprint indentify them as an empty lists.

Packages included in the image

```
[[packages]]
name = "package-name"
version = "package-version"
```

Replace ***package-name*** with name of the package, such as **httpd**, **gdb-doc**, or **coreutils**.

Replace ***package-version*** with a version to use. This field supports **dnf** version specifications:

- For a specific version, use the exact version number such as **7.30**.
- For latest available version, use the asterisk *****.
- For a latest minor version, use format such as **7.***.

Repeat this block for every package to be included.

3.7. SUPPORTED IMAGE CUSTOMIZATIONS

A number of image customizations are supported in blueprints. In order to make use of these options, you need to initially configure them in the blueprint and then use the command `push` to import the modified blueprint to Image Builder.



注意

These customizations are not currently supported in the accompanying `cockpit-composer` GUI.`

Set the image host name

```
[customizations]
hostname = "baseimage"
```

User specifications for the resulting system image

```
[[customizations.user]]
name = "USER-NAME"
description = "USER-DESCRIPTION"
password = "PASSWORD-HASH"
key = "PUBLIC-SSH-KEY"
home = "/home"/USER-NAME/"
shell = "/usr/bin/bash"
groups = ["users", "wheel"]
uid = NUMBER
gid = NUMBER
```

Only the user name is required, you can leave out any other lines.

Replace `PASSWORD-HASH` with the actual password hash. To generate the hash, use a command such as:

```
$ python3 -c 'import crypt,getpass;pw=getpass.getpass();print(crypt.crypt(pw) if
(pw==getpass.getpass("Confirm: ")) else exit()'
```



重要

To generate the hash, you must have the **python3** package on your system. Use the following command to install the package:

```
# yum install python3
```

Replace `PUBLIC-SSH-KEY` with the actual public key.

Repeat this block for every user you want to include.

Group specifications for the resulting system image

```
[[customizations.group]]
name = "GROUP-NAME"
gid = NUMBER
```

Repeat this block for every group you want to include.

Set an existing user's ssh key

```
[[customizations.sshkey]]
user = "root"
key = "PUBLIC-SSH-KEY"
```



注意

This option is only applicable for existing users. To create a user and set an ssh key, use the User specifications for the resulting system image customization.

Append a kernel boot parameter option to the defaults

```
[[customizations.kernel]]
append = "KERNEL-OPTION"
```

Set the image host name

```
[customizations]
hostname = "BASE-IMAGE"
```

Add a group for the resulting system image


```
[[customizations.group]]  
name = "USER-NAME"  
gid = NUMBER
```

Only the name is required and GID is optional.

Set the timezone and the *Network Time Protocol* (NTP) servers for the resulting system image

```
[customizations.timezone]  
timezone = "TIMEZONE"  
ntpservers = NTP-SERVER
```

If you do not set a timezone, the system uses *Universal Time, Coordinated* (UTC) as default. Setting NTP servers is optional.

Set the locale settings for the resulting system image

```
[customizations.locale]  
language = "[LANGUAGE]"  
keyboard = "KEYBOARD"
```

Setting both language and keyboard options is mandatory. You can add multiple languages. The first language you add will be the primary language and the other languages will be secondary.

Set the firewall for the resulting system image

```
[customizations.firewall]  
port = "[PORTS]"
```

You can use the numeric ports, or theirs names from the `/etc/services` file to enable or disable lists.


Set which services to enable during the boot time

```
[customizations.services]  
enabled = "[SERVICES]"  
disabled = "[SERVICES]"
```

You can control which services to enable during the boot time. Some image types already have services enabled or disabled so that the image works correctly and this setup cannot be overridden.

第 4 章 CREATING SYSTEM IMAGES WITH IMAGE BUILDER WEB CONSOLE INTERFACE

Image Builder is a tool for creating custom system images. To use Image Builder and create your custom system images, you can use the web console interface. Note that the command-line interface is the currently preferred alternative, because it offers more features.



注意

The command-line interface is the currently preferred alternative, because it offers more features.

4.1. ACCESSING IMAGE BUILDER GUI IN THE RHEL 7 WEB CONSOLE

The `cockpit-composer` plug-in for the RHEL 7 web console enables users to manage Image Builder blueprints and composes with a graphical interface. Note that the preferred method for controlling Image Builder is at the moment using the command-line interface.


Prerequisites

- You must have root access to the system.

Procedure

- Open <https://localhost:9090/> in a web browser on the system where Image Builder is installed.

图 4.1. Log into the web console



[D]


For more information on how to remotely access Image Builder, see [managing systems using the RHEL 7 web console](#).

- Log into the web console with your root username and password.

3. To display the Image Builder controls, click the Image Builder icon, which is in the upper-left corner of the window.

The Image Builder view opens, listing existing blueprints.

图 4.2. Image Builder on Web Console



[D]

Related information

- [第 3 章 *Creating system images with Image Builder command-line interface*](#)
- You will be able to create customized RHEL OS images using [Image Builder scenario](#)

4.2. CREATING AN IMAGE BUILDER BLUEPRINT IN THE WEB CONSOLE INTERFACE

To describe the customized system image, create a blueprint first.


Prerequisites

- You have opened the Image Builder interface of the RHEL 7 web console in a browser.

Procedure

1. Click **Create Blueprint** in the top right corner.

图 4.3. Creating a Blueprint



A pop-up appears with fields for the blueprint **name** and **description**.


2. Fill in the name of the blueprint, its description, then click Create.

The screen changes to **blueprint editing mode**.

3. Add **components** that you want to include in the system image:

- i. On the left, enter all or part of the component name in the **Available Components** field and press Enter.

图 4.4. Searching for Available Componentes



The search is added to the list of filters under the text entry field, and the list of components below is reduced to these that match the search.

If the list of components is too long, add further search terms in the same way.

- ii. The list of components is paged. To move to other result pages, use the arrows and entry field above the component list.
- iii. Click on name of the component you intend to use to display its details. The right pane fills with details of the components, such as its version and dependencies.
- iv. Select the version you want to use in the Component Options box, with the Version Release dropdown.

- v. Click **Add** in the top left.
- vi. If you added a component by mistake, remove it by clicking the ... button at the far right of its entry in the right pane, and select **Remove** in the menu.



注意

If you do not intend to select version for some components, you can skip the component details screen and version selection by clicking the **+** buttons on the right side of the component list.

4. To save the blueprint, click **Commit** in the top right. A dialog with a summary of the changes pops up. Click **Commit**.

A small pop-up on the right informs you of the saving progress and then the result.

5. To exit the editing screen, click **Back to Blueprints** in the top left.

The Image Builder view opens, listing existing blueprints.

4.3. EDITING AN IMAGE BUILDER BLUEPRINT IN THE WEB CONSOLE INTERFACE

To change the specifications for a custom system image, edit the corresponding blueprint.

Prerequisites

- You have opened the Image Builder interface of the RHEL 7 web console in a browser.
- A blueprint exists.

Procedure

1. Locate the blueprint that you want to edit by entering its name or a part of it into the search box at top left, and press **Enter**.

The search is added to the list of filters under the text entry field, and the list of blueprints below is reduced to these that match the search.

If the list of blueprints is too long, add further search terms in the same way.

2. On the right side of the blueprint, press the Edit Blueprint button that belongs to the blueprint.

The view changes to the blueprint editing screen.

3. Remove unwanted components by clicking the ... button at the far right of its entry in the right pane, and select **Remove** in the menu.

4. Change version of existing components:

- i. On the Blueprint Components search field, enter component name or a part of it into the field under the heading **Blueprint Components** and press **Enter**.

The search is added to the list of filters under the text entry field, and the list of components below is reduced to these that match the search.

If the list of components is too long, add further search terms in the same way.

- ii. Click the  button at the far right of the component entry, and select **View** in the menu.

A component details screen opens in the right pane.

- iii. Select the desired version in the **Version Release** drop-down menu and click **Apply Change** in top right.


The change is saved and the right pane returns to listing the blueprint components.

5. Add new components:

- i. On the left, enter component name or a part of it into the field under the heading Available Components and press Enter.

The search is added to the list of filters under the text entry field, and the list of components below is reduced to these that match the search.

If the list of components is too long, add further search terms in the same way.

- ii. The list of components is paged. To move to other result pages, use the arrows and entry field above the component list.
- iii. Click on the name of the component you intend to use to display its details. The right pane fills with details of the components, such as its version and dependencies.
- iv. Select the version you want to use in the **Component Options** box, with the **Version Release** drop-down menu.
- v. Click **Add** in the top right.
- vi. If you added a component by mistake, remove it by clicking the  button at the far right of its entry in the right pane, and select **Remove** in the menu.



注意

If you do not intend to select version for some components, you can skip the component details screen and version selection by clicking the **+** buttons on the right side of the component list.

1. Commit a new version of the blueprint with your changes:

- i. Click the Commit button in top right.

A pop-up window with a summary of your changes appears.

- ii. Review your changes and confirm them by clicking Commit.

A small pop-up on the right informs you of the saving progress and then result. A new version of the blueprint is created.

- iii. In the top left, click **Back to Blueprints** to exit the editing screen.

The Image Builder view opens, listing existing blueprints.

4.4. ADDING USERS AND GROUPS TO AN IMAGE BUILDER BLUEPRINT IN THE WEB CONSOLE INTERFACE

Adding customizations such as users and groups to blueprints in the web console interface is currently not possible. To work around this limitation, use the **Terminal** tab in web console to use the command-line interface (CLI) workflow.

Prerequisites

- A blueprint must exist.
- A CLI text editor such as **vim**, **nano**, or **emacs** must be installed. To install them:

```
# yum install editor-name
```

Procedure

1. Find out the name of the blueprint: Open the Image Builder (**Image builder**) tab on the left in the RHEL 7 web console to see the name of the blueprint.

2. Navigate to the CLI in web console: Open the system administration tab on the left, then select the last item **Terminal** from the list on the left.

3. Enter the super-user (root) mode:

```
$ sudo bash
```

Provide your credentials when asked. Note that the terminal does not reuse your credentials you entered when logging into the web console.

A new shell with root privileges starts in your home directory.

4. Export the blueprint to a file:

```
# composer-cli blueprints save BLUEPRINT-NAME
```

5. Edit the file *BLUEPRINT-NAME.toml* with a CLI text editor of your choice and add the users and groups.



重要

RHEL 7 web console does not have any built-in feature to edit text files on the system, so the use of a CLI text editor is required for this step.

- i. For every user to be added, add this block to the file:

```
[[customization.user]]
name = "USER-NAME"
description = "USER-DESCRIPTION"
password = "PASSWORD-HASH"
key = "ssh-rsa (...) key-name"
home = "/home/USER-NAME"
shell = "/usr/bin/bash"
groups = ["users", "wheel"]
uid = NUMBER
gid = NUMBER
```

Replace PASSWORD-HASH with the actual password hash. To generate the hash, use a command such as this:

```
$ python3 -c 'import crypt,getpass;pw=getpass.getpass();print(crypt.crypt(pw) if
(pw==getpass.getpass("Confirm: ")) else exit()'
```

Replace ssh-rsa (...) key-name with the actual public key.

Replace the other placeholders with suitable values.

Leave out any of the lines as needed, only the user name is required.

- ii. For every user group to be added, add this block to the file:

```
[[customizations.group]]
name = "GROUP-NAME"
gid = NUMBER
```

iii. Increase the version number.

iv. Save the file and close the editor.

- 6. Import the blueprint back into Image Builder:

```
# composer-cli blueprints push BLUEPRINT-NAME.toml
```

Note that you must supply the file name including the **.toml** extension, while in other commands you use only the name of the blueprint.

- 7. To verify that the contents uploaded to Image Builder match your edits, list the contents of blueprint:

```
# composer-cli blueprints show BLUEPRINT-NAME
```

Check if the version matches what you put in the file and if your customizations are present.



重要

The Image Builder plug-in for RHEL 7 web console does not show any information that could be used to verify that the changes have been applied, unless you edited also the packages included in the blueprint.

- 8. Exit the privileged shell:

```
# exit
```

- 9. Open the Image Builder (Image builder) tab on the left and refresh the page, in all browsers and all tabs where it was opened.

This prevents state cached in the loaded page from accidentally reverting your changes.

Additional information

- [第 3.6 节 “Image Builder blueprint format”](#)

- [第 3.3 节 “Editing an Image Builder blueprint with command-line interface”](#)

4.5. CREATING A SYSTEM IMAGE WITH IMAGE BUILDER IN THE WEB CONSOLE INTERFACE

The following steps below describe creating a system image.

Prerequisites

- You have opened the Image Builder interface of the RHEL 7 web console in a browser.
- A blueprint exists.

Procedure

1. Locate the blueprint that you want to build an image by entering its name or a part of it into the search box at top left, and press **Enter**.

The search is added to the list of filters under the text entry field, and the list of blueprints below is reduced to these that match the search.

If the list of blueprints is too long, add further search terms in the same way.

2. On the right side of the blueprint, press the Create Image button that belongs to the blueprint.

A pop-up window appears.

3. Select the image type and architecture and press Create.

A small pop-up in the top right informs you that the image creation has been added to the queue.

4. Click the name of the blueprint.

A screen with details of the blueprint opens.

5. Click the Images tab to switch to it. The image that is being created is listed with the status In Progress.



重要

Image creation takes a longer time, measured in minutes. There is no indication of progress while the image is created.

To abort image creation, press its Stop button on the right.

6. Once the image is successfully created, the Stop button is replaced by a Download button. Click this button to download the image to your system.

第 5 章 DEPLOYING CLOUD IMAGES WITH IMAGE BUILDER

Image Builder can create custom system images ready for use in clouds of various providers. To use your customized RHEL system image in a cloud, create the system image with Image Builder using the respective output type, configure your system for uploading the image, and upload the image to your cloud account.

5.1. PREPARING AWS AMI IMAGES FOR UPLOAD

This section describes steps to configure a system for uploading AWS AMI images.

Prerequisites

- You must have an Access Key ID configured in the [AWS IAM account manager](#).
- You must have a writable [S3 bucket](#) prepared.

Procedure

1. Install Python 3 and the **pip** tool:

```
# yum install python3 python3-pip
```

2. Install the AWS command-line tools with pip:

```
# pip3 install awscli
```

3. Configure the AWS command-line client according to your AWS access details:

```
$ aws configure AWS Access Key ID [None]: AWS Secret Access Key [None]: Default region name [None]: Default output format [None]:
```

4. Configure the AWS command-line client to use your bucket:

```
$ BUCKET=bucketname
```

```
$ aws s3 mb s3://$BUCKET
```

Replace *bucketname* with the actual bucket name.

5. Create a **vmimport** S3 Role in IAM and grant it permissions to access S3, if you have not already done so:

```
$ printf '{ "Version": "2012-10-17", "Statement": [ { "Effect": "Allow", "Principal": { "Service": "vmie.amazonaws.com" }, "Action": "sts:AssumeRole", "Condition": { "StringEquals": { "sts:Externalid": "vmimport" } } } ] }' > trust-policy.json $ printf '{ "Version": "2012-10-17", "Statement": [ { "Effect": "Allow", "Action": [ "s3:GetBucketLocation", "s3:GetObject", "s3:ListBucket" ], "Resource": [ "arn:aws:s3:::%s", "arn:aws:s3:::%s/*" ] }, { "Effect": "Allow", "Action": [ "ec2:ModifySnapshotAttribute", "ec2:CopySnapshot", "ec2:RegisterImage", "ec2:Describe*" ], "Resource": "*" } ] }' $BUCKET $BUCKET > role-policy.json $ aws iam create-role --role-name vmimport --assume-role-policy-document file://trust-policy.json $ aws iam put-role-policy --role-name vmimport --policy-name vmimport --policy-document file://role-policy.json
```

5.2. UPLOADING AN AMI IMAGE TO AWS

This section describes how to upload an AMI image to AWS.

Prerequisites

- Your system must be set up for uploading AWS images.
- You must have an AWS image created by Image Builder. Use the **ami** output type in CLI or **Amazon Machine Image Disk (.ami)** in GUI when creating the image.

Procedure

1. Push the image to S3:

```
$ $ AMI=8db1b463-91ee-4fd9-8065-938924398428-disk.ami
```

```
$ aws s3 cp $AMI s3://$BUCKET Completed 24.2 MiB/4.4 GiB (2.5 MiB/s) with 1 file(s) remaining ...
```

2. After the upload to S3 ends, import the image as a snapshot into EC2:

```
$ A printf '{ "Description": "my-image", "Format": "raw", "UserBucket": { "S3Bucket": "%s", "S3Key": "%s" } }' $BUCKET $AMI > containers.json
```

```
$ aws ec2 import-snapshot disk-container file://containers.json
```


Replace *my-image* with the name of the image.

To track progress of the import, run:

```
$ aws ec2 describe-import-snapshot-tasks --filters Name=task-state,Values=active
```


3. Create an image from the uploaded snapshot by selecting the snapshot in the EC2 console, right clicking on it and selecting Create Image:

图 5.1. Create Image



4. Select the Virtualization type of Hardware-assisted virtualization in the image you create:


图 5.2. Virtualization type



5. Now you can run an instance using whatever mechanism you like (CLI or AWS Console) from the snapshot. Use your private key via SSH to access the resulting EC2 instance. Log in as `ec2-user`.

5.3. UPLOADING VMDK IMAGES TO VSPHERE

Image Builder can generate images suitable for uploading to a VMware ESXi or vSphere system. This section describes steps to upload an VMDK image to VMware vSphere.



注意

Because VMware deployments typically do not have cloud-init configured to inject user credentials to virtual machines, you have to perform that task yourself on the blueprint.

Prerequisites


- You must have an VMDK image created by Image Builder. Use the `vmdk` output type in CLI or VMware Virtual Machine Disk (`.vmdk`) in GUI when creating the image.

Procedure

1. Upload the image into vSphere via HTTP. Click on Upload Files in the vCenter:

2. When you create a VM, on the Device Configuration, delete the default New Hard Disk and use the drop-down to select an Existing Hard Disk disk image:

图 5.3. Virtualization type



3. Make sure you use an IDE device as the Virtual Device Node for the disk you create. The default **SCSI** value results in an unbootable virtual machine.

图 5.4. Virtualization type

New Virtual Machine	
✓ 1 Select a creation type	✓ 2 Select a name and folder
✓ 3 Select a compute resource	✓ 4 Select storage
✓ 5 Select compatibility	✓ 6 Select a guest OS
7 Customize hardware	8 Ready to complete
▼ New Hard disk *	3.35546875 GB
Maximum Size	N/A
VM storage policy	Datastore Default
Sharing	Unspecified
Disk File	[NFS-Synology-1- composer/55070ff6-d637-40fe- 80f9-9518f2ee0f21-disk.vmdk
Shares	Normal 1000
Limit - IOPs	Unlimited
Virtual flash read cache	0 MB
Disk Mode	Dependent
Virtual Device Node	IDE 0

CANCEL BACK NEXT

5.4. UPLOADING QCOW2 IMAGE TO OPENSTACK

Image Builder can generate images suitable for uploading to OpenStack cloud deployments, and starting instances there. This describes steps to upload a QCOW2 image to OpenStack.

Prerequisites

- You must have an OpenStack-specific image created by Image Builder. Use the openstack output type in CLI or OpenStack Image (.qcow2) in GUI when creating the image.




警告

Image Builder also offers a generic QCOW2 image type output format as qcow2 or QEMU QCOW2 Image (.qcow2). Do not mistake it with the OpenStack image type which is also in the QCOW2 format, but contains further changes specific to OpenStack.

Procedure

- Upload the image to OpenStack and start an instance from it. Use the Images interface to do this:

图 5.5. Virtualization type



Create An Image ✕

Name: *
96268ffb-2c71-4e97-a855-7ac25e983a6e-disk.qcow2

Description:

Image Source:
Image File

Image File
Browse... 96268ffb-2c71-4e97-a85...c25e98

Format: *
QCOW2 - QEMU Emulator

Architecture:
x86_64

Minimum Disk (GB):
5

Minimum Ram (MB):
1024

Public:

Protected:

Cancel Create Image

Description:
Specify an image to upload to the Image Service.
Currently only images available via an HTTP URL are supported. The image location must be accessible to the Image Service. Compressed image binaries are supported (.zip and .tar.gz.)
Please note: The Image Location field MUST be a valid and direct URL to the image binary. URLs that redirect or serve error pages will result in unusable images.

2. Start an instance with that image:

图 5.6. Virtualization type

Launch Instance ✕

Details *
Access & Security *
Networking *
Post-Creation
Advanced Options

Availability Zone:
nova

Instance Name: *
my-instance

Flavor: *
m1.small

Some flavors not meeting minimum image requirements have been disabled.

Instance Count: *
1

Instance Boot Source: *
Boot from image

Image Name:
96268ffb-2c71-4e97-a855-7ac25e983a6e-disk.qc


Specify the details for launching an instance.


The chart below shows the resources used by this project in relation to the project's quotas.


Flavor Details

Name	m1.small
VCPUs	1
Root Disk	20 GB
Ephemeral Disk	0 GB
Total Disk	20 GB
RAM	2,048 MB

Project Limits

Number of Instances 4 of 10 Used


Number of VCPUs 17 of 20 Used


Total RAM 34,816 of 51,200 MB Used


Cancel
Launch

3. You can run the instance using any mechanism (CLI or OpenStack web UI) from the snapshot. Use your private key via SSH to access the resulting instance. Log in as cloud-user.

附录 A. REVISION HISTORY

修订 1.1.0-	Tue Aug 06 2019	Eliane Pereira
修订 1.0.0-	Thu Jul 11 2019	Eliane Pereira
Composer has been splitted to its own guide and it is now available.		
修订 0.0-0	Sun Jun 2 2019	Eliane Pereira
Preparing document for 7.7 GA publication.		